

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

WEST QUARTER Corner of Section 30, Township 40, Range 25, 4TH P.M.

STATE OF MINNESOTA, County of KANABEC

At the corner location shown on the sketch:  
SET A #7 REBAR WITH AN ALUMINUM CAP.

Kanabec County U.S. Survey Feet Coordinates  
NAD 1983, HARN 1996 Adjustment  
Obtained by RTK GPS Observation

Northing= 173420.93

Easting= 342607.06

Note: NAD 1983, HARN 1996 Adjustment  
coordinates are NOT compatible with  
NAD 1983 coordinates

Note: 1 Meter=3937/1200 U.S. Survey Feet

## SKETCH OF REFERENCE TIES



SPIKE IN EAST FACE  
OF 12" TWIN OAK



8.61  
NORTH



S50°E  
14.33



SPIKE IN SW FACE  
OF 10" TWIN MAPLE

S20°W  
27.54



Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data  
contained herein was prepared by me or under  
my direct supervision.

  
Signature

12-21-2010  
Date

Registration No. 9808

Land Surveyor,  Professional Engineer

County Surveyor,  County Engineer

## OFFICE OF THE COUNTY RECORDER

County of \_\_\_\_\_

I hereby certify that this document was filed in  
the County Recorder's office at \_\_\_\_\_ M. on the

\_\_\_\_\_ day of \_\_\_\_\_ A.D., 20\_\_\_\_

County Recorder \_\_\_\_\_

BY \_\_\_\_\_ Deputy

DOCUMENT NO. \_\_\_\_\_

W1/4 CORNER, SEC. 30, T40, R25

**STATEMENT OF EVIDENCE**

**THE WEST LINE OF T.40, R.25 WAS RUN BY DEPUTY SURVEYOR THEO CONKEY IN DEC. 1849. WE WERE UNABLE TO FIND ANY REMNANTS OF HIS MONUMENT OR ACCESSORIES FOR THIS CORNER.**

**THERE ARE NO "OLD SURVEY" RECORDS ON FILE WITH THOSE KEPT IN THE SURVEY RECORDS BOOK NOW IN THE VAULT AT THE COUNTY HIGHWAY DEPARTMENT.**

**NO ARE NO OTHER SUBSEQUENT SURVEYS THAT WE ARE AWARE OF.**

**ON DEC. 2, 2010 E.G. RUD AND SONS, INC. SET A #7 REBAR WITH AN ALUMINUM CAP ON LINE AND EQUIDISTANT FROM THE NW AND SW CORNER OF SAID SEC. 30, TIES WERE TAKEN AND KANABEC COUNTY COORDINATES WERE ESTABLISHED ON THIS POSITION.**