

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

EAST QUARTER Corner of Section 30, Township 40, Range 25, 4TH P.M.  
STATE OF MINNESOTA, County of KANABEC

At the corner location shown on the sketch:  
SET A #7 REBAR WITH AN ALUMINUM CAP

Kanabec County U.S. Survey Feet Coordinates  
NAD 1983, HARN 1996 Adjustment  
Obtained by RTK GPS Observation

Northing= 173166.76  
Easting= 348127.86

Note: NAD 1983, HARN 1996 Adjustment  
coordinates are NOT compatible with  
NAD 1983 coordinates

Note: 1 Meter=3937/1200 U.S. Survey Feet

## SKETCH OF REFERENCE TIES



SPIKE IN WEST FACE  
OF 12" POPLAR

N5°E  
10.08

PASTURE

WOODED

BARBED WIRE FENCE

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data  
contained herein was prepared by me or under  
my direct supervision.

Ernst W. Rud 12-21-2010  
Signature Date

Registration No. 9808

Land Surveyor,  Professional Engineer  
 County Surveyor,  County Engineer

## OFFICE OF THE COUNTY RECORDER

County of \_\_\_\_\_

I hereby certify that this document was filed in  
the County Recorder's office at \_\_\_\_\_ M. on the

\_\_\_\_\_ day of \_\_\_\_\_ A.D., 20\_\_\_\_

County Recorder \_\_\_\_\_

BY \_\_\_\_\_ Deputy

DOCUMENT NO. \_\_\_\_\_

E1/4 CORNER, SEC. 30, T40, R25

**STATEMENT OF EVIDENCE**

THE ORIGINAL CORNER WAS SET ON NOV. 12, 1855 BY DEPUTY SURVEYOR SILAS BARNARD AND 2 BEARING TREES NOTED AS:

10" YELLOW BIRCH @ 15 LINKS BEARING S44°W  
12" BLACK ASH @ 25 LINKS BEARING EAST

NO VISIBLE EVIDENCE REMAINS TODAY FOR THE CORNER OR THE BEARING TREES.

THERE IS A ROAD OPENING ON FILE ALONG THE EAST LINE OF SEC. 30 DATED JULY 5, 1905 AND A SURVEY BY VICKERY WHO MEASURED THIS LINE TO BE 78.6 CHAINS OR 5187.6 FEET.

THE KANABEC COUNTY HWY DEPT RAN THIS LINE IN 1914 AND MEASURED IT TO BE 5221 FEET BUT NO TIES OR TYPE OF MONUMENTS WERE DOCUMENT IN THE NOTES.

TODAY WE MEASURE THIS LINE TO BE 5183.75 FEET. TESTIMONY FROM KEN MONSON (OWNER OF E1/2 OF SEC. 30) AND DAN WEBER (OWNER OF W1/2 OF SEC. 29) BOTH THOUGHT FENCE LINE IN PLACE WAS SECTION LINE. THIS CORNER WAS TREATED AS LOST AND SET ON LINE AND SPLIT BETWEEN THE NE AND SE CORNERS OF SEC. 30. THIS FELL 4 FEET WEST OF THE FENCE.

A #7 REBAR WITH AN ALUMINUM CAP WAS SET, TIES WERE TAKEN AND KANABEC COUNTY COORDINATES WERE ESTABLISHED ON THIS POSITION.