

EAST QUARTER CORNER SECTION 06, T39, R24

STATEMENT OF EVIDENCE

THE ORIGINAL CORNER WAS SET BY DEPUTY SURVEYOR SILAS BARNARD IN OCTOBER 5, 1855 AND TWO BEARING TREES ESTABLISHED – NO VISIBLE EVIDENCE REMAINS FOR THE CORNER OR BEARING TREE.

IN BOOK A1 OF SURVEYS PAGE 56 AND 57 THERE IS AN UNDATED SURVEY RECORDED BY CHARLES HANDSCHU FOR THE NORTH HALF OF SECTION 5. HE NOTED A ROCK WITH X FOR THE NORTHEAST CORNER OF SECTION 6 AND A CIRCLE FOR THE EAST QUARTER CORNER WITH NOTHING EXPLAINING WHAT IT WAS. HE MEASURED A DISTANCE OF 2675 FEET FOR THE EAST LINE OF THE NORTHEAST QUARTER OF SECTION 6.

ON OCTOBER 22, 2007 E.G. RUD AND SONS RAN A SURVEY AROUND SECTION 6 TO LOCATE EXISTING MONUMENTS, LINES OF OCCUPATION AND DETERMINE SEARCH AREAS. THIS CORNER FALLS ON THE CENTERLINE OF A NORTH SOUTH ROAD WITH NO EAST OR WEST OCCUPATION.

ON OCTOBER 29, 2007 AN EXCAVATION WITH THE COUNTY BACKHOE WAS MADE ON THE PRORATED DISTANCE BETWEEN THE NORTHEAST AND SOUTHEAST CORNERS OF SECTION 6. THE PRORATED DISTANCE FOR THE EAST LINE OF NORTHEAST QUARTER WAS 2673.4 WHICH COMPARED WELL WITH HANDSCHU'S MEASUREMENT OF 2675 FEET. THE EXCAVATION WAS 12' EAST-WEST, AND 20' NORTH-SOUTH AND 1 FOOT INTO NATURAL GROUND. A POINTED ROCK WAS FOUND AND NO OTHER EVIDENCE WAS FOUND. THEREFORE THE CORNER WAS SET ON A PRO-RATED DISTANCE FROM THE NORTHEAST CORNER TO THE SOUTHEAST CORNER OF SECTION 6. A #7 REBAR WITH AN ALUMINUM CAP WAS SET, TIES TAKEN, AND KANABEC COUNTY COORDINATES ESTABLISHED ON THIS POSITION.