

N1/4 CORNER, SEC. 10, T39, R23

STATEMENT OF EVIDENCE

THE ORIGINAL CORNER WAS SET ON SEPTEMBER 8, 1855 BY U.S. DEPUTY SURVEYOR SILAS BARNARD AND 2 BEARING TREES NOTED AS:

**10" ELM @ 25 LINKS BEARING S43°W
10" ELM @ 20 LINKS BEARING N45°E**

NO VISIBLE EVIDENCE COULD BE FOUND FOR THE ORIGINAL CORNER OR BEARING TREES.

IN BOOK 2 OF 2 OF SURVEYS, PAGE 6, JOHN NELSON RECORDED A SURVEY OF SEC. 10 DATED DECEMBER 26, 1901. HE SET A POST AT THE N1/4 CORNER OF SEC. 10 WITH 16" TAMARACK BEARING S25°W @ 0.44 CHAINS. THIS WAS SET EQUIDISTANT BETWEEN THE NW AND NE CORNERS OF SEC. 10. A SEARCH WAS MADE FOR THE POST AND BEARING TREE BUT NO EVIDENCE COULD BE FOUND.

ON OCTOBER 16, 2003, E.G. RUD AND SONS DID A SURVEY AROUND SEC. 3 AND THIS CORNER FALLS ON AN EAST-WEST FENCE LINE WITH NO OCCUPATION LINES RUNNING NORTH-SOUTH. A COMPUTED POSITION FOR A LINE AND SPLIT FELL RIGHT ON THE EAST-WEST FENCE LINE SO A #7 REBAR WITH ALUMINUM CAP WAS SET BY LOST METHODS. KANABEC COUNTY COORDINATES WERE ESTABLISHED ON THIS POSITION.