

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Northeast Corner of Section 32, Township 39 North, Range 23 West,
4th Principal Meridian, Kanabec County, State of Minnesota

At the corner location shown on the sketch:
Found a 2" Iron Pin at the centerline intersection.

Kanabec County U.S. Survey Feet Coordinates
NAD 1983, HARN 1996 Adjustment
Obtained by RTK GPS observation
Northing: 137232.3131
Easting: 417071.3215

Note: NAD 1983, HARN 1996 Adjustment
coordinates are NOT compatible with
NAD 1983 coordinates
Note: 1 Meter = 3937/1200 U.S. Survey Feet

SKETCH OF REFERENCE TIES

NOT TO SCALE

KROSCHEL LAND SURVEYORS, INC.
ASSUMES NO LIABILITY FOR THE ACCURACY
OF THE GPS COORDINATES SHOWN HEREON.
ALL COORDINATES AND DIMENSIONS
SHOULD BE FIELD VERIFIED BY THE USER.



SECTION 29

3" IRONWOOD
SET NAIL IN SW FACE

80.15

OLYMPIC STREET

109.3 (1962)
109.52

OLD
SCHOOL

SECTION 28

SW FACE OF WELL PIPE

70.48
70.5 (1925)

CL OF

170TH AVENUE

CL OF

SECTION 32

SECTION 33




Kroschel Land Surveyors, Inc.

1639 Main Street North, Suite 6, Pine City, MN 55063
Phone: 320-629-3267 Fax: 320-629-0176

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision, that the United States public land survey monument record is correct and complete to the best of my knowledge and belief, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.


Tyler J. Kroschel
License No. 44490
 Land Surveyor County Surveyor
Date 1-14-2014

OFFICE OF THE COUNTY RECORDER

County of Kanabec

I hereby certify that this document was filed in the County Recorder's office at _____ .M. on the _____ day of _____ A.D., 20____
County Recorder _____
By _____, Deputy
DOCUMENT NO. _____

114/50

Statement of Evidence:

In August of 1855 Deputy Surveyor Silas Barnard set a post to mark the Northeast corner of Section 32, Township 39 North, Range 23 West of the 4th Principal Meridian.

All of the original Government evidence was searched for. None was found.

1895—Thomas Vickery made a survey around Section 28. He does not state what type of monument was in place at the Southwest corner of Section 28.

1900—Thomas Vickery made a survey along the west line of Section 28. He does not state what type of monument was in place at the Southwest corner of Section 28.

1901—County Surveyor John Nelson made a survey around Section 29. He found a "stake drove by former surveyor" at the Southeast corner of Section 29.

1903—County Surveyor John Nelson made a survey around Section 28. He states "the west boundary line of this section having been previously established". He placed a stone at the Southwest corner of Section 28.

1912—County Surveyor John Nelson made a survey in Section 29. He set Sandstone monuments at the interior 40 corners in Section 29.

1925—County Surveyor George Jenks filed a corner certificate for the Southwest corner of Section 28. The corner was evidenced by an old post which was replaced by a Sandstone marked "x". He established ties.

1937—County Surveyor Frank Turnacliiff, RLS 1918 filed a corner certificate for the Northwest corner of Section 33. He found a Sandstone marked "x" and established ties.

1962—Kanbec County Highway crew consisting of Ralph Fairbanks, Marvin Lorenz and Don Nelson dug from old ties and found a Rock with "x" 20" under the road bed. They place an I.P. directly over the "x" and established ties. They recorded a distance of 10,683.7 feet to the Northeast corner of Section 34.

In November 2013 I made a survey around Section 29, Township 39, Range 23 for Jeff Scullard to locate existing monuments, lines of occupation and establish search areas.

On 11/15/2013 I found a 2" Iron Pin at the surface of the paved highway. The found pin fit the remaining ties to the school house and the well pipe. I measure 10,683.71 feet to the Northeast corner of Section 33. I left the 2" pin as found and established one additional reference tie.

This location was determined to be the best available evidence of the original government corner monument location. No excavation was made at this location.



Kroschel Land Surveyors, Inc.

1639 Main Street North, Suite 6, Pine City, MN 55063
Phone: 320-629-3267 Fax: 320-629-0176