

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter corner of Section 25, Township 42 North, Range 23 West,
4th Principal Meridian, Kanabec County, State of Minnesota

At the corner location shown on the sketch:
On 4/6/2012 found an aluminum capped Kanabec County Monument.

Kanabec County U.S. Survey Feet Coordinates
NAD 1983, HARN 1996 Adjustment
Obtained by RTK GPS observation
Northing: 232537.5182
Easting: 429066.6591

Note: NAD 1983, HARN 1996 Adjustment
coordinates are NOT compatible with
NAD 1983 coordinates

Note: 1 Meter = 3937/1200 U.S. Survey Feet

SKETCH OF REFERENCE TIES

NOT TO SCALE

DISTANCE UNITS FOR THIS DRAWING IS
U.S. SURVEY FEET

NE CORNER OF SECTION 25, T.42, R.23
FOUND KANABEC COUNTY MONUMENT

THE BASIS OF BEARINGS FOR THIS
DRAWING IS THE KANABEC COUNTY
COORDINATE SYSTEM BY MNDOT,
NAD 1983, HARN 1996 ADJUSTMENT

SECTION 25, T.42, R.23

E 1/4 CORNER OF SECTION 25, T.42, R.23
FOUND KANABEC COUNTY MONUMENT

SECTION 30, T.42, R.22

N0°19'44"E
2628.10

N00°19'29"E
2627.55

SE CORNER OF SECTION 25, T.42, R.23
MN DNR COORDINATE



Kroschel Land Surveyors, Inc.

1639 Main Street North, Suite 6, Pine City, MN 55063
Phone: 320-629-3267 Fax: 320-629-0176

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this report was prepared by me or under my direct supervision, that the United States public land survey monument record is correct and complete to the best of my knowledge and belief, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

Tyler J. Kroschel, County Surveyor

3-1-2022
Date

License No. 44490

OFFICE OF THE COUNTY RECORDER
County of Kanabec

I hereby certify that this document was filed in the
County Recorder's office at _____ .M. on the
_____ day of _____ A.D., 20____
County Recorder _____

_____, Deputy

DOCUMENT NO. _____

Statement of Evidence:

In November of 1849, Deputy Surveyor James E. Freeman set a post to mark the East Quarter Corner of Section 25, Township 42 North, Range 23 West, 4th Principal Meridian.

Reference ties were taken to:

10 inch Tamarack at North 10 degrees West a distance of 6 links
8 inch Birch at South 65 degrees West a distance of 8 links

All of the original Government corner evidence was searched for. None was found.

2004– County Surveyor Ernie Rud, LS 9808, made a survey along the east line of Section 25, T.42, R.23. At the East Quarter corner of Section 25, Rud set a #7 rebar with Aluminum Cap on–line and halfway between the NE and SE corners of Section 25. No corner Certificate was filed.

2004– MN DNR Surveyor John Walker, LS 16098, made a survey in Section 30, T.42, R.22, and Sections 24, 25, and 36, T.42, R.23. Walker found a Kanabec County Monument at the East Quarter corner of Section 25, T.42, R.23. No corner Certificate was filed.

In April 2012, I made a survey around Section 25, Township 42 North, Range 23 West, 4th Principal Meridian for Lee Giese to locate existing monuments, lines of occupation and establish search areas.

On 4/6/2012, I found an 7/8" Rebar monument with Aluminum Cap at the East Quarter corner of Section 25. Assigned Kanabec County Coordinates. I accepted the found Rebar monument with Aluminum Cap to be the best available evidence of the original corner monument location.