



Statement of Evidence:

In November of 1849, Deputy Surveyor James Freeman set a post to mark the Northeast Corner of Section 2, Township 42 North, Range 24 West, 4th Principal Meridian.

Reference ties were taken to:

- 10 inch Spruce at North 43 degrees West a distance of 35 links
- 7 inch Balsam at North 72 degrees East a distance of 19 links
- 9 inch Balsam at South 30 degrees East a distance of 28 links
- 10 inch Birch at South 55 degrees West a distance of 16 links

All of the original Government corner evidence was searched for. None was found.

1926—Aitkin County Surveyor H.D. Keath made a survey in Section 36 of T.43, R.24 (Field Book 2, Page 30). He shows a distance of 5280 feet along the south line of Section 36.

2011— Paul Schoborg, LS 14700 made a survey in Section 2, T.42, R.24 for Jon Kennedy. Schoborg set a Kanabec County monument at the Northeast corner of Section 2. It appears he set the corner by single proration between the Northeast corner of Section 1 and the Northwest corner of Section 2. No corner certificate was filed.

In October 2023, I made a survey around Section 1, Township 42 North, Range 24 West, 4th Principal Meridian for Stephen Hennen to locate existing monuments.

On 10/25/2023 I made a search with a magnetic locator and found a 1/2" Iron Pipe with Aluminum cap. The found 1/2" Iron Pipe fit Mr. Schoborg's dimensions very well. Established reference ties and assigned Kanabec County Coordinates.

This location was determined to be the best available evidence of the original corner monument location.