

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

NORTHWEST Corner of Section 18, Township 41, Range 24, 4TH P.M.

STATE OF MINNESOTA, County of: KANABEC

At the corner location shown on the sketch:  
SET 1/2 INCH IRON PIPE  
AND ESTABLISHED G.P.S. COORDINTES ON THE LOCATION.

Kanabec County U.S. Survey Feet Coordinates  
NAD 1983, HARN 1996 Adjustment  
Obtained by RTK GPS Observation

Northing= 213240.73

Easting= 364700.18

Note: NAD 1983, HARN 1996 Adjustment  
coordinates are NOT compatible with  
NAD 1983 coordinates

Note: 1 Meter=3937/1200 U.S. Survey Feet

## SKETCH OF REFERENCE TIES



C/L CO. RD. NO. 79 (GRAVEL)

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data  
contained herein was prepared by me or under  
my direct supervision.

Ernest Blund  
Signature

1-23-2006  
Date

Registration No. Minn No 9808

Land Surveyor,       Professional Engineer

County Surveyor,       County Engineer

## OFFICE OF THE COUNTY RECORDER

County of \_\_\_\_\_

I hereby certify that this document was filed in  
the County Recorder's office at \_\_\_\_\_ M. on the

\_\_\_\_\_ day of \_\_\_\_\_ A.D., 20\_\_\_\_

County Recorder \_\_\_\_\_

BY \_\_\_\_\_ Deputy

DOCUMENT NO. \_\_\_\_\_

**STATEMENT OF EVIDENCE:**

**THE ORIGINAL CORNER WAS SET BY DEPUTY SURVEYOR ISAAC BANKER IN DECEMBER 1855. NO EVIDENCE FOR THE CORNER OR BEARING TREES REMAIN.**

**ON PAGE 89 OF THE COUNTY TIE BOOK GEORGE JENKE PLACED AN IRON ROD AT THIS CORNER ON MARCH 31, 1925.**

**THE M.H.D. PRIOR TO 1956 RAN A SURVEY FOR HIGHWAY 47 AND THEIR RIGHT OF WAY MAP INDICATES THEY USED THE CENTERLINE OF THE ROAD TO THE NORTH AND EAST. NO INDICATION OF A MONUMENT.**

**IN APRIL 2004 WE RAN A SURVEY AROUND SECTION 7, 8, 18, AND 19 TO LOCATE EXISTING MONUMENTATION AND TIE IN LINES OF OCCUPATION. WE FOUND A LARGE SPIKE IN BLACKTOP SET ON THE CENTERLINE OF HIGHWAY 47 AND COUNTY ROAD 79. THIS SPIKE FITS A PROJECTED DISTANCE FROM THE N.W. CORNER OF SECTION 7 TO THE NORTHWEST CORNER OF SECTION 30. WE ACCEPTED THIS SPIKE AND REPLACED IT WITH A 1/2 INCH IRON PIPE. WE TOOK TIES AND ESTABLISHED KANABEC COUNTY COORDINATES ON THIS POSITION.**