

NE CORNER, SEC. 26, T39, R25

STATEMENT OF EVIDENCE

THE ORIGINAL CORNER WAS SET BY DEPUTY SURVEYOR SILAS BARNARD ON JUNE 22, 1855 AND 4 BEARING TREES NOTED AS:

10" WHITE BIRCH @ 5 LINKS BEARING S45°E

10" BASSWOOD @ 28 LINKS BEARING N52°W

15" PINE @ 50 LINKS BEARING S65°W

10" MAPLE @ 12 LINKS BEARING N65°E

NO VISIBLE EVIDENCE COULD BE FOUND FOR THE ORIGINAL CORNER OR BEARING TREES.

NO SUBSEQUENT SURVEYS COULD BE FOUND AT THE KANABEC COUNTY OFFICES THAT USED THIS CORNER.

THERE IS A ROAD OPENING ALONG THE EAST LINE OF SEC. 23 BUT NO SURVEY WAS DONE AND THE ROAD WAS ONLY BUILT A 1/4 MILE SOUTH OF THE NE CORNER OF SEC. 23.

M.B. RUDE IN SETTING THE N1/4 CORNER OF SEC. 26 USED THE EXTENSION SOUTH OF THIS TOWNSHIP ROAD TO SET A POSITION ON THE NE CORNER OF SEC. 26

THEREFORE, WE USED THE SAME METHOD TO SET THE NE CORNER OF SEC. 26 AND PROPORTIONED BETWEEN THE NE CORNER OF SEC. 23 AND THE NE CORNER OF SEC. 35.

ON JANUARY 19, 2004, WE SET A 1/2" IRON PIPE WITH A CAP, TOOK TIES AND ESTABLISHED KANABEC COUNTY COORDINATES ON THIS POSITION.