

4222025

Index No. A -25

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

NORTHEAST Corner of Section 1, Township 42, Range 23, 4TH P.M.

STATE OF MINNESOTA, County of KANABEC

At the corner location shown on the sketch:

On \_\_\_\_\_ found a \_\_\_\_\_  
DATE

left monument as found,  lowered monument,  removed monument (explain)

On \_\_\_\_\_ Placed a \_\_\_\_\_  
DATE

## SKETCH OF REFERENCE TIES



CORNER NOT SET

KANABEC CO.  
COORDINATES  
N 256427.88  
E 429278.18

Statement of evidence relative to this corner location is on back of page.

12/98  
WMA00271

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

John D. Womack 12/8/98  
SIGNATURE DATE

License Number 16098

- Land Surveyor,  Professional Engineer  
 County Surveyor,  County Engineer

## OFFICE OF THE COUNTY RECORDER

County of \_\_\_\_\_

I hereby certify that this document was filed in the Co. recorders office at \_\_\_\_\_ .M. on the \_\_\_\_\_ day of \_\_\_\_\_ A.D., 19\_\_\_\_

County Recorder \_\_\_\_\_

By \_\_\_\_\_, Deputy

DOCUMENT NO. \_\_\_\_\_

Northeast Corner Section 1, Township 42 North, Range 23 West

The DNR Bureau of Engineering contacted the following for survey information:

Minnesota Secretary of State's Office  
Kanabec County Recorders's Office  
Kanabec County Highway Engineer  
Kanabec County Surveyor  
Aitkin County Recorder's Office  
Aitkin County Land Department  
Bill Hayden, Land Surveyor  
Terrence Johnson, Land Surveyor

1849 U.S. General Land Office notes obtained from the Secretary of State's Office states that a post was set to mark the corner with the following bearing trees marked:

W. Pine 30" S 60° W 30 links (19.80 feet)  
Sugar 14" N 55° W 31 links (20.46 feet)  
Maple 14" N 69° E 23 links (15.18 feet)  
Balsam 7" S 15° E 11 links (7.26 feet)

1998 MN DNR Bureau of Engineering found the Northeast Corner Section 5 of Township 42, Range 22, the Northeast Corner of Sections 3 and 18 of Township 42, Range 23 and the Northeast Corner Section 24 of Township 43, Range 23. This corner was double proportioned from these corners. The corner was not searched for at this time. The distance to the corners are as follows:

Northeast Section 5 - S89°22'48"E 10700.58 feet  
Northeast Section 3 - N89°52'00"W 10529.47 feet  
Northeast Section 13 - S00°50'43"W 10677.73 feet  
Northeast Section 24 - N00°29'24"E 15794.48 feet

For more information on our survey in this area please contact MN DNR, Bureau of Engineering, Survey Section, 1601 Minnesota Drive, Brainerd, MN 56425