

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

North Quarter Corner of Section 5, Township 41 North, Range 22 West,
4th Principal Meridian, Kanabec County, State of Minnesota

At the corner location shown on the sketch:
On 10/07/2010 set a 1/2" x 72" Iron Pipe Monument with
Plastic Cap marked RLS 44490.

Kanabec County U.S. Survey Feet Coordinates
NAD 1983, HARN 1996 Adjustment
Obtained by RTK GPS observation
Northing: 224653.3877
Easting: 436900.9724

Note: NAD 1983, HARN 1996 Adjustment
coordinates are NOT compatible with
NAD 1983 coordinates
Note: 1 Meter = 3937/1200 U.S. Survey Feet

SKETCH OF REFERENCE TIES

NOT TO SCALE

BEARINGS SHOWN TO REFERENCE TIES
ARE MAGNETIC COMPASS BEARINGS
DISTANCE UNITS FOR THIS DRAWING IS
U.S. SURVEY FEET

THE BASIS OF BEARINGS FOR THIS
DRAWING IS THE KANABEC COUNTY
COORDINATE SYSTEM BY MNDOT,
NAD 1983, HARN 1996 ADJUSTMENT

SECTION 32
T.42, R.22

NW CORNER OF
SECTION 5, T.41, R.22
SET 1/2" IRON PIPE

NE CORNER OF
SECTION 5, T.41, R.22
FOUND 7/8" REBAR

S89°58'07"E
2583.40

S89°58'07"E
2583.40

NO TIES AVAILABLE

SECTION 5
T.41, R.22




Kroschel Land Surveyors, Inc.

1639 Main Street North, Suite 6, Pine City, MN 55063
Phone: 320-629-3267 Fax: 320-629-0176

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and
the data contained herein was prepared
by me or under my direct supervision.


Tyler J. Kroschel

10-27-2010
Date

License No. 44490

- Land Surveyor
- County Surveyor

OFFICE OF THE COUNTY RECORDER

County of Kanabec

I hereby certify that this document was filed in the
County Recorder's office at _____ M. on the
_____ day of _____ A.D., 20____

County Recorder _____
By _____, Deputy

DOCUMENT NO. _____

120/17

Statement of Evidence:

In October of 1849, Deputy Surveyor James Freeman set a post to mark the North Quarter Corner of Section 5, Township 41 North, Range 22 West, 4th Principal Meridian.

Reference ties were taken to:

5 inch Tamarack at North 64 degrees West a distance of 50 links

8 inch Tamarack Ash at South 88.5 degrees East a distance of 157 links

All of the original Government corner evidence was searched for. None was found.

1918 Townships of Pomroy and Kroschel file road orders in the office of the County Auditor opening a town road along the south line of Sections 31, 32, and 33 of Kroschel Township. No road was ever built along the south line of Sections 31 and 32.

1996 MNDNR Bureau of Engineering (John Walker, RLS 16098) made a survey of the Kroschel Wildlife Management Area in Sections 32 and 33 of Kroschel Township. The survey shows a computed position for the South Quarter corner of Section 32 being 2640 feet west of the Southeast corner of Section 32. No monument was set and no corner certificate was filed.

In October 2010, a survey was made around Section 6, Township 41 North, Range 22 West, 4th Principal Meridian for Darline Campbell to locate existing monuments, lines of occupation and establish search areas.

On 10/07/2010, a search was made by checking with a magnetic locator. No evidence of corner was found. I set a 1/2" x 72" Iron Pipe monument with Plastic Cap marked RLS 44490 on-line and at proportional distance between the Northwest corner of Section 5 and the Northeast corner of Section 5, all in Township 41, Range 22. This location was determined to be the best available evidence of the original corner monument location. This location is approximately 56.6 feet east of the position used by the MNDNR in 1996. Assigned Kanabec County Coordinates.



Kroschel Land Surveyors, Inc.

1639 Main Street North, Suite 6, Pine City, MN 55063
Phone: 320-629-3267 Fax: 320-629-0176