

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

North Quarter Corner of Section 25, Township 42 North, Range 22 West,  
4th Principal Meridian, Kanabec County, State of Minnesota

At the corner location shown on the sketch:  
On 10/23/2012 set a 7/8" x 24" Rebar Monument with Aluminum Cap.

Kanabec County U.S. Survey Feet Coordinates  
NAD 1983, HARN 1996 Adjustment  
Obtained by RTK GPS observation  
Northing: 235102.8084  
Easting: 458105.3073

NAD 1983, HARN 1996 Adjustment  
coordinates are NOT compatible with  
NAD 1983 coordinates  
1 Meter = 3937/1200 U.S. Survey Feet

## SKETCH OF REFERENCE TIES

NOT TO SCALE

KROSCHER LAND SURVEYORS, INC.  
ASSUMES NO LIABILITY FOR THE ACCURACY  
OF THE GPS COORDINATES SHOWN HEREON.  
ALL COORDINATES AND DIMENSIONS  
SHOULD BE FIELD VERIFIED BY THE USER.

BEARINGS SHOWN TO REFERENCE TIES  
ARE MAGNETIC COMPASS BEARINGS  
DISTANCE UNITS FOR THIS DRAWING IS  
U.S. SURVEY FEET

THE BASIS OF BEARINGS FOR THIS  
DRAWING IS THE KANABEC COUNTY  
COORDINATE SYSTEM BY MNDOT,  
NAD 1983, HARN 1996 ADJUSTMENT




SECTION 24

NO TIES AVAILABLE

NW CORNER OF SECTION  
25 FOUND 7/8" REBAR  
WITH ALUM. CAP

N 1/4 CORNER OF  
SECTION 25 SET 7/8"  
REBAR WITH ALUM. CAP

NE CORNER OF SECTION  
25 FOUND 7/8" REBAR  
WITH ALUM. CAP



SWAMP

SECTION 25




**Kroschel Land Surveyors, Inc.**

1639 Main Street North, Suite 6, Pine City, MN 55063  
Phone: 320-629-3267 Fax: 320-629-0176

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision, that the United States public land survey monument record is correct and complete to the best of my knowledge and belief, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

  
Tyler J. Kroschel  
License No. 44490  
 Land Surveyor       County Surveyor

Date 1-23-2013

**OFFICE OF THE COUNTY RECORDER**  
County of Kanabec

I hereby certify that this document was filed in the County Recorder's office at \_\_\_\_\_ M. on the \_\_\_\_\_ day of \_\_\_\_\_ A.D., 20\_\_\_\_  
County Recorder \_\_\_\_\_  
By \_\_\_\_\_, Deputy  
DOCUMENT NO. \_\_\_\_\_

111/78

Statement of Evidence:

In November of 1855, Deputy Surveyor Isaac Banker set a post to mark the North Quarter Corner of Section 25, Township 42 North, Range 22 West, 4th Principal Meridian.

Reference ties were taken to:

- 6 inch Spruce at North 18 degrees 30 minutes East a distance of 52 links
- 5 inch Spruce at South 37 degrees 15 minutes West a distance of 57 links

All of the original Government corner evidence was searched for. None was found.

There is no resurvey data available for this corner.

In October 2012, I made a survey around Section 25, Township 42 North, Range 22 West, 4th Principal Meridian for Mark Wicklund to locate existing monuments, lines of occupation and establish search areas.

On 10/23/12, a search was made by probing with machetes and checking with a magnetic locator at a lost location. No evidence of corner was found. I set a 7/8" x 72" Rebar monument with Aluminum Cap on-line and halfway between the Northwest and Northeast corners of Section 25. This location was determined to be the best available evidence of the original government corner.



**Kroschel Land Surveyors, Inc.**

1639 Main Street North, Suite 6, Pine City, MN 55063  
Phone: 320-629-3267 Fax: 320-629-0176