

4222130

Index No. E - 5

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

NORTHEAST Corner of Section 7, Township 42, Range 22, 4TH P.M.

STATE OF MINNESOTA, County of KANABEC

At the corner location shown on the sketch:

On \_\_\_\_\_ found a \_\_\_\_\_  
DATE

left monument as found,  lowered monument,  removed monument (explain)

On \_\_\_\_\_ Placed a \_\_\_\_\_  
DATE

## SKETCH OF REFERENCE TIES



CORNER NOT SET

KANABEC CO.  
COORDINATES

N 250976.56  
E 434605.33

Statement of evidence relative to this corner location is on back of page.

12/98  
WMA00271

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

John D. Walker 12/8/98  
SIGNATURE DATE

License Number 16098

Land Surveyor,  Professional Engineer  
 County Surveyor,  County Engineer

## OFFICE OF THE COUNTY RECORDER

County of \_\_\_\_\_

I hereby certify that this document was filed in the Co. recorders office at \_\_\_\_\_ .M. on the \_\_\_\_\_ day of \_\_\_\_\_ A.D., 19\_\_\_\_

County Recorder \_\_\_\_\_

By \_\_\_\_\_, Deputy

DOCUMENT NO. \_\_\_\_\_

Northeast Corner Section 7, Township 42 North, Range 22 West

The DNR Bureau of Engineering contacted the following for survey information:

Minnesota Secretary of State's Office  
Kanabec County Recorders's Office  
Kanabec County Highway Engineer  
Kanabec County Surveyor  
Bill Hayden, Land Surveyor  
Terrence Johnson, Land Surveyor

1855 U.S. General Land Office notes obtained from the Secretary of State's Office states that a post was set to mark the corner with the following bearing trees marked:

Black Ash 20" N 20° 35' E 15 links (9.90 feet)  
Balsam 16" N 89° W 10 links (6.60 feet)  
Sugar 12" S 29° 30' W 31 links (20.46 feet)  
Balsam 9" S 62° 45' E 16 links (10.56 feet)

1998 MN DNR Bureau of Engineering considered this corner lost and established a position for it by double proportion. The corners used for the proportion are the Northeast Corner Section 18, Northeast Corner Section 8, Northeast Corner Section 6 and the Northwest Corner Section 7. The corner was not searched for and no monument was set at this time. Measurements to the section corners south, east, north and west are:

S01°32'06"W 5250.50 feet  
N89°47'51"E 5247.93 feet  
N01°09'05"E 5393.58 feet  
N89°35'12"W 5407.16 feet

For more information on our survey in this area please contact MN DNR, Bureau of Engineering, Survey Section, 1601 Minnesota Drive, Brainerd, MN 56425