

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

SOUTHEAST Corner of Section 31, Township 41, Range 23, 4TH P.M.

STATE OF MINNESOTA, County of KANABEC

At the corner location shown on the sketch:

Kanabec County U.S. Survey Feet Coordinates
 NAD 1983, HARN 1996 Adjustment
 Obtained by RTK GPS Observation

Northing= 191953.76

Easting= 402032.32

Note: NAD 1983, HARN 1996 Adjustment
 coordinates are NOT compatible with
 NAD 1983 coordinates

Note: 1 Meter=3937/1200 U.S. Survey Feet

SKETCH OF REFERENCE TIES

**THIS CORNER FALLS IN KNIFE LAKE. THIS POSITION WAS COMPUTED BY USING
 CHARLES HANDSCHU'S SURVEY FOR KNIFE LAKE DONE IN MARCH OF 1927.**

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Ernest L. Krol
Signature

11-27-10
Date

Registration No. 9808

Land Surveyor, Professional Engineer

County Surveyor, County Engineer

OFFICE OF THE COUNTY RECORDER

County of _____

I hereby certify that this document was filed in the County Recorder's office at _____ M. on the

_____ day of _____ A.D., 20__

County Recorder _____

BY _____ Deputy

DOCUMENT NO. _____

SE CORNER, SEC. 31, T41, R23

STATEMENT OF EVIDENCE

THE ORIGINAL CORNER GOV'T POST WAS SET BY DEPUTY SURVEYOR JOHN M. GLEY ON OCT. 6, 1851 AND BEARING TREES NOTED AS:

12" WHITE OAK @ 890 LINKS BEARING N87.75°E

10" WHITE PINE @ 900 LINKS BEARING N88.5°W

THIS CORNER AND BEARING TREES NOW FALL IN THE BED OF KNIFE LAKE.

IN 1927, CHARLES HANDSCHU DID A SURVEY OF SEC. 31 AND PARTS OF SEC. 30 AND 32. HANDSCHU HAD SET CORNERS AND COMPUTED POSITIONS FOR ALL 1/4 AND 1/16 CORNERS. IN 2007, E.G. RUD AND SONS, INC. TIED IN MONUMENTS, PERPETUATED AND RESURRECTED HANDSCHU'S SURVEY. THE MEASUREMENTS FIT VERY WELL SO KANABEC COUNTY MONUMENTS WERE COMPUTED AND ASSIGNED TO THIS CORNER FOR USE IN SURVEYS IN SEC. 31.