

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

NORTHEAST Corner of Section 35, Township 41, Range 23, 4TH P.M.

STATE OF MINNESOTA, County of KANABEC

At the corner location shown on the sketch:

FOUND THIS CORNER  
AND ESTABLISHED KANABEC COUNTY COORDINATES ON ITS LOCATION

Kanabec County U.S. Survey Feet Coordinates  
NAD 1983, HARN 1996 Adjustment  
Obtained by RTK GPS Observation

Northing= 196970.37

Easting= 423263.48

Note: NAD 1983, HARN 1996 Adjustment  
coordinates are NOT compatible with  
NAD 1983 coordinates

Note: 1 Meter=3937/1200 U.S. Survey Feet

## SKETCH OF REFERENCE TIES



E 1/4 CORNER  
SEC 26



2646.20  
S00°47'53"W

2' ±

NE CORNER  
SEC 35



5292.38  
S00°47'54"W

SE CORNER  
SEC 35



(PILOT STREET)

CO. HWY. NO. 72

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data  
contained herein was prepared by me or under  
my direct supervision.

Ernest G. Rud  
Signature

5-1-2007  
Date

### OFFICE OF THE COUNTY RECORDER

County of \_\_\_\_\_

I hereby certify that this document was filed in  
the County Recorder's office at \_\_\_\_\_ M. on the

\_\_\_\_\_ day of \_\_\_\_\_ A.D., 20\_\_\_\_

County Recorder \_\_\_\_\_

BY \_\_\_\_\_ Deputy

DOCUMENT NO. \_\_\_\_\_

Registration No. Minn No 9808

Land Surveyor,      [ ] Professional Engineer

County Surveyor,      [ ] County Engineer

# NORTHEAST CORNER SECTION 35, T41, R23

## **STATEMENT OF EVIDENCE**

ALL OF THE ORIGINAL BEARING TREES ARE NOW GONE.

THERE IS NO RE-SURVEY DATA ON FILE FOR THIS CORNER.

IN AUGUST OF 1988, M.B. RUDE RAN A SURVEY FROM THE NORTHEAST CORNER OF SECTION 23 TO THE SOUTHEAST CORNER OF SECTION 35 TO LOCATE THE EXISTING MONUMENTS, LINES OF OCCUPATION AND SEARCH AREAS.

THIS CORNER FALLS IN COUNTY HIGHWAY NO. 72.

ON AUGUST 21, 1988, M.B. RUDE MADE AN EXCAVATION WITH THE COUNTY BACKHOE FOR THIS CORNER. THE EXCAVATION WAS 15 FEET SQUARE DOWN TO THE NATURAL GROUND LEVEL. NO EVIDENCE WAS FOUND IN THE EXCAVATION.

THIS CORNER WAS SET BY PROPORTIONAL MEASUREMENTS BETWEEN THE EAST QUARTER CORNER OF SECTION 26 AND THE SOUTHEAST QUARTER OF SECTION 35.

IN APRIL 2007 FOUND THIS MONUMENT AND ESTABLISHED KANABEC COUNTY COORDINATES ON THIS POSITION.