

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter Corner of Section 1, Township 41 North, Range 23 West,  
4th Principal Meridian, Kanabec County, State of Minnesota

At the corner location shown on the sketch:  
On 10/5/2010, found a 7/8" Rebar Monument with  
Aluminum Cap. Left said monument as found.

Kanabec County U.S. Survey Feet Coordinates  
NAD 1983, HARN 1996 Adjustment  
Obtained by RTK GPS observation  
Northing: 220616.9874  
Easting: 428919.6010

Note: NAD 1983, HARN 1996 Adjustment  
coordinates are NOT compatible with  
NAD 1983 coordinates

Note: 1 Meter = 3937/1200 U.S. Survey Feet

## SKETCH OF REFERENCE TIES

NOT TO SCALE

BEARINGS SHOWN TO REFERENCE TIES  
ARE MAGNETIC COMPASS BEARINGS  
DISTANCE UNITS FOR THIS DRAWING IS  
U.S. SURVEY FEET



NE CORNER OF  
SECTION 1, T.41, R.23



N1°26'46"E  
4042.01

SECTION 1  
T. 41 R. 23

E 1/4 CORNER OF  
SECTION 1, T.41, R.23



N1°26'46"E  
2618.31

SECTION 6  
T. 41 R. 22

KROSCHER LAND SURVEYORS, INC.  
ASSUMES NO LIABILITY FOR THE ACCURACY  
OF THE GPS COORDINATES SHOWN HEREON.  
ALL COORDINATES AND DIMENSIONS  
SHOULD BE FIELD VERIFIED BY THE USER.



**Kroschel Land Surveyors, Inc.**

1639 Main Street North, Suite 6, Pine City, MN 55063  
Phone: 320-629-3267 Fax: 320-629-0176

SE CORNER OF  
SECTION 1, T.41, R.23



Statement of evidence relative to this corner location is on back of page.

I hereby certify that this report was prepared by me  
or under my direct supervision, that the United  
States public land survey monument record is  
correct and complete to the best of my knowledge  
and belief, and that I am a duly Licensed Land  
Surveyor under the laws of the State of Minnesota.


### OFFICE OF THE COUNTY RECORDER

County of Kanabec

I hereby certify that this document was filed in the  
County Recorder's office at \_\_\_\_\_ .M. on the  
\_\_\_\_\_ day of \_\_\_\_\_ A.D., 20\_\_\_\_

County Recorder \_\_\_\_\_, Deputy

DOCUMENT NO. \_\_\_\_\_

  
Tyler J. Kroschel, County Surveyor

2-24-2023  
Date

License No. 44490

Statement of Evidence:

In October of 1849, Deputy Surveyor James E. Freeman set a post to mark the East Quarter Corner of Section 1, Township 41 North, Range 23 West, 4th Principal Meridian.

Reference ties were taken to:

9 inch White Oak at South 22 degrees West a distance of 20 links  
9 inch Lind at North 20 degrees East a distance of 7 links

All of the original Government corner evidence was searched for. None was found.

In October 2010, I made a survey around Section 6, Township 41 North, Range 22 West, 4th Principal Meridian for Darline Campbell to locate existing monuments.

On 10/5/2010, I found a 7/8" Rebar Monument with Aluminum Cap at the East Quarter corner of Section 1, Township 41, Range 23 and assigned Kanabec County Coordinates. The corner was previously set by County Surveyor Ernie Rud, LS 9808 during a survey of the Township line in 2004. The found Rebar was placed on-line and at a proportional measurement between the NE corner and SE corner of Section 1.

The found Rebar was determined to be the best available evidence of the original corner location.



**Kroschel Land Surveyors, Inc.**

1639 Main Street North, Suite 6, Pine City, MN 55063  
Phone: 320-629-3267 Fax: 320-629-0176