

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter Corner of Section 6, Township 41 North, Range 22 West,  
4th Principal Meridian, Kanabec County, State of Minnesota

At the corner location shown on the sketch:  
On 10/14/2010 set a 1/2" x 72" Iron Pipe Monument with Plastic Cap marked RLS 44490.

Kanabec County U.S. Survey Feet Coordinates  
NAD 1983, HARN 1996 Adjustment  
Obtained by RTK GPS observation  
Northing: 220646.9623  
Easting: 434287.1054

Note: NAD 1983, HARN 1996 Adjustment coordinates are NOT compatible with NAD 1983 coordinates  
Note: 1 Meter = 3937/1200 U.S. Survey Feet

## SKETCH OF REFERENCE TIES

NOT TO SCALE

BEARINGS SHOWN TO REFERENCE TIES ARE MAGNETIC COMPASS BEARINGS  
DISTANCE UNITS FOR THIS DRAWING IS U.S. SURVEY FEET

THE BASIS OF BEARINGS FOR THIS DRAWING IS THE KANABEC COUNTY COORDINATE SYSTEM BY MNDOT, NAD 1983, HARN 1996 ADJUSTMENT



NE CORNER OF SECTION 6, T.41, R.22  
SET 1/2" IRON PIPE



SECTION 6

SECTION 5

SWAMP

SWAMP

NO TIES AVAILABLE

SE CORNER OF SECTION 6, T.41, R.22  
FOUND 7/8" REBAR




**Kroschel Land Surveyors, Inc.**

1639 Main Street North, Suite 6, Pine City, MN 55063  
Phone: 320-629-3267 Fax: 320-629-0176

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

  
Tyler J. Kroschel

10-27-2010  
Date

License No. 44490

- Land Surveyor
- County Surveyor

**OFFICE OF THE COUNTY RECORDER**  
County of Kanabec

I hereby certify that this document was filed in the County Recorder's office at \_\_\_\_\_ M. on the \_\_\_\_\_ day of \_\_\_\_\_ A.D., 20\_\_\_\_\_

County Recorder \_\_\_\_\_

By \_\_\_\_\_, Deputy

DOCUMENT NO. \_\_\_\_\_

Statement of Evidence:

In October of 1855, Deputy Surveyor Isaac Banker set a post to mark the East Quarter Corner of Section 6, Township 41 North, Range 22 West, 4th Principal Meridian.

Reference ties were taken to:


- 10 inch Balsam at North 65 degrees 15 minutes East a distance of 3 links
- 16 inch Yellow Birch at South 70 degrees West a distance of 13 links

All of the original Government corner evidence was searched for. None was found.

There is no resurvey data available for this corner.

In October 2010, a survey was made around Section 6, Township 41 North, Range 22 West, 4th Principal Meridian for Darline Campbell to locate existing monuments, lines of occupation and establish search areas.

On 10/14/2010, a search was made by checking with a magnetic locator. No evidence of corner was found. I set a 1/2" x 72" Iron Pipe monument with Plastic Cap marked RLS 44490 on-line and at proportional distance between the Northeast corner of Section 6 and the Southeast corner of Section 6. This location was determined to be the best available evidence of the original corner monument location. Assigned Kanabec County Coordinates.



**Kroschel Land Surveyors, Inc.**

1639 Main Street North, Suite 6, Pine City, MN 55063  
Phone: 320-629-3267 Fax: 320-629-0176