

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

SOUTH QUARTER Corner of Section 33, Township 38, Range 25, 4TH P.M.

STATE OF MINNESOTA, County of KANABEC

At the corner location shown on the sketch:

FOUND A 3/4 INCH REBAR WITH ALUMINUM CAP DOWN 0.4 FEET AND 1.5 FEET SOUTH OF CENTERLINE ROAD

Kanabec County U.S. Survey Feet Coordinates  
NAD 1983, HARN 1996 Adjustment  
Obtained by RTK GPS Observation

Northing= 101570.62

Easting= 356584.15

Note: NAD 1983, HARN 1996 Adjustment  
coordinates are NOT compatible with  
NAD 1983 coordinates

Note: 1 Meter=3937/1200 U.S. Survey Feet

## SKETCH OF REFERENCE TIES



Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Ernst Rud  
Signature

9-30-2008  
Date

Registration No. Minn No 9808

Land Surveyor,  Professional Engineer

County Surveyor,  County Engineer

## OFFICE OF THE COUNTY RECORDER

County of \_\_\_\_\_

I hereby certify that this document was filed in the County Recorder's office at \_\_\_\_\_ M. on the

\_\_\_\_\_ day of \_\_\_\_\_ A.D., 20\_\_

County Recorder \_\_\_\_\_

BY \_\_\_\_\_ Deputy

DOCUMENT NO. \_\_\_\_\_

SOUTH QUARTER CORNER SECTION 33, TOWNSHIP 38, RANGE 25

**STATEMENT OF EVIDENCE**

THE DEPARTMENT OF NATURAL RESOURCES, DIVISION OF LANDS AND MINERALS, CONTACTED THE FOLLOWING OFFICES FOR INFORMATION REGARDING THIS CORNER:  
MN SECRETARY OF STATE, ISANTI COUNTY RECORDER AND ENGINEER, MILLE LACS COUNTY RECORDER AND ENGINEER, POLARIS LAND SURVEYING, DALE ANDERSON-PASSE ENGINEERING, HANSEN SURVEYING, AND MNDOT IN ST. CLOUD.

1851

THE US GENERAL LAND OFFICE FIELD NOTES, ON FILE IN THE SECRETARY OF STATE'S OFFICE, SHOW THIS CORNER TO BE MARKED WITH A POST IN SWAMP AND THE FOLLOWING BEARING TREES WERE MARKED:

TAMARACK 4" N 69°W 17 LINKS (11.22")

TAMARACK 4" S 53°E 5 LINKS (3.3")

1914

IN THE SURVEYOR'S RECORD BOOK B, PAGE 165 A.M. HOLM SURVEYED SECTION 2 AND STATES "NW SEC. CORNER ESTABLISHED BY RICHARD CHAPMAN" FOR CORNER. HE RECORDS A DISTANCE OF 40.24 CHAINS (2655.84') TO THE NORTH QUARTER CORNER AND 40.94 CHAINS (2702.04') TO THE WEST QUARTER CORNER.

1916

IN AUGUST R.S. CHAPMAN FILED A RE-SURVEY PLAT OF SECTION 36, TOWN 38 NORTH-RANGE 26 WEST-4TH P.M. IN THE MILLE LACS COUNTY RECORDERS OFFICE. HE SHOWS THE FOLLOWING INFORMATION FROM THE SOUTHEAST CORNER OF SECTION 36 (SUPPOSED GOVT. COR.) TO THE NORTH QUARTER CORNER OF SECTION 2, T. 37, R. 25 (GOVT. COR.): GOVT DIST. 23,824.68 FT. AND RE-SURVEY 24,024.00 FT.. [BASED ON THE INFORMATION SHOWN ON THIS PLAT, IT IS ASSUMED THAT THERE WERE NO OTHER GOVERNMENT CORNERS FOUND ALONG THIS LINE.]

1999

THE DNR SURVEY CREW LOCATED THE NORTHWEST CORNER SECTION 6 AND THE NORTH QUARTER CORNER SECTION 2. THE DISTANCE BETWEEN THEM IS 23,926.42 FEET WHICH IS APPROXIMATELY 100' LONGER THAN GLO AND 100' SHORTER THAN CHAPMAN'S DISTANCE. COUNTY CIM'S WERE FOUND AT THE NORTH QUARTER AND NORTHEAST CORNERS OF SECTION 6. LOST POSITIONS WERE COMPUTED FOR THE CORNERS ALONG THE NORTH LINE OF SECTIONS 3, 4, AND 5. THE HALF MILE PROPORTIONAL DISTANCE IS 2654.77 FEET. IRON PIPES WERE FOUND AT THE NORTH QUARTER AND NORTHEAST CORNERS OF SECTION 5 THAT FIT THE PROPORTIONAL POSITION WELL.

2000

IN MARCH, THE DNR SURVEY CREW SET THE CORNERS ALONG THE NORTH LINE OF SECTIONS 3 AND 4 ON LINE AND AT THE LOST POSITION BETWEEN THE NORTHEAST CORNER SECTION 5 AND THE NORTH QUARTER CORNER SECTION 2. THE PROPORTION DISTANCE IS 2654.73'. A 3/4" x 24" REBAR WITH AN ALUMINUM "DNR SURVEY MARKER" CAP WAS SET TO MARK THE CORNER.

FOR MORE INFORMATION ON THE ABOVE SAID SURVEY IN THIS AREA PLEASE CONTACT MN DNR, DIVISIONS OF LANDS AND MINERALS, SURVEY SECTION, 1601 MINNESOTA DRIVE, BRAINERD, MN 56401.

ON APRIL 8, 2008 E.G. RUD & SONS, INC. FOUND THIS MONUMENT AND KANABEC COUNTY COORDINATES WERE ESTABLISHED ON THIS POSITION USING GLOBAL POSITIONING SYSTEM (G.P.S.) EQUIPMENT.