

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

NORTHEAST Corner of Section 32, Township 38, Range 25, 4TH P.M.

STATE OF MINNESOTA, County of KANABEC

At the corner location shown on the sketch:
SET A #7 REBAR WITH AN ALUMINUM CAP.

Kanabec County U.S. Survey Feet Coordinates
NAD 1983, HARN 1996 Adjustment
Obtained by RTK GPS Observation

Northing= 107115.87
Easting= 353780.94

Note: NAD 1983, HARN 1996 Adjustment
coordinates are NOT compatible with
NAD 1983 coordinates
Note: 1 Meter=3937/1200 U.S. Survey Feet

SKETCH OF REFERENCE TIES



C/L OF GRAVEL ROAD

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Ernest J. Paul 12-21-2010
Signature Date

Registration No. 9808

- Land Surveyor, Professional Engineer
 County Surveyor, County Engineer

OFFICE OF THE COUNTY RECORDER

County of _____

I hereby certify that this document was filed in the County Recorder's office at _____ M. on the _____ day of _____ A.D., 20____

County Recorder _____

BY _____ Deputy

DOCUMENT NO. _____

NE CORNER, SEC. 32, T38, R25

STATEMENT OF EVIDENCE

THE ORIGINAL CORNER POST WAS SET BY DEPUTY SURVEYOR DANIEL HIGBEE ON NOV. 20, 1851 AND 2 BEARING TREES ESTABLISHED AS FOLLOWS:

12" TAMARACK BEARING N54°W @ 15 LINKS

10" TAMARACK BEARING S43.5°E @ 15 LINKS

NO VISIBLE EVIDENCE COULD BE FOUND FOR THE POST OR BEARING TREES..

THERE IS A ROAD OPENING ON FILE ALONG THE NORTH LINE OF SEC. 32 DATED JUNE 1919 BUT NO SURVEY WAS DONE.

ON PAGE 27 OF BOOK 2 OF SURVEYS A SURVEY BY JOHN NELSON IS RECORDED FOR THE E1/2 OF SEC 29 DATED MARCH 1904. AT THAT TIME JOHN STATED THAT HE FOUND THE SE CORNER OF SEC. 29 TO BE A GOOD GOV'T CORNER AND THAT HE SET THE E1/4 CORNER OF SEC. 29.

ON PAGE 140 OF BOOK A1 OF SURVEYS CHARLES HANDSCHU RECORDED A SURVEY OF SEC. 28. HANDSCHU FOUND A POST AT THE E1/4 CORNER OF SEC. 29 AND A POST AT THE NE CORNER OF SEC. 29 WHICH COMPARED TO JOHN NELSON'S DISTANCE WITHIN LESS THAN 2 FEET.

THE NE CORNER OF SEC. 32 FALLS ON THE CENTERLINE OF AN EAST-WEST GRAVEL ROAD WITH NO OCCUPATION LINES RUNNING NORTH OR SOUTH AS LAND ON ALL SIDES OF THE SEC. CORNER IS OWNED BY THE SAME LAND OWNERS. THEREFORE THE NE AND E1/4 CORNERS OF SEC. 29 WERE REESTABLISHED AND THIS LINE EXTENDED SOUTH TO THE CENTERLINE OF THIS GRAVEL ROAD. THIS FIT WITHIN 5 FEET OF JOHN NELSON'S MEASUREMENT.

ON AUG. 10, 2010 AN EXCAVATION WITH THE COUNTY BACKHOE WAS 20 FEET EAST-WEST AND 10 FEET NORTH-SOUTH AND 1 FOOT INTO NATURAL GROUND. AT THE NATURAL GROUND LINE, IN THE CENTER OF THE EXCAVATION, A WOOD POST WAS FOUND, BUT IT WAS NOT POINTED. NO OTHER EVIDENCE COULD BE FOUND. THEREFORE WE SET THIS CORNER ON THE EXTENSION OF A LINE THROUGH THE NE AND E1/4 CORNERS OF SEC. 29 AND ON THE CENTERLINE OF THE GRAVEL ROAD. A #7 REBAR WITH AN ALUMINUM CAP WAS SET, TIES WERE TAKEN AND KANABEC COUNTY COORDINATES WERE ESTABLISHED ON THIS POSITION.