

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

NORTH ~~3~~ ⁴ Corner of Section 32, Township 38, Range 25, 4TH P.M.

STATE OF MINNESOTA, County of KANABEC

At the corner location shown on the sketch:
SET A #7 REBAR WITH AN ALUMINUM CAP.

Kanabec County U.S. Survey Feet Coordinates
NAD 1983, HARN 1996 Adjustment
Obtained by RTK GPS Observation


Northing= 107224.81

Easting= 351124.38

Note: NAD 1983, HARN 1996 Adjustment
coordinates are NOT compatible with
NAD 1983 coordinates

Note: 1 Meter=3937/1200 U.S. Survey Feet


SKETCH OF REFERENCE TIES



C/L OF GRAVEL ROAD

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.


Signature

12-21-2010
Date

Registration No. 9808

- Land Surveyor, Professional Engineer
- County Surveyor, County Engineer

OFFICE OF THE COUNTY RECORDER

County of _____

I hereby certify that this document was filed in the County Recorder's office at _____ M. on the

_____ day of _____ A.D., 20__

County Recorder _____

BY _____ Deputy

DOCUMENT NO. _____

N1/4 CORNER, SEC. 32, T38, R25

STATEMENT OF EVIDENCE

THE ORIGINAL CORNER POST WAS SET BY DEPUTY SURVEYOR DANIEL HIGBEE ON NOV. 28, 1851 AND 2 BEARING TREES ESTABLISHED AS FOLLOWS:

14" PINE BEARING N16°E @ 14 LINKS

12" BURR OAK BEARING S2°W @ 11 LINKS

NO VISIBLE EVIDENCE COULD BE FOUND FOR THE POST OR BEARING TREES..

THERE IS A ROAD OPENING ON FILE ALONG THE NORTH LINE OF SEC. 32 DATED JUNE 1919 BUT NO SURVEY WAS DONE.

ON PAGE 27 OF BOOK 2 OF SURVEYS A SURVEY BY JOHN NELSON IS RECORDED FOR THE E1/2 OF SEC 29 DATED MARCH 1904. JOHN NOTED A GOOD GOV'T CORNER AT THE NE CORNER OF SEC. 32 AND THAT HE FOUND 1 BEARING TREE AT THE NW CORNER OF SEC. 32. HE THEN SET THE N1/4 CORNER OF SEC. 32 AND NOTED A 30" PINE BEARING N11°W @ 1.07 LINKS. THIS PINE ISN'T EVIDENT TODAY. JOHN DOESN'T STATE WHAT WAS SET AT THE N1/4 CORNER.

THIS CORNER FALLS ON THE CENTERLINE OF AN EAST-WEST GRAVEL ROAD AT THE INTERSECTION WITH A FENCE LINE NORTH AND OCCUPATION LINE RUNNING SOUTH.

ON AUG. 10, 2010 E.G. RUD AND SONS, INC. MADE AN EXCAVATION WITH THE COUNTY BACKHOE AT THIS LOCATION. AT 2-1/2 FEET BELOW THE SURFACE A RECTANGULAR ROCK 5" THICK, 12" WIDE AND 2 FEET LONG WAS FOUND. THIS TAPERED TO THE TOP AND A "4" WAS CHISELED ON TOP. THIS STONE WAS LAYING DOWN BUT WAS IN CLOSE PROXIMITY TO THE FENCE LINE AND ON THE CENTERLINE OF THE ROAD. THE ROCK WAS PLACED UPRIGHT AGAIN AND A #7 REBAR WITH AN ALUMINUM CAP WAS SET FOR THE CORNER LOCATION, TIES WERE TAKEN AND KANABEC COUNTY COORDINATES WERE ESTABLISHED ON THIS POSITION.