

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter Corner of Section 24, Township 40 North, Range 24 West,
4th Principal Meridian, Kanabec County, State of Minnesota

At the corner location shown on the sketch:
On 2/05/2019, found a 1/2" Iron Pipe with plastic cap marked LS 41643. Left said monument as found.

Kanabec County U.S. Survey Feet Coordinates
NAD 1983, HARN 1996 Adjustment
Obtained by RTK GPS observation
Northing: 177010.3355
Easting: 406845.7055

Note: NAD 1983, HARN 1996 Adjustment coordinates are NOT compatible with NAD 1983 coordinates
Note: 1 Meter = 3937/1200 U.S. Survey Feet

SKETCH OF REFERENCE TIES

DISTANCE UNITS FOR THIS DRAWING IS
U.S. SURVEY FEET

NOT TO SCALE



NE CORNER OF
SECTION 24, T.40, R.24
SET LARGE MAG SPIKE

THE BASIS OF BEARINGS FOR THIS
DRAWING IS THE KANABEC COUNTY
COORDINATE SYSTEM BY MNDOT,
NAD 1983, HARN 1996 ADJUSTMENT

SECTION 24
T.40, R.24

SECTION 19
T.40, R.23



SE CORNER OF
SECTION 24, T.40, R.24
FOUND CAST ALUM
MONUMENT



Kroschel Land Surveyors, Inc.

1639 Main Street North, Suite 6, Pine City, MN 55063
Phone: 320-629-3267 Fax: 320-629-0176

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this report was prepared by me or under my direct supervision, that the United States public land survey monument record is correct and complete to the best of my knowledge and belief, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

OFFICE OF THE COUNTY RECORDER

County of Kanabec

I hereby certify that this document was filed in the County Recorder's office at _____ .M. on the _____ day of _____ A.D., 20_____

County Recorder _____, Deputy

DOCUMENT NO. _____


Tyler J. Kroschel, County Surveyor

1-29-2021
Date

License No. 44490

Statement of Evidence:

In September of 1849, Deputy Surveyor John M. Smith set a post to mark the East Corner of Section 24 , Township 40 North, Range 24 West, 4th Principal Meridian.

Reference ties were taken to:

- 12 inch Tamarack at North 15 degrees East a distance of 9 links
- 11 inch Tamarack at South 84 degrees West a distance of 11 links

All of the original Government corner evidence was searched for. None was found.

Approx 1900—Surveyor T.B. Vickery made a survey along the township line between Knife Lake and Whited Townships, recorded in Book A of Surveys, Page 206 located at the Kanabec County Highway Department. Vickery measures 80 chains along the east line of Section 24, Knife Lake Township.

1925— County Surveyor George Jenks filed a corner certificate for the Center of Section 24, T.40, R.24. Jenks set a stone marked +.

In February 2019, I made a survey around Section 24, Township 40 North, Range 24 West, 4th Principal Meridian for Jennifer Kvam to locate existing monuments, lines of occupation and establish search areas.

On 2/05/2019 I made a search with a magnetic locator at a lost position. I found a 1/2" Iron Pipe with plastic cap marked LS 41643. The found Iron Pipe fits a lost position very well. There are no lines of occupation in the immediate vicinity of this corner. This location was determined to be the best available evidence of the original corner monument location. Assigned Kanabec County Coordinates.

I was able to compute the location of Jenks' stone at the Center of Section 24 from a 1981 traverse done by M.B. Rude, LS 8195. The Jenks' stone at the Center of Section 24 is approximately 7 feet south of the east-west quarter line of Section 24.



Kroschel Land Surveyors, Inc.

1639 Main Street North, Suite 6, Pine City, MN 55063
Phone: 320-629-3267 Fax: 320-629-0176