

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

NORTH QUARTER Corner of Section 04, Township 39, Range 23, 4TH P.M.
SOUTH QUARTER Corner of Section 33, Township 40, Range 23, 4TH P.M.

STATE OF MINNESOTA, County of KANABEC

At the corner location shown on the sketch:

1/2" PIPE SET AND ESTABLISHED
 G.P.S. COORDINATES ON THE LOCATION

Kanabec County U.S. Survey Feet Coordinates
 NAD 1983, HARN 1996 Adjustment
 Obtained by RTK GPS Observation

Northing= 163831.65

Easting= 419878.85

Note: NAD 1983, HARN 1996 Adjustment
 coordinates are NOT compatible with
 NAD 1983 coordinates

Note: 1 Meter=3937/1200 U.S. Survey Feet

SKETCH OF REFERENCE TIES



MINIMUM MAINTENANCE RD.
 ORCHARD STREET

C/L 220TH AVENUE (GRAVEL)

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Ernest L. Rud
 Signature

1-23-2006
 Date

Registration No. Mian No 9808

Land Surveyor, [] Professional Engineer

[] County Surveyor, [] County Engineer

OFFICE OF THE COUNTY RECORDER

County of _____

I hereby certify that this document was filed in the County Recorder's office at _____ M. on the _____ day of _____ A.D., 20_____

County Recorder _____

BY _____ Deputy

DOCUMENT NO. _____

STATEMENT OF EVIDENCE

THE ORIGINAL CORNER WAS SET AND TIES TAKEN BY GOVERNMENT SURVEYOR SILAS BARNARD IN AUGUST 1855. THERE IS NO REMAINING EVIDENCE FOR THIS CORNER OR BEARING TREES. NO SUBSEQUENT SURVEY RECORDS FOR THIS CORNER COULD BE FOUND.

IN OCTOBER 2005 E.G. RUD RAN A SURVEY AROUND SECTION 33 TO LOCATE EXISTING MONUMENTATION AND LINES OF OCCUPATION.

ON OCTOBER 6, 2005 THE KANABEC COUNTY HIGHWAY DEPARTMENT MADE AN EXCAVATION AT THE CENTERLINE OF AN EAST-WEST GRAVEL ROAD AND THE CENTERLINE OF A MINIMUM MAINTENANCE ROAD GOING TO THE NORTH.

THE EXCAVATION WE MADE WAS APPROXIMATELY 8 FEET BY 12 FEET BY 1.5 FEET INTO NATURAL GROUND. NO EVIDENCE WAS IN THE EXCAVATION.

THE CENTERLINE INTERSECTION OF THE TWO ROADS WAS ACCEPTED AS THE BEST EVIDENCE FOR THE PERPETUATION OF THIS CORNER. A-HALF INCH PIPE WAS SET AND KANABEC COUNTY COORDINATES ESTABLISHED USING G.P.S. EQUIPMENT.