



TOWN OF  
**PETERBOROUGH**  
DEPARTMENT OF PUBLIC WORKS

1 Grove Street  
Peterborough, NH 03458  
Office: (603) 924-8000  
Fax: (603) 924-8001  
[www.townofpeterborough.com](http://www.townofpeterborough.com)

Permit No. \_\_\_\_\_

**PERMIT TO EXCAVATE IN PUBLIC STREET (RSA249:13)**

Permission is hereby granted to \_\_\_\_\_ of \_\_\_\_\_  
to disturb the surface, sidewalk, shoulders, or ditches of the \_\_\_\_\_ road in the Town  
of Peterborough for the purpose of installing/repairing \_\_\_\_\_.  
The work or excavation area is to be approximately \_\_\_\_\_ feet in length and \_\_\_\_\_ feet in width.

**PERMIT REQUIREMENTS AND CONDITIONS**  
(See Reverse Side)

Work to Begin \_\_\_\_\_ Work to End \_\_\_\_\_

“I hereby agree to assume such additional costs as the Town may incur, by reason of my failure to perform this work in the manner prescribed on the reverse side of this form, and to remain responsible for all required repairs to the street or roadway area disturbed for a period of 60 days after Completion Date of the work, and am familiar with the penalty imposed by RSA Chapter 249:18.”

By: \_\_\_\_\_  
Applicant

Permission for the above work granted, subject to the conditions and agreements printed hereon. This Permit to Expire on \_\_\_\_\_. (Expiration date to be 60 days from date of Completion Date.)

TOWN OF PETERBOROUGH

\_\_\_\_\_  
Issue Date

\_\_\_\_\_  
Public Works Superintendent

**(THIS PORTION OF PERMIT MUST BE FILLED OUT AND RETURNED BY APPLICANT.)**

JOB COMPLETED AND ROADWAY RESURFACED ON \_\_\_\_\_.

\_\_\_\_\_  
Applicant

COMPLETED JOB INSPECTED AND ACCEPTED ON \_\_\_\_\_.

\_\_\_\_\_  
Date

\_\_\_\_\_  
Public Works Department

## PERMIT REQUIREMENTS AND CONDITIONS

In opening the road surface, care must be taken not to disturb any more of the hardened surface than is absolutely necessary. All pavement must be cut with a pavement breaker or with a saw so that there shall be no uneven edges and every edge must be in an unbroken straight line. The road surface material must be removed and placed in a pile separate from the sub-grade material and shall not be used as backfill material.

Upon completion of the installation of pipes, or the repair thereof, the sub-grade material must be replaced in layers, each layer being thoroughly tamped mechanically, or puddle with water, until the subsurface is thoroughly compacted.

All pipe installation shall be of First Class Permanent Type Material and in the case of Heating Pipes or pipes used to carry liquid material other than water or sewage they shall be enclosed within a conduit, and it is suggested that an entrance manhole be installed on each side of the right-of-way on all such installations.

In all cases where concrete surface is disturbed, the opening shall be made in accordance with the foregoing requirements **AND PRIOR TO REPLACEMENT** of the surface material a second cut the full length and width of the excavation shall be made as directed by the Public Works Superintendent or the Town Engineer.

In the replacement of the hardened surface, concrete shall be used to replace concrete, and Type I Bituminous Concrete shall be laid in two courses to a minimum thickness of Three (3) inches as a wearing surface on all other forms of pavement. All surfaces shall be replaced on at least twelve (12) inches of good quality gravel, and in the event excavated sub-grade material does not consist of same, suitable gravel material shall be used as a replacement for poor quality material.

During the performance of this work, interruption of traffic must be kept at a Minimum, and the road shall be thoroughly protected by suitable barricades and flags during the daytime and properly lighted at night. **NO ROADWAYS SHALL BE CLOSED TO TRAFFIC AT ANY TIME UNLESS** special permission is obtained from the Public Works Superintendent and the Chief of Police.