

Proposal for **Santa Fe Springs F D**

Prepared by **South Coast Fire Equipment, Inc**

09/30/2020



*Pierce*

PERFORM. LIKE NO OTHER.™



## **CONTENTS**

GENERAL DESIGN AND CONSTRUCTION .....	20
QUALITY AND WORKMANSHIP .....	20
DELIVERY .....	21
MANUAL AND SERVICE INFORMATION.....	21
SAFETY VIDEO .....	21
PERFORMANCE TESTS .....	21
SERVICE AND WARRANTY SUPPORT .....	22
LIABILITY .....	22
INSURANCE PROVIDED BY BIDDER .....	22
COMMERCIAL GENERAL LIABILITY INSURANCE .....	22
COMMERCIAL AUTOMOBILE LIABILITY INSURANCE .....	23
UMBRELLA/EXCESS LIABILITY INSURANCE.....	23
INSURANCE PROVIDED BY MANUFACTURER .....	23
PRODUCT LIABILITY INSURANCE .....	23
UMBRELLA/EXCESS LIABILITY INSURANCE.....	24
SINGLE SOURCE MANUFACTURER .....	24
NFPA 2016 STANDARDS.....	24
NFPA COMPLIANCY.....	25
VEHICLE INSPECTION PROGRAM CERTIFICATION .....	25
INSPECTION CERTIFICATE.....	25
PUMP TEST .....	26
GENERATOR TEST .....	26
BREATHING AIR TEST.....	26
AFTERMARKET SUPPORT WEBSITE.....	26
BID BOND.....	27
PERFORMANCE BOND NOT REQUESTED .....	28
APPROVAL DRAWING .....	28
COMPARTMENT LAYOUT DRAWING .....	28
ELECTRICAL WIRING DIAGRAMS .....	29
ARROW XT CHASSIS.....	29
MAXIMUM OVERALL HEIGHT .....	29

WHEELBASE.....	29
GVW RATING .....	29
FRAME.....	29
FRAME REINFORCEMENT .....	29
FRONT NON DRIVE AXLE .....	29
FRONT SUSPENSION .....	30
FRONT SHOCK ABSORBERS.....	31
FRONT OIL SEALS .....	31
FRONT TIRES.....	31
REAR AXLE.....	31
TOP SPEED OF VEHICLE .....	31
REAR SUSPENSION.....	31
REAR OIL SEALS.....	31
REAR TIRES .....	31
TIRE BALANCE .....	31
TIRE PRESSURE MANAGEMENT .....	32
FRONT HUB COVERS .....	32
REAR HUB COVERS.....	32
CHROME LUG NUT COVERS.....	32
MUD FLAPS.....	32
WHEEL CHOCKS .....	32
Wheel Chock Brackets.....	32
ELECTRONIC STABILITY CONTROL.....	32
ANTI-LOCK BRAKE SYSTEM .....	33
AUTOMATIC TRACTION CONTROL.....	33
BRAKES .....	33
AIR COMPRESSOR, BRAKE SYSTEM .....	33
BRAKE SYSTEM .....	33
BRAKE SYSTEM AIR DRYER.....	34
BRAKE LINES .....	34
AIR INLET.....	34
ALL WHEEL LOCK-UP .....	34

ENGINE .....	34
REPTO DRIVE.....	35
HIGH IDLE .....	35
ENGINE BRAKE.....	35
CLUTCH FAN .....	35
ENGINE AIR INTAKE .....	36
EXHAUST SYSTEM .....	36
RADIATOR .....	36
COOLANT LINES.....	37
FUEL TANK .....	37
DIESEL EXHAUST FLUID TANK .....	37
AUXILIARY FUEL PUMP .....	38
FUEL COOLER .....	38
TRANSMISSION.....	38
TRANSMISSION SHIFTER.....	38
TRANSMISSION PROGRAMMING.....	39
TRANSMISSION COOLER.....	39
DRIVELINE.....	39
STEERING.....	39
STEERING WHEEL .....	39
LOGO AND CUSTOMER DESIGNATION ON DASH .....	39
BUMPER .....	40
Gravel Pan .....	40
LEFT SIDE HOSE TRAY .....	40
Left Side Hose Tray Restraint .....	40
LIFT AND TOW MOUNTS.....	40
TOW HOOKS .....	40
CAB.....	40
CAB ROOF DRIP RAIL .....	42
CAB PUMP ENCLOSURE.....	42
INTERIOR CAB INSULATION .....	42
FENDER LINERS .....	42



WINDSHIELD .....	42
WINDSHIELD WIPERS.....	42
GLOVE BOX.....	42
ENGINE TUNNEL .....	42
CAB REAR WALL EXTERIOR COVERING .....	43
CAB LIFT .....	43
Cab Lift Interlock.....	43
GRILLE .....	43
DOOR JAMB SCUFFPLATES.....	43
MIRRORS.....	43
DOORS .....	44
Door Panels .....	44
ELECTRIC OPERATED CAB DOOR WINDOWS.....	44
ELECTRIC CAB DOOR LOCKS.....	44
KEY PAD FOR ELECTRIC DOOR LOCKS.....	45
CAB STEPS.....	45
CAB EXTERIOR HANDRAILS .....	45
STEP LIGHTS .....	45
FENDER CROWNS.....	45
LEFT SIDE UPPER CREW CAB DOOR WINDOW TINT .....	45
LEFT SIDE ROLLUP CREW CAB DOOR WINDOW TINT .....	45
RIGHT SIDE UPPER CREW CAB DOOR WINDOW TINT.....	46
RIGHT SIDE ROLLUP CREW CAB DOOR WINDOW TINT.....	46
CUP HOLDER.....	46
CAB INTERIOR .....	46
CAB INTERIOR UPHOLSTERY .....	46
CAB INTERIOR PAINT .....	46
CAB FLOOR.....	46
CAB DEFROSTER .....	47
CAB/CREW CAB HEATER .....	47
AIR CONDITIONING .....	47
GRAVITY DRAIN TUBES .....	48

SUN VISORS .....	48
GRAB HANDLE.....	48
ENGINE COMPARTMENT LIGHTS .....	48
ACCESS TO ENGINE DIPSTICKS.....	48
MAP BOX .....	48
SEATING CAPACITY .....	49
DRIVER SEAT .....	49
OFFICER SEAT .....	49
REAR FACING LEFT SIDE CABINET .....	49
Cabinet Light .....	50
REAR FACING RIGHT SIDE CABINET .....	50
Cabinet Light .....	50
FORWARD FACING DRIVER SIDE OUTBOARD SEAT .....	50
FORWARD FACING CENTER CABINET .....	50
Cabinet Light .....	51
FORWARD FACING PASSENGER SIDE OUTBOARD SEAT .....	51
SEAT UPHOLSTERY.....	51
SEAT BELTS .....	51
SHOULDER HARNESS HEIGHT ADJUSTMENT .....	51
HELMET STORAGE PROVIDED BY FIRE DEPARTMENT .....	52
CAB DOME LIGHTS.....	52
OVERHEAD MAP LIGHTS .....	52
PORTABLE HAND LIGHTS PROVIDED BY FIRE DEPARTMENT .....	52
CAB INSTRUMENTATION .....	52
Cab Interior .....	53
Gauges.....	53
Indicator Lamps .....	54
Alarms.....	55
Indicator Lamp and Alarm Prove-Out .....	55
Control Switches .....	55
Custom Switch Panels.....	56
Diagnostic Panel.....	56

Cab LCD Display .....	57
AIR RESTRICTION INDICATOR .....	57
"DO NOT MOVE APPARATUS" INDICATOR .....	57
DO NOT MOVE TRUCK MESSAGES .....	57
SWITCH PANELS .....	58
WIPER CONTROL.....	58
HOURLMETER - AERIAL DEVICE .....	58
AERIAL MASTER .....	58
AERIAL PTO SWITCH.....	59
SPARE CIRCUIT.....	59
SPARE CIRCUIT .....	59
INSTRUMENT PANEL RECESS .....	59
STEREO RADIO .....	59
INFORMATION CENTER .....	60
General Screen Design.....	60
Home/Transit Screen .....	61
On Scene Screen .....	61
Virtual Buttons .....	61
Page Screen.....	61
COLLISION MITIGATION.....	63
VEHICLE DATA RECORDER.....	64
Seat Belt Monitoring System.....	64
INTERCOM SYSTEM .....	65
RADIO INTERFACE NOT REQUIRED .....	65
HEADSET, OVER THE HEAD.....	65
COMPLETE MDT INSTALLATION .....	65
PORTABLE RADIO CHARGER INSTALLATION .....	66
TWO WAY RADIO INSTALLATION .....	66
RADIO ANTENNA MOUNT.....	66
VEHICLE CAMERA SYSTEM.....	66
ELECTRICAL POWER CONTROL SYSTEM.....	66
SOLID-STATE CONTROL SYSTEM.....	67



CIRCUIT PROTECTION AND CONTROL DIAGRAM .....	68
ON-BOARD ADVANCED/VISUAL ELECTRICAL SYSTEM DIAGNOSTICS.....	68
TECH MODULE WITH WIFI.....	68
PROGNOSTICS .....	69
ADVANCED DIAGNOSTICS .....	69
INDICATOR LIGHT AND ALARM PROVE-OUT SYSTEM.....	69
VOLTAGE MONITOR SYSTEM.....	69
DEDICATED RADIO EQUIPMENT CONNECTION POINTS .....	69
ENHANCED SOFTWARE.....	70
EMI/RFI PROTECTION .....	70
ELECTRICAL.....	70
BATTERY SYSTEM .....	71
ISOLATED BATTERY .....	71
BATTERY SYSTEM .....	71
MASTER BATTERY SWITCH .....	72
BATTERY COMPARTMENTS .....	72
JUMPER STUDS .....	72
BATTERY CHARGER.....	72
KUSSMAUL AUTO EJECT FOR SHORELINE .....	72
SHORELINE TO SHORELINE TRANSFER SWITCH.....	73
ALTERNATOR.....	73
ELECTRONIC LOAD MANAGER.....	73
SEQUENCER.....	74
HEADLIGHTS.....	74
DIRECTIONAL LIGHTS .....	75
INTERMEDIATE LIGHT.....	75
CAB CLEARANCE/MARKER/ID LIGHTS .....	75
PLATFORM CLEARANCE/MARKER/ID LIGHTS .....	75
FRONT CAB SIDE DIRECTIONAL/MARKER LIGHTS .....	75
REAR CLEARANCE/MARKER/ID LIGHTING .....	75
MARKER LIGHTS .....	76
REAR FMVSS LIGHTING .....	76

LICENSE PLATE BRACKET .....	77
LIGHTING BEZEL.....	77
BACK-UP ALARM.....	77
CAB PERIMETER SCENE LIGHTS .....	77
PUMP HOUSE PERIMETER LIGHTS.....	77
BODY PERIMETER SCENE LIGHTS.....	77
ADDITIONAL PERIMETER LIGHTS.....	78
ADDITIONAL PERIMETER LIGHTS.....	78
STEP LIGHTS .....	78
12 VOLT LIGHTING.....	78
12 VOLT LIGHTING.....	78
12 VOLT DC SCENE LIGHTS .....	79
12 VOLT DC SCENE LIGHTS .....	79
DECK LIGHTS.....	79
WALKING SURFACE LIGHT .....	79
WATER TANK .....	80
HOSE BED.....	81
AERIAL HOSE BED HOSE RESTRAINT.....	81
RUNNING BOARDS .....	81
HANDRAILS .....	81
TURNTABLE STEPS.....	81
STEP LIGHTS .....	82
SMOOTH ALUMINUM REAR WALL .....	82
TOW EYES .....	82
COMPARTMENTATION .....	82
AGGRESSIVE WALKING SURFACE .....	83
LOUVERS.....	83
LEFT SIDE COMPARTMENTATION.....	83
PASSENGER SIDE COMPARTMENTATION.....	84
SIDE COMPARTMENT ROLLUP DOORS .....	84
SIDE COMPARTMENT LAP DOORS .....	85
REAR BUMPER.....	85

DOOR GUARD .....	86
ELECTRIC DOOR LOCKS.....	86
ROLL-UP DOOR TRIM .....	86
COMPARTMENT LIGHTING .....	86
MOUNTING TRACKS .....	86
ADJUSTABLE SHELVES.....	86
SLIDE-OUT ADJUSTABLE HEIGHT TRAY .....	86
SLIDE-OUT/TILT-DOWN TRAY .....	87
SLIDE-OUT FLOOR MOUNTED TRAY .....	87
SWING OUT TOOLBOARD .....	88
TOOL BOARD .....	88
DRAWER ASSEMBLY .....	88
RUB RAIL.....	89
BODY FENDER CROWNS .....	89
HARD SUCTION HOSE .....	89
THREE AIR BOTTLE STORAGE COMPARTMENT .....	89
AIR BOTTLE COMPARTMENT STRAP .....	89
SINGLE AIR BOTTLE STORAGE COMPARTMENT .....	89
EXTINGUISHER STORAGE .....	90
EXTENSION LADDER.....	90
ADDED EXTENSION LADDER .....	90
AERIAL EXTENSION LADDER.....	90
ROOF LADDERS.....	90
AERIAL FOLDING LADDER.....	90
GROUND LADDER STORAGE.....	90
LADDER STORAGE LIGHTING .....	91
NESTED LADDER STORAGE .....	91
PIKE POLES.....	91
8' PIKE POLE.....	91
6' PIKE POLE.....	91
ADDITIONAL PIKE POLE(S) .....	91
PIKE POLE STORAGE IN TORQUE BOX/LADDER STORAGE.....	91



PIKE POLE STORAGE .....	92
PIKE POLE STORAGE .....	92
PUMP .....	92
PUMP MOUNTING.....	93
MECHANICAL SEALS .....	93
PUMP GEAR CASE.....	93
CLUTCH.....	94
PUMPING MODE.....	94
PUMP SHIFT.....	94
TRANSMISSION LOCK UP .....	95
AUXILIARY COOLING SYSTEM .....	95
INTAKE RELIEF VALVE - PUMP.....	95
PRESSURE CONTROLLER.....	95
PRIMING PUMP .....	96
GARDEN HOSE DIRECT TANK FILL.....	96
PUMP MANUALS .....	97
PLUMBING, STAINLESS STEEL AND HOSE .....	97
FOAM SYSTEM PLUMBING.....	97
MAIN PUMP INLETS.....	97
MAIN PUMP INLET CAP .....	97
INLET BUTTERFLY VALVE.....	97
VALVES.....	98
LEFT SIDE INLET .....	98
RIGHT SIDE INLET .....	98
ANODE, INLET .....	98
INLET CONTROL.....	98
INLET BLEEDER VALVE .....	98
TANK TO PUMP .....	98
TANK REFILL.....	99
LEFT SIDE DISCHARGE OUTLETS .....	99
RIGHT SIDE DISCHARGE OUTLETS.....	99
LARGE DIAMETER DISCHARGE OUTLET .....	99

FRONT DISCHARGE OUTLET .....	100
DISCHARGE CAPS/ INLET PLUGS .....	100
OUTLET BLEEDER VALVE .....	100
LARGE DIAMETER OUTLET CAP .....	100
DISCHARGE OUTLET CONTROLS .....	100
AERIAL OUTLET .....	101
CROSSLAY MODULE.....	101
ROLLUP DOOR, CROSSLAY ENDS.....	101
CROSSLAY(S), LOWER .....	101
1.50" Crosslays .....	102
Crosslay Hose Trays .....	102
UPPER DEADLAY HOSE BED .....	102
Crosslay Hose Trays .....	102
BOOSTER HOSE REEL .....	102
HUSKY 3 FOAM PROPORTIONER.....	103
System Capacity.....	103
Control System.....	103
Hydraulic Drive System .....	104
Foam Concentrate Pump.....	104
External Foam Concentrate Connection .....	104
Panel Mounted External Pick-Up Connection / Valve .....	105
Pick-Up Hose .....	105
Discharges.....	105
System Electrical Load .....	105
SINGLE FOAM TANK REFILL .....	105
FOAM TANK .....	105
FOAM TANK DRAIN.....	105
PUC MODULE .....	105
PUMP CONTROL PANELS (Left Side Control) .....	106
PASSENGER SIDE PUC MODULE COMPARTMENT .....	107
PUMP OPERATOR'S PANEL DRAWING .....	107
REMAINING PUMP PANEL(S) .....	107

COLOR CODED TAGS .....	108
SPECIAL TEXT/VERBIAGE TAGS.....	108
PUMP PANEL CONFIGURATION.....	108
PUMP OPERATOR'S PLATFORM.....	108
PUMP OPERATOR'S PLATFORM PERIMETER LIGHT.....	108
PUMP AND GAUGE PANEL .....	108
PUMP AND PLUMBING ACCESS .....	109
PUMP COMPARTMENT LIGHT .....	109
THROTTLE READY GREEN INDICATOR LIGHT.....	109
VACUUM AND PRESSURE GAUGES .....	109
PRESSURE GAUGES .....	110
WATER LEVEL GAUGE.....	110
ADDITIONAL WATER LEVEL GAUGE .....	110
FOAM LEVEL GAUGE .....	111
SIDE CONTROL PUMP OPERATOR'S/PUMP PANEL LIGHTING .....	111
AIR HORN SYSTEM.....	111
Air Horn Location .....	111
Air Horn Control .....	111
ELECTRONIC SIREN.....	112
SPEAKER.....	112
AUXILIARY MECHANICAL SIREN .....	112
FRONT ZONE UPPER WARNING LIGHTS .....	113
FRONT ZONE UPPER LIGHTING, PLATFORM.....	113
TRAFFIC LIGHT CONTROLLER .....	113
CAB FACE WARNING LIGHTS.....	114
HEADLIGHT FLASHER .....	114
SIDE ZONE LOWER LIGHTING.....	114
INTERIOR CAB DOOR WARNING LIGHTS .....	115
INTERIOR CAB DOOR WARNING LIGHTS .....	115
SIDE WARNING LIGHTS.....	115
REAR ZONE LOWER LIGHTING .....	115
WARNING LIGHTS (Rear).....	116



WARNING LIGHTS (Rear of Hose Bed) .....	116
TRAFFIC DIRECTING LIGHT .....	116
ELECTRICAL SYSTEM GENERAL DESIGN for ALTERNATING CURRENT.....	116
General .....	116
Grounding .....	117
Operation .....	117
Overcurrent protection.....	118
Wiring Methods.....	118
Wiring Identification .....	118
Wet Locations .....	118
Dry Locations.....	119
Listing .....	119
Electrical System Testing.....	119
Operational Test per Current NFPA 1901 Standard .....	119
GENERATOR .....	120
Generator Instruments and Controls .....	120
GENERATOR LOCATION .....	120
GENERATOR START.....	120
CIRCUIT BREAKER PANEL .....	120
SUB FEED CIRCUIT BREAKER PANEL.....	120
ELECTRIC CORD REEL .....	120
CORD .....	121
PORTABLE JUNCTION BOX.....	121
120 VOLT RECEPTACLE.....	121
120 VOLT RECEPTACLE.....	121
120 VOLT RECEPTACLE.....	122
THREE SECTION 100' AERIAL PLATFORM .....	122
General Information .....	122
Operation on Grades.....	122
Construction Standards.....	122
Ladder Construction .....	123
Vertical Height .....	124

Horizontal Reach .....	124
Mounting of Elevating Platform .....	124
Torque Box .....	124
Turntable.....	124
Elevation System .....	124
Extension/Retraction System .....	125
Rotation System .....	125
Manual Override Controls .....	126
Ladder Slide Mechanism.....	126
Basket Leveling System.....	126
Rotation Interlock.....	126
Load Capacities .....	126
35 MPH Wind Conditions/Dry.....	127
Water Tower Operation.....	127
35 MPH Wind Conditions/Water Charged .....	127
Elevation -5 to +75 Degrees.....	127
Ladder Cradle Interlock System .....	127
Boom Support.....	127
AERIAL BOOM SUPPORT LIGHT .....	128
AERIAL BOOM PANEL.....	128
EXTENSION INDICATOR .....	128
AERIAL DEVICE RUNG COVERS.....	128
RUBBISH HOOK MOUNTING BRACKET .....	128
STOKES AND BACKBOARD STORAGE BOX .....	128
STABILITY TEST.....	129
BASKET STRUCTURE.....	129
BASKET SIDES .....	129
BASKET ENTRANCES/EXITS.....	130
ACCESSORY MOUNTING RECEPTACLES .....	130
ADDITIONAL MASK BOX AT BASKET .....	130
LYFE BRACKET STORAGE BOX AT PLATFORM .....	130
BASKET LANDING PAD EXTENSIONS.....	130

MULTIPLEX DISPLAY COVER .....	130
LIGHTS FOR TURNTABLE WALKWAY .....	130
ROTATION BEARING COVER .....	131
BASKET HEAT SHIELDS.....	131
INFORMATION CENTER .....	131
Operation .....	131
General Screen Design.....	131
Page Screens .....	132
Menu Screens .....	133
LOWER CONTROL STATION .....	134
AERIAL DEVICE CONTROL STATIONS .....	134
TURNTABLE CONTROL STATION .....	135
BASKET CONTROL CONSOLE.....	135
AERIAL FUNCTION CONTROLS .....	135
HIGH IDLE .....	135
STABILIZERS.....	135
STABILIZER CONTROLS .....	136
STABILIZER PADS .....	137
AUXILIARY STABILIZER PADS.....	137
CRADLE INTERLOCK SYSTEM .....	137
STABILIZER PINS .....	137
STABILIZER CONTROL BOX ALUMINUM DOOR .....	137
STABILIZER PLACEMENT.....	137
HYDRAULIC SYSTEM.....	138
HYDRAULIC RESERVOIR .....	138
HYDRAULIC FILTERS .....	138
HYDRAULIC CYLINDERS.....	139
POWER TAKEOFF / HYDRAULIC PUMP.....	139
EMERGENCY PUMP .....	139
HYDRAULIC SWIVEL .....	139
ELECTRIC SWIVEL.....	140
WATER SWIVEL.....	140



12-BIT ABSOLUTE ENCODER.....	140
ELECTRICAL SYSTEM.....	140
SPOTLIGHTS.....	142
LIGHTING ON AERIAL LADDER.....	142
STABILIZER WARNING LIGHTS.....	143
STABILIZER BEAM WARNING LIGHTS .....	143
STABILIZER SCENE LIGHTS.....	143
PLATFORM 120-VOLT ELECTRIC SYSTEM .....	143
120 VOLT UNDER PLATFORM LIGHTING .....	143
120 VOLT BASKET LIGHTING .....	143
2-WAY AERIAL COMMUNICATION SYSTEM.....	144
VIDEO CAMERA SYSTEM.....	144
BREATHING AIR.....	144
BREATHING AIR LEVEL AND WARNING SYSTEM .....	145
RAISED AERIAL PEDESTAL.....	145
WINCH .....	145
<i>Lyfe</i> Combo™BRACKETS .....	145
AERIAL TURNTABLE MANSERVER™ BARS.....	146
AERIAL WATERWAY.....	146
WATERWAY SEALS .....	146
PLATFORM WATER SYSTEM .....	146
AERIAL MONITOR.....	147
WATERWAY FLOWMETER .....	147
REAR INLET .....	147
TOOLS.....	147
MANUALS .....	147
INITIAL INSTRUCTION .....	147
LOOSE EQUIPMENT .....	148
NFPA REQUIRED LOOSE EQUIPMENT PROVIDED BY FIRE DEPARTMENT .....	148
SOFT SUCTION HOSE .....	149
DRY CHEMICAL EXTINGUISHER PROVIDED BY FIRE DEPARTMENT .....	149
WATER EXTINGUISHER PROVIDED BY FIRE DEPARTMENT .....	149

AERIAL LADDER BELTS .....	149
FLATHEAD AXE PROVIDED BY FIRE DEPARTMENT .....	149
PICKHEAD AXE PROVIDED BY FIRE DEPARTMENT .....	150
PAINT .....	150
PAINT - ENVIRONMENTAL IMPACT .....	151
PAINT CHASSIS FRAME ASSEMBLY .....	152
AXLE HUB PAINT .....	152
COMPARTMENT INTERIOR PAINT .....	152
AERIAL DEVICE PAINT COLOR.....	152
REFLECTIVE BAND .....	153
REAR CHEVRON STRIPING .....	154
REFLECTIVE STRIPE ON STABILIZERS .....	154
JOG(S) IN REFLECTIVE BAND .....	154
CAB DOOR REFLECTIVE STRIPE .....	154
BODY STRIPE.....	154
CAB STRIPE .....	154
LETTERING .....	154
LETTERING .....	154
LETTERING .....	154
LETTERING .....	155
LETTERING .....	155
DECAL INSTALLATION .....	155
EMBLEM/S .....	155
DEALER PROVIDED TOOL MOUNTING.....	155
FIRE APPARATUS PARTS MANUAL.....	155
Service Parts Internet Site.....	155
CHASSIS SERVICE MANUALS .....	156
CHASSIS OPERATION MANUAL .....	156
ONE (1) YEAR MATERIAL AND WORKMANSHIP .....	156
ENGINE WARRANTY .....	156
STEERING GEAR WARRANTY .....	156
FIFTY (50) YEAR STRUCTURAL INTEGRITY .....	156

FRONT AXLE THREE (3) YEAR MATERIAL AND WORKMANSHIP WARRANTY .....	156
TDM REAR AXLE FIVE (5) YEAR MATERIAL AND WORKMANSHIP WARRANTY.....	156
ABS BRAKE SYSTEM THREE (3) YEAR MATERIAL AND WORKMANSHIP WARRANTY .....	157
TEN (10) YEAR STRUCTURAL INTEGRITY .....	157
TEN (10) YEAR PRO-RATED PAINT AND CORROSION.....	157
FIVE (5) YEAR MATERIAL AND WORKMANSHIP .....	157
CAMERA SYSTEM WARRANTY.....	157
COMPARTMENT LIGHT WARRANTY.....	157
TRANSMISSION WARRANTY.....	157
TRANSMISSION COOLER WARRANTY.....	157
WATER TANK WARRANTY .....	157
TEN (10) YEAR STRUCTURAL INTEGRITY .....	157
ROLL UP DOOR MATERIAL AND WORKMANSHIP WARRANTY.....	157
SIX (6) YEAR PARTS, ONE (1) YEAR LABOR.....	158
TEN (10) YEAR PUMP PLUMBING WARRANTY .....	158
FOAM SYSTEM WARRANTY .....	158
TWENTY (20) YEAR AERIAL DEVICE STRUCTURAL INTEGRITY WARRANTY.....	158
AERIAL SWIVEL WARRANTY.....	158
HYDRAULIC SYSTEM COMPONENTS WARRANTY.....	158
HYDRAULIC SEAL WARRANTY .....	158
AERIAL WATERWAY WARRANTY.....	158
FOUR (4) YEAR PRO-RATED PAINT AND CORROSION .....	158
FIVE (5) YEAR MATERIAL AND WORKMANSHIP .....	158
SIX (6) YEAR GENERATOR MATERIAL AND WORKMANSHIP WARRANTY .....	158
TEN (10) YEAR PRO-RATED PAINT AND CORROSION .....	158
THREE (3) YEAR MATERIAL AND WORKMANSHIP .....	159
VEHICLE STABILITY CERTIFICATION .....	159
ENGINE INSTALLATION CERTIFICATION.....	159
POWER STEERING CERTIFICATION .....	159
CAB INTEGRITY CERTIFICATION .....	159
CAB DOOR DURABILITY CERTIFICATION .....	160
WINDSHIELD WIPER DURABILITY CERTIFICATION.....	160

ELECTRIC WINDOW DURABILITY CERTIFICATION.....	160
SEAT BELT ANCHOR STRENGTH .....	160
SEAT MOUNTING STRENGTH .....	160
CAB DEFROSTER CERTIFICATION.....	160
CAB HEATER CERTIFICATION.....	160
CAB AIR CONDITIONING PERFORMANCE CERTIFICATION.....	161
AMP DRAW REPORT .....	161

South Coast Fire Equipment is pleased to submit a proposal to Santa Fe Springs Fire Department for a **Pierce® 100' Aerial Platform** per your request for quotation. The following paragraphs will describe in detail the apparatus, construction methods, and equipment proposed. This proposal will indicate size, type, model and make of components parts and equipment, providing proof of compliance with each and every item (except where noted) in the departments advertised specifications.

PIERCE MANUFACTURING was founded in 1913. Since then we have been building bodies with one philosophy, "BUILD THE FINEST". Our skilled craftsmen take pride in their work, which is reflected, in the final product. We have been building fire apparatus since the early "forties" giving Pierce Manufacturing over 75 years of experience in the fire apparatus market. Pierce Manufacturing has built and put into service more than 62,500 apparatus, including more than 33,900 on Pierce custom chassis designed and built specifically for fire and emergency applications. Our Appleton, Wisconsin facility has over 870,000 total square feet of floor space situated on approximately 105 acres of land. Our Bradenton, Florida facility has 300,000 square feet of floor space situated on approximately 38 acres of land.

Our beliefs in high ethical standards are carried through in all of our commitments and to everyone with whom we do business. Honesty, Integrity, Accountability and Citizenship are global tenets by which we all live and work. Consequently, we neither engage in, nor have we ever been convicted of price fixing, bid rigging, or collusion in any domestic or international fire apparatus market.

Pierce has only one brand of fire apparatus "Pierce", ensuring you are receiving top of the line product that meets your specification.

In accordance with the current edition of NFPA 1901 standards, this proposal will specify whether the fire department, manufacturer, or apparatus dealership will provide required loose equipment.

Images and illustrative material in this proposal are as accurate as known at the time of publication, but are subject to change without notice. Images and illustrative material is for reference only, and may include optional equipment and accessories and may not include all standard equipment.

#### **GENERAL DESIGN AND CONSTRUCTION**

To control quality, ensure compatibility, and provide a single source for service and warranty, the custom cab, chassis, pump module and body will be entirely designed, assembled/welded and painted in Pierce owned manufacturing facilities. This includes, but not limited to the cab weldment, the pumphouse module assembly, the chassis assembly, the body and the electrical system.

#### **QUALITY AND WORKMANSHIP**

Pierce has set the pace for quality and workmanship in the fire apparatus field. Our tradition of building the highest quality units with craftsmen second to none has been the rule right from the beginning and we demonstrate that ongoing commitment by: Ensuring all steel welding follows American Welding Society D1.1-2004 recommendations for structural steel welding. All aluminum welding follows American Welding society and ANSI D1.2-2003 requirements for structural welding of

aluminum. All sheet metal welding follows American welding Society B2.1-2000 requirements for structural welding of sheet metal. Our flux core arc welding uses alloy rods, type 7000 and is performed to American Welding Society standards A5.20-E70T1. Furthermore, all employees classified as welders are tested and certified to meet the American welding Society codes upon hire and every three (3) years thereafter. Pierce also employs an American Welding Society certified welding inspector in plant during working hours to monitor weld quality.

Pierce Manufacturing operates a Quality Management System under the requirements of ISO 9001. These standards sponsored by the International Organization for Standardization (ISO) specify the quality systems that are established by the manufacturer for design, manufacture, installation and service. A copy of the certificate of compliance is included with this proposal.

In addition to the Quality Management system, we also employ a Quality Achievement Supplier program to insure the vendors and suppliers that we utilize meet the high standards we demand. That is just part of our overall "Quality at the Source" program at Pierce.

To demonstrate the quality of our products and services, a list of at least twenty five (25) fire departments/municipalities that have purchased vehicles for a second time is provided.

### **DELIVERY**

The apparatus will be delivered under its own power to insure proper break-in of all components while the apparatus is still under warranty. A qualified delivery representative shall deliver the apparatus and remain for a sufficient length of time to instruct personnel in proper operation, care and maintenance of the equipment delivered.

### **MANUAL AND SERVICE INFORMATION**

At time of delivery, complete operation and maintenance manuals covering the apparatus will be provided. A permanent plate will be mounted in the driver's compartment specifying the quantity and type of fluids required including engine oil, engine coolant, transmission, pump transmission lubrication, pump primer and drive axle.

### **SAFETY VIDEO**

At the time of delivery Pierce will also provide one (1) 39-minute, professionally produced apparatus safety video, in DVD format. This video will address key safety considerations for personnel to follow when they are driving, operating, and maintaining the apparatus, including the following: vehicle pre-trip inspection, chassis operation, pump operation, aerial operation, and safety during maintenance.

### **PERFORMANCE TESTS**

A road test will be conducted with the apparatus fully loaded and a continuous run of no less than ten (10) miles. During that time the apparatus will show no loss of power nor will it overheat. The transmission drive shaft or shafts and the axles will run quietly and be free of abnormal vibration or noise. The apparatus when fully loaded will not have less than 25 percent nor more than 50 percent on the front axle, and not less than 50 percent nor more than 75 percent on the rear axle. The apparatus will meet NFPA 1901 acceleration and braking requirements.



## **SERVICE AND WARRANTY SUPPORT**

Pierce dealership support will be provided by South Coast Emergency Vehicle Service by operating in conjunction with a Pierce authorized service center. The service center will have factory-trained mechanics on staff versed in Pierce fire apparatus. The service facility will be located within fifty (50) miles of the fire department.

In addition to the dealership, Pierce has service facilities located in both, Weyauwega, Wisconsin and Bradenton, Florida. Pierce also maintains a dedicated parts facility of over 100,000 square feet in Appleton, Wisconsin. The parts facility stocks in excess of \$5,000,000 in parts dedicated to service and replacement parts. The parts facility employs a staff dedicated solely for the distribution and shipment of service and replacement parts.

Service parts for the apparatus being proposed can be found via [Pierceparts.com](http://Pierceparts.com) which, is an interactive online tool that delivers information regarding your specific apparatus as well as the opportunity to register for training classes.

As a Pierce customer you have the ability to view the complete bill of materials for your specific apparatus, including assembly drawings, piece part drawings, and beneficial parts notations. You will also have the ability to search the complete Pierce item master through a parts search function which offers all Pierce SKU's and descriptions offered on all Pierce apparatus. Published component catalogs, which include proprietary systems along with an extensive operators manual library is available for easy reference.

Pierce Manufacturing maintains a dedicated service and warranty staff of over 35 personnel, dedicated to customer support, which also maintains a 24 hour 7 day a week toll free hot line, four (4) on staff EVT's, and offers hands-on repair and maintenance training classes multiple times a year.

## **LIABILITY**

The successful bidder will defend any and all suits and assume all liability for the use of any patented process including any device or article forming a part of the apparatus or any appliance furnished under the contract.

## **INSURANCE PROVIDED BY BIDDER**

### **COMMERCIAL GENERAL LIABILITY INSURANCE**

The successful bidder will, during the performance of the contract and for three (3) years following acceptance of the product, keep in force at least the following minimum limits of commercial general liability insurance:

Each Occurrence\$1,000,000

Products/Completed Operations Aggregate\$1,000,000

Personal and Advertising Injury\$1,000,000

General Aggregate\$2,000,000

Coverage will be written on a Commercial General Liability form. The policy will be written on an occurrence form and will include Contractual Liability coverage for bodily injury and property damage subject to the terms and conditions of the policy. The policy will include Owner as an additional insured when required by written contract.

#### **COMMERCIAL AUTOMOBILE LIABILITY INSURANCE**

The successful bidder will, during the performance of the contract, keep in force at least the following minimum limits of commercial automobile liability insurance and coverage will be written on a Commercial Automobile liability form:

Each Accident Combined Single Limit:\$1,000,000

#### **UMBRELLA/EXCESS LIABILITY INSURANCE**

The successful bidder will, during the performance of the contract and for three (3) years following acceptance of the product, keep in force at least the following minimum limits of umbrella liability insurance:

Aggregate:\$3,000,000

Each Occurrence:\$3,000,000

The umbrella policy will be written on an occurrence basis and at a minimum provide excess to the bidder's General Liability and Automobile Liability policies.

The required limits can be provided by one (1) or more policies provided all other insurance requirements are met.

Coverage will be provided by a carrier(s) rated A- or better by A.M. Best.

All policies will provide a 30-day notice of cancellation to the named insured. The Certificate of Insurance will provide the following cancellation clause: Should any of the above described policies be cancelled before the expiration date thereof, notice will be delivered in accordance with the policy provisions.

Bidder agrees to furnish owner with a current Certificate of Insurance with the coverages listed above along with the bid. The certificate will show the purchaser as certificate holder.

#### **INSURANCE PROVIDED BY MANUFACTURER**

##### **PRODUCT LIABILITY INSURANCE**

The manufacturer will, during the performance of the contract and for three (3) years following acceptance of the product, keep in force at least the following minimum limits of Product Liability insurance:

Each Occurrence\$1,000,000

Products/Completed Operations Aggregate\$1,000,000

Coverage will be written on a Commercial General Liability form. The policy will be written on an occurrence form. The manufacturer's policy will include the owner as additional insured when required by written contract between the Owner and a Pierce authorized dealer.

#### **UMBRELLA/EXCESS LIABILITY INSURANCE**

The manufacturer will, during the performance of the contract and for three (3) years following acceptance of the product, keep in force at least the following minimum limits of umbrella liability insurance:

Each Occurrence:\$25,000,000

Aggregate:\$25,000,000

The umbrella policy will be written on an occurrence basis and provide excess to the manufacturer's General Liability/Products policies.

The required limits can be provided by one (1) or more policies provided all other insurance requirements are met.

Coverage will be provided by a carrier(s) rated A- or better by A.M. Best.

All policies will provide a 30-day notice of cancellation to the named insured. The Certificate of Insurance will provide the following cancellation clause: Should any of the above described policies be cancelled before the expiration date thereof, notice will be delivered in accordance with the policy provisions.

Manufacturer agrees to furnish owner with a current Certificate of Insurance with the coverages listed above along with the bid. The certificate will show the purchaser as the certificate holder.

#### **SINGLE SOURCE MANUFACTURER**

Pierce Manufacturing, Inc. provides an integrated approach to the design and manufacture of our products that delivers superior apparatus and a dedicated support team. From our facilities, the chassis, cab weldment, cab, pump house (including the sheet metal enclosure, valve controls, piping and operators panel) body and aerial device will be entirely designed, tested, and hand assembled to the customer's exact specifications. The electrical system either hardwired or multiplexed, will be both designed and integrated by Pierce Manufacturing. The warranties relative to these major components (excluding component warranties such as engine, transmission, axles, pump, etc.) will be provided by Pierce as a single source manufacturer. Pierce's single source solution adds value by providing a fully engineered product that offers durability, reliability, maintainability, performance, and a high level of quality.

Your apparatus will be manufactured in Appleton, Wisconsin.

#### **NFPA 2016 STANDARDS**

This unit will comply with the NFPA standards effective January 1, 2016, except for fire department directed exceptions. These exceptions will be set forth in the Statement of Exceptions.

Certification of slip resistance of all stepping, standing and walking surfaces will be supplied with delivery of the apparatus.

All horizontal surfaces designated as a standing or walking surface that are greater than 48.00" above the ground must be defined by a 1.00" wide line along its outside perimeter. Perimeter markings and designated access paths to destination points will be identified on the customer approval print and are shown as approximate. Actual location(s) will be determined based on materials used and actual conditions at final build. Access paths may pass through hose storage areas and opening or removal of covers or restraints may be required. Access paths may require the operation of devices and equipment such as the aerial device or ladder rack.

A plate that is highly visible to the driver while seated will be provided. This plate will show the overall height, length, and gross vehicle weight rating.

The manufacturer will have programs in place for training, proficiency testing and performance for any staff involved with certifications.

An official of the company will designate, in writing, who is qualified to witness and certify test results.

#### **NFPA COMPLIANCY**

Apparatus proposed by the bidder will meet the applicable requirements of the National Fire Protection Association (NFPA) as stated in current edition at time of contract execution. Fire department's specifications that differ from NFPA specifications will be indicated in the proposal as "non-NFPA".

#### **VEHICLE INSPECTION PROGRAM CERTIFICATION**

To assure the vehicle is built to current NFPA standards, the apparatus, in its entirety, will be third-party, audit-certified through Underwriters Laboratory (UL) that it is built and complies to all applicable standards in the current edition of NFPA 1901. The certification will include: all design, production, operational, and performance testing of not only the apparatus, but those components that are installed on the apparatus.

A placard will be affixed in the driver's side area stating the third party agency, the date, the standard and the certificate number of the whole vehicle audit.

#### **INSPECTION CERTIFICATE**

A third party inspection certificate for the aerial device will be furnished upon delivery of the aerial device. The certificate will be Underwriters Laboratories Inc. Type 1 and will indicate that the aerial device has been inspected on the production line and after final assembly.

Visual structural inspections will be performed on all welds on both aluminum and steel ladders.

On critical weld areas, or on any suspected defective area, the following tests will be conducted:

- Magnetic particle inspection will be conducted on steel aerials to assure the integrity of the weldments and to detect any flaws or weaknesses. Magnets will be placed on each side of the weld while iron powder is placed on the weld itself. The powder will detect any crack that may

exist. This test will conform to ASTM E709 and be performed prior to assembly of the aerial device.

- A liquid penetrant test will be conducted on aluminum aerials to assure the integrity of the weldments and to detect any flaws or weaknesses. This test will conform to ASTM E165 and be performed prior to assembly of the aerial device.
- Ultrasonic inspection will be conducted on all aerials to detect any flaws in pins, bolts and other critical mounting components.

In addition to the tests above, functional tests, load tests, and stability tests will be performed on all aerials. These tests will determine any unusual deflection, noise, vibration, or instability characteristics of the unit.

### **PUMP TEST**

The pump will be tested, approved and certified by Underwriter's Laboratory at the manufacturer's expense. The test results and the pump manufacturer's certification of hydrostatic test; the engine manufacturer's certified brake horsepower curve; and the manufacturer's record of pump construction details will be forwarded to the Fire Department.

### **GENERATOR TEST**

If the unit has a generator, the generator will be tested, approved, and certified by Underwriters Laboratories at the manufacturer's expense. The test results will be provided to the Fire Department at the time of delivery.

### **BREATHING AIR TEST**

If the unit has breathing air, Pierce Manufacturing will draw an air sample from the air system and certify that the air quality meets the requirements of NFPA 1989, *Standard on Breathing Air Quality for Fire and Emergency Services Respiratory Protection*.

### **AFTERMARKET SUPPORT WEBSITE**

Pierceparts.com will provide Pierce authorized dealer access to comprehensive information pertaining to the maintenance and service of their customer's apparatus. This tool will provide the Pierce authorized dealer the ability to service and support their customers to the best of their ability with factory support at their fingertips.

Pierceparts.com is also accessible to the end user through the guest login. Limited access is available and vehicle specific parts information accessible by entering a specific VIN number. All end users should see their local authorized Pierce dealer for additional support and service.

The website will consist of the following screens at the dealer level:

#### **My Fleet Screen**

The My Fleet screen will provide access to truck detail information on the major components of the vehicle, warranty information, available vehicle photographs, vehicle drawings, sales options, applicable vehicle software downloads, etc.

## **Parts Screens**

The Parts screens will provide parts look-up capability of Pierce Manufacturing sourced items, with the aid of digital photographs, part drawings and assembly drawings. The parts search application will permit the searching of parts by item description or function group (major system category). The parts application will provide the ability to submit electronically a parts order, parts quote, or parts return request directly to Pierce Manufacturing for processing.

## **Warranty Screen**

The Warranty screens will provide dealers the ability to submit electronically warranty claims directly to Pierce Manufacturing for reimbursement.

## **My Reports Screens**

The My Reports screens will provide access to multiple dealer reports to allow the dealership to maintain communication with the customer on the status of orders, claims, and phone contacts.

## **Technical Support Screens**

The Technical Support screens will provide access to all currently published Operation and Maintenance and Service Publications. Access to Pierce Manufacturing Service Bulletins and Work Instructions, containing information on current service topics and recommendations will be provided.

## **Training**

The Training screens will provide access to upcoming training classes offered by Pierce Manufacturing along with interactive electronic learning modules (Operators Guides) covering the operation of major vehicle components will be provided. Access to training manuals used in Pierce Manufacturing training classes will be provided.

## **About Pierce**

Access to customer service articles, corporate news, quarterly newsletters, and key contacts within the Customer Service Department will be provided. The current Customer Service Policy and Procedure Manual, detailing the operation of the Customer Service group will also be accessible.

## **BID BOND**

A bid bond as security for the bid in the form of a 10% bid bond will be provided with the proposal. This bid bond will be issued by a Surety Company who is listed on the U.S. Treasury Departments list of acceptable sureties as published in Department Circular 570. The bid bond will be issued by an authorized representative of the Surety Company and will be accompanied by a certified power of attorney dated on or before the date of bid. The bid bond will include language which assures that the bidder/principal will give a bond or bonds, as may be specified in the bidding or contract documents, with good and sufficient surety for the faithful performance of the contract, including the Basic One (1)

Year Limited Warranty, and for the prompt payment of labor and material furnished in the prosecution of the contract.

Notwithstanding any document or assertion to the contrary, any surety bond related to the sale of a vehicle will apply only to the Basic One (1) Year Limited Warranty for such vehicle. Any surety bond related to the sale of a vehicle will not apply to any other warranties that are included within this bid (OEM or otherwise) or to the warranties (if any) of any third party of any part, component, attachment or accessory that is incorporated into or attached to the vehicle. In the event of any contradiction or inconsistency between this provision and any other document or assertion, this provision will prevail.

#### **PERFORMANCE BOND NOT REQUESTED**

A performance bond will not be included. If requested at a later date, one will be provided to you for an additional cost and the following will apply:

The successful bidder will furnish a Performance and Payment bond (Bond) equal to 100 percent of the total contract amount within 30 days of the notice of award. Such Bond will be in a form acceptable to the Owner and issued by a surety company included within the Department of Treasury's Listing of Approved Sureties (Department Circular 570) with a minimum A.M. Best Financial Strength Rating of A and Size Category of XV. In the event of a bond issued by a surety of a lesser Size Category, a minimum Financial Strength rating of A+ is required.

Bidder and Bidder's surety agree that the Bond issued hereunder, whether expressly stated or not, also includes the surety's guarantee of the vehicle manufacturer's Bumper to Bumper warranty period included within this proposal. Owner agrees that the penal amount of this bond will be simultaneously amended to 25 percent of the total contract amount upon satisfactory acceptance and delivery of the vehicle(s) included herein. Notwithstanding anything contained within this contract to the contrary, the surety's liability for any warranties of any type will not exceed three (3) years from the date of such satisfactory acceptance and delivery, or the actual Bumper to Bumper warranty period, whichever is shorter.

#### **APPROVAL DRAWING**

A drawing of the proposed apparatus will be prepared and provided to the purchaser for approval before construction begins. The Pierce sales representative will also be provided with a copy of the same drawing. The finalized and approved drawing will become part of the contract documents. This drawing will indicate the chassis make and model, location of the lights, siren, horns, compartments, major components, etc.

A "revised" approval drawing of the apparatus will be prepared and submitted by Pierce to the purchaser showing any changes made to the approval drawing.

#### **COMPARTMENT LAYOUT DRAWING**

A sales drawing will be provided as if the rear body compartment doors are open. This drawing will be provided for graphic representation only and will include such things as shelves, trays, reels, dividers, air control panels, air bottle storage bins, poly boxes, etc.



## **ELECTRICAL WIRING DIAGRAMS**

Two (2) electrical wiring diagrams, prepared for the model of chassis and body, will be provided.

## **ARROW XT CHASSIS**

The Pierce Arrow XT™ is the custom chassis developed exclusively for the fire service. Chassis provided will be a new, tilt-type custom fire apparatus. The chassis will be manufactured in the apparatus body builder's facility eliminating any split responsibility. The chassis will be designed and manufactured for heavy-duty service, with adequate strength, capacity for the intended load to be sustained, and the type of service required. The chassis will be the manufacturer's heavy-duty line tilt cab.

## **MAXIMUM OVERALL HEIGHT**

The maximum overall height of the apparatus will be 11' 11".

## **WHEELBASE**

The wheelbase of the vehicle will be 270.50.

## **GVW RATING**

The gross vehicle weight rating will be 76,800.

## **FRAME**

The chassis frame will be built with two (2) steel channels bolted to five (5) cross members or more, depending on other options of the apparatus. The side rails will have a 13.38" tall web over the front and mid sections of the chassis, with a continuous smooth taper to 10.75" over the rear axle. Each rail will have a section modulus of 25.992 cubic inches and a resisting bending moment (rbm) of 3,119,040 in-lb over the critical regions of the frame assembly, with a section modulus of 18.96 cubic inches with an rbm of 2,275,200 in-lb over the rear axle. The frame rails will be constructed of 120,000 psi yield strength heat-treated 0.38" thick steel with 3.50" wide flanges.

## **FRAME REINFORCEMENT**

In addition, a full-length mainframe internal "C" liner will be provided. The liner will be an internal "C" design that steps to a smaller internal "C" design over the rear axle. It will be heat-treated steel measuring 12.50" x 3.00" x 0.25" through the front "C" portion of the liner, stepping to 9.38" x 3.00" x 0.25" through the rear "C" portion of the liner. Each liner will have a section modulus of 13.58 cubic inches, yield strength of 110,000 psi, and rbm of 857,462 in-lb. Total rbm at wheelbase center will be 4,391,869 in-lb.

The frame liner will be mounted inside of the chassis frame rail and extend the full length of the frame.

## **FRONT NON DRIVE AXLE**

The Oshkosh TAK-4® front axle will be of the independent suspension design with a ground rating of 24,000 lb.

Upper and lower control arms will be used on each side of the axle. Upper control arm castings will be made of 100,000-psi yield strength 8630 steel and the lower control arm casting will be made of 55,000-psi yield ductile iron.

The center cross members and side plates will be constructed out of 80,000-psi yield strength steel.

Each control arm will be mounted to the center section using elastomer bushings. These rubber bushings will rotate on low friction plain bearings and be lubricated for life. Each bushing will also have a flange end to absorb longitudinal impact loads, reducing noise and vibrations.

There will be nine (9) grease fittings supplied, one (1) on each control arm pivot and one (1) on the steering gear extension.

The upper control arm will be shorter than the lower arm so that wheel end geometry provides positive camber when deflected below rated load and negative camber above rated load.

Camber at load will be zero degrees for optimum tire life.

The ball joint bearing will be of low friction design and be maintenance free.

Toe links that are adjustable for alignment of the wheel to the center of the chassis will be provided.

The wheel ends must have little to no bump steer when the chassis encounters a hole or obstacle.

The steering linkage will provide proper steering angles for the inside and outside wheel, based on the vehicle wheelbase.

The axle will have a third party certified turning angle of 45 degrees. Front discharge, front suction, or aluminum wheels will not infringe on this crank angle.

### **FRONT SUSPENSION**

Front Oshkosh TAK-4™ independent suspension will be provided with a minimum ground rating of 24,000 lb.

The independent suspension system has been designed to provide maximum ride comfort. The design will allow the vehicle to travel at highway speeds over improved road surfaces and at moderate speeds over rough terrain with minimal transfer of road shock and vibration to the vehicle's crew compartment.

Each wheel will have a torsion bar type spring. In addition, each front wheel end will also have energy absorbing jounce bumpers to prevent bottoming of the suspension.

The suspension design will be such that there is at least 10.00" of total wheel travel and a minimum of 3.75" before suspension bottoms.

The torsion bar anchor lock system allows for simple lean adjustments, without the use of shims. One can adjust for a lean within 15 minutes per side. Anchor adjustment design is such that it allows for ride height adjustment on each side.

The independent suspension was put through a durability test that simulated 140,000 miles of inner city driving.

### **FRONT SHOCK ABSORBERS**

KONI heavy-duty telescoping shock absorbers will be provided on the front suspension.

### **FRONT OIL SEALS**

Oil seals with viewing window will be provided on the front axle.

### **FRONT TIRES**

Front tires will be Goodyear 425/65R22.50 radials, 20 ply G296 tread, rated for 24,400 lb maximum axle load and 68 mph maximum speed.

The tires will be mounted on Alcoa 22.50" x 12.25" polished aluminum disc type wheels with a ten (10)stud, 11.25" bolt circle.

### **REAR AXLE**

The rear axle will be a Meritor™, Model RT58-185, tandem axle assembly with a capacity of 58,000 lb.

An inter-axle differential, which divides torque evenly between axles, will be provided, with an indicator light mounted on the cab instrument panel.

### **TOP SPEED OF VEHICLE**

A rear axle ratio will be furnished to allow the vehicle to reach a top speed of 60 mph.

### **REAR SUSPENSION**

Rear suspension will be Link® combination air ride and walking beam with a ground rating of 60,000 lb.

### **REAR OIL SEALS**

Oil seals will be provided on the rear axle(s).

### **REAR TIRES**

Rear tires will be eight (8) Goodyear 12R22.50 radials, LRH all season G622 RSD tread, rated for 58,040 lb maximum axle load and 65 mph maximum speed. The tires will be fire service load rated.

The tires will be mounted on Alcoa® 22.50" x 8.25" polished aluminum disc wheels with a ten (10) stud 11.25" bolt circle.

### **TIRE BALANCE**

All tires will be balanced with Counteract balancing beads. The beads will be inserted into the tire and eliminate the need for wheel weights.

## **TIRE PRESSURE MANAGEMENT**

There will be a RealWheels LED AirSecure™ tire alert pressure management system provided, that will monitor each tire's pressure. A sensor will be provided on the valve stem of each tire for a total of 10 tires.

The sensor will calibrate to the tire pressure when installed on the valve stem for pressures between 10 and 200 psi. The sensor will activate an integral battery operated LED when the pressure of that tire drops 5 to 8 psi.

Removing the cap from the sensor will indicate the functionality of the sensor and battery. If the sensor and battery are in working condition, the LED will immediately start to flash.

## **FRONT HUB COVERS**

Stainless steel hub covers will be provided on the front axle. An oil level viewing window will be provided.

## **REAR HUB COVERS**

Stainless steel, high hat, hub covers will be provided on the rear axle hubs.

## **CHROME LUG NUT COVERS**

Chrome lug nut covers will be supplied on front and rear wheels.

## **MUD FLAPS**

Mud flaps with a Pierce logo will be installed behind the front and rear wheels.

## **WHEEL CHOCKS**

There will be one (1) pair of folding Ziamatic, Model SAC-44-E, aluminum alloy, Quick-Choc wheel blocks, with easy-grip handle provided.

## **Wheel Chock Brackets**

There will be one (1) pair of Zico, Model SQCH-44-H, horizontal mounting wheel chock brackets provided for the Ziamatic, Model SAC-44-E, folding wheel chocks. The brackets will be made of aluminum and consist of a quick release spring loaded rod to hold the wheel chocks in place. The brackets will be mounted forward of the left side rear tire.

## **ELECTRONIC STABILITY CONTROL**

A vehicle control system will be provided as an integral part of the ABS brake system from Meritor Wabco.

The system will monitor and update the lateral acceleration of the vehicle and compare it to a critical threshold where a side roll event may occur. If the critical threshold is met, the vehicle control system will automatically reduce engine RPM, engage the engine retarder (if equipped), and selectively apply brakes to the individual wheel ends of the front and rear axles to reduce the possibility of a side roll event.

The system will monitor directional stability through a lateral accelerometer, steer angle sensor and yaw rate sensor. If spinout or drift out is detected, the vehicle control system will selectively apply brakes to the individual wheel ends of the front and rear axles to bring the vehicle back to its intended direction.

### **ANTI-LOCK BRAKE SYSTEM**

The vehicle will be equipped with a Wabco 6S6M, anti-lock braking system. The ABS will provide a six (6) channel anti-lock braking control on both the front and rear wheels. A digitally controlled system that utilizes microprocessor technology will control the anti-lock braking system. Each wheel will be monitored by the system. When any wheel begins to lockup, a signal will be sent to the control unit. This control unit will then reduce the braking of that wheel for a fraction of a second and then reapply the brake. This anti-lock brake system will eliminate the lockup of any wheel thus helping to prevent the apparatus from skidding out of control.

### **AUTOMATIC TRACTION CONTROL**

An anti-slip feature will be included with the ABS. The Automatic Traction Control will be used for traction in poor road and weather conditions. The Automatic Traction Control will act as an electronic differential lock that will not allow a driving wheel to spin, thereby supplying traction at all times. The ABS electronic control unit (ECU) will work with the engine ECU, sharing information concerning wheel slip. Engine ECU will use information to control engine speed, allowing only as much throttle application as required for the available traction, regardless of how much the driver is asking for. An "off road traction" switch will be provided on the instrument panel. Activation of the switch will allow additional tire slip to let the truck climb out and get on top of deep snow or mud.

### **BRAKES**

The service brake system will be full air type.

The front brakes will be Knorr/Bendix disc type with a 17.00" ventilated rotor for improved stopping distance.

The brake system will be certified, third party inspected, for improved stopping distance.

The rear brakes will be Meritor™ 16.50" x 8.63" cam operated with automatic slack adjusters.

### **AIR COMPRESSOR, BRAKE SYSTEM**

The air compressor will be a Bendix®, Model BA-921, with 15.80 cubic feet per minute output at 1,250 rpm.

### **BRAKE SYSTEM**

The brake system will include:

- Bendix dual brake treadle valve
- Heated automatic moisture ejector on air dryer
- Total air system capacity of 8,108 cubic inches

- Two (2) air pressure gauges with a red warning light and an audible alarm, that activates when air pressure falls below 60 psi
- Spring set parking brake system
- Parking brake operated by a push-pull style control valve
- A parking "brake on" indicator light on instrument panel
- Park brake relay/inversion and anti-compounding valve, in conjunction with a double check valve system, will be provided with an automatic spring brake application at 40 psi
- A pressure protection valve will be provided to prevent all air operated accessories from drawing air from the air system when the system pressure drops below 80 psi (550 kPa)
- 1/4 turn drain valve on each air tank

The air tank will be primed and painted to meet a minimum 750 hour salt spray test.

To reduce the effects of corrosion, the air tank will be mounted with stainless steel brackets.

### **BRAKE SYSTEM AIR DRYER**

The air dryer will be WABCO System Saver 1200 with spin-on coalescing filter cartridge and 100 watt heater.

### **BRAKE LINES**

Color-coded nylon brake lines will be provided. The lines will be wrapped in a heat protective loom in the chassis areas that are subject to excessive heat.

### **AIR INLET**

One (1) air inlet with 3D series male coupling will be provided. It will allow station air to be supplied to the apparatus brake system through a shoreline hose. The inlet will be located forward in the driver side lower step well of cab. A check valve will be provided to prevent reverse flow of air. The inlet will discharge into the "wet" tank of the brake system. A mating female fitting will also be provided with the loose equipment.

### **ALL WHEEL LOCK-UP**

An additional all wheel lock-up system will be installed which applies air to the front brakes only. The standard spring brake control valve system will be used for the rear.

### **ENGINE**

The chassis will be powered by an electronically controlled engine as described below:

Make:	Detroit™
Model:	DD13®
Power:	525 hp at 1625 rpm
Torque:	1850 lb-ft at 1075 rpm
Governed Speed:	Full Load - 1900 rpm Road/2080 rpm Parked PTO
Emissions Certification:	EPA 2016 (GHG17)
Fuel:	Diesel

Cylinders:	Six (6)
Displacement:	781 cubic inches (12.8L)
Starter:	Delco Remy 39MT™
Fuel Filters:	Dual cartridge style with check valve, water separator, and water in fuel sensor

The engine will include On-board diagnostics (OBD), which provides self diagnostic and reporting. The system will give the owner or repair technician access to state of health information for various vehicle sub systems. The system will monitor vehicle systems, engine and after treatment. The system will illuminate a malfunction indicator light on the dash console if a problem is detected.

### **REPTO DRIVE**

A rear engine power take off will be provided to drive the water pump. A vibration dampener will be provided between the REPTO and water pump. Transmission PTO's used to drive the water pump will not be allowed due to their lower torque ratings. The rear engine power take off will be the same as used extensively throughout the construction industry. Rear engine PTO's allow for continuous 240 hp and 480 lb-ft torque ratings needed for large pump applications. The rear engine power take off will have the same warranty as the engine provided by the engine manufacturer.

### **HIGH IDLE**

A high idle switch will be provided, inside the cab, on the instrument panel, that will automatically maintain a preset engine rpm. A switch will be installed, at the cab instrument panel, for activation/deactivation.

The high idle will be operational only when the parking brake is on and the truck transmission is in neutral. A green indicator light will be provided, adjacent to the switch. The light will illuminate when the above conditions are met. The light will be labeled "OK to Engage High Idle."

### **ENGINE BRAKE**

A Jacobs engine brake is to be installed with the controls located on the instrument panel within easy reach of the driver.

The driver will be able to turn the engine brake system on/off and have high, medium and low setting.

The engine brake will be installed in such a manner that when the engine brake is slowing the vehicle the brake lights are activated.

The ABS system will automatically disengage the auxiliary braking device, when required.

### **CLUTCH FAN**

A Horton® fan clutch will be provided. The fan clutch will be automatic when the pump transmission is in "Road" position, and fully engaged in "Pump" position.

## **ENGINE AIR INTAKE**

The air intake with an ember separator will be mounted high on the passenger side of the cab, to the front of the crew cab door. The ember separator is designed to prevent road dirt and recirculating hot air from entering the engine. The ember separator will be easily accessible through a hinged stainless steel grille, with one (1) flush quarter turn latch.

## **EXHAUST SYSTEM**

The exhaust system will include a diesel particulate filter (DPF) and a selective catalytic reduction (SCR) device to meet current EPA standards. The exhaust system will be stainless steel from the turbo to the inlet of the SCR device and will be 5.00" in diameter. An insulation wrap will be provided on all exhaust pipes between the turbo and SCR to minimize the transfer of heat to the cab. The exhaust will terminate horizontally ahead of the right side rear wheels. A tailpipe diffuser will be provided to reduce the temperature of the exhaust as it exits. Heat deflector shields will be provided to isolate chassis and body components from the heat of the tailpipe diffuser.

## **RADIATOR**

The radiator and the complete cooling system will meet or exceed NFPA and engine manufacturer cooling system standards.

For maximum corrosion resistance and cooling performance, the entire radiator core will be constructed using long life aluminum alloy. The core will be made of aluminum fins, having a serpentine design, brazed to aluminum tubes. The tubes will be brazed to aluminum headers. No solder joints or leaded material of any kind will be acceptable in the core assembly. The radiator core will have a minimum frontal area of approximately 1,352 square inches. Supply tank made of glass-reinforced nylon and a return tank of cast aluminum alloy will be crimped on to the core assembly using header tabs and a compression gasket to complete the radiator core assembly. The radiator will be compatible with commercial antifreeze solutions.

There will be a full steel frame around the entire radiator core assembly. The radiator core assembly will be isolated within the steel frame by rubber inserts to enhance cooling system durability and reliability. The radiator will be mounted in such a manner as to prevent the development of leaks caused by twisting or straining when the apparatus operates over uneven ground. The radiator assembly will be isolated from the chassis frame rails with rubber isolators.

The radiator assembly will include an integral de-aeration tank permanently mounted to the top of the radiator framework, with a readily accessible remote-mounted overflow tank. For visual coolant level inspection, the radiator will have a built-in sight glass. The radiator will be equipped with a 15 psi pressure relief cap.

A drain port will be located at the lowest point of the cooling system and/or the bottom of the radiator to permit complete flushing of the coolant from the system.

A heavy-duty fan will draw in fresh, cool air through the radiator. Shields or baffles will be provided to prevent recirculation of hot air to the inlet side of the radiator.



### **COOLANT LINES**

Gates, or Goodyear, rubber hose will be used for all engine coolant lines installed by Pierce Manufacturing.

Hose clamps will be stainless steel constant torque type to prevent coolant leakage. They will expand and contract according to coolant system temperature thereby keeping a constant clamping pressure on the hose.

### **FUEL TANK**

A 65 gallon fuel tank will be provided and mounted at rear of chassis. The tank will be constructed of 12-gauge, hot rolled steel. It will be equipped with swash partitions and a vent. To eliminate the effects of corrosion, the fuel tank will be mounted with stainless steel straps.

A .75" drain plug will be provided in a low point of the tank for drainage.

A fill inlet will be located on the left hand and right hand sides of the body and be covered with a hinged, spring loaded, stainless steel door that is marked "Ultra Low Sulfur - Diesel Fuel Only."

A .50" diameter vent will be provided running from top of tank to just below fuel fill inlets.

The tank will meet all FHWA 393.67 requirements including a fill capacity of 95 percent of tank volume.

Servicing the fuel tank pick-up tubes and fuel gauge sending unit will be capable of being accomplished by draining fuel and dropping tank.

All fuel lines will be provided as recommended by the engine manufacturer.

### **DIESEL EXHAUST FLUID TANK**

A 4.5 gallon diesel exhaust fluid (DEF) tank will be provided and mounted in the driver's side body forward of the rear axle.

A 0.50" drain plug will be provided in a low point of the tank for drainage.

A fill inlet will be located on the driver's side of the body and be covered with a hinged, spring loaded, polished stainless steel door that is marked "Diesel Exhaust Fluid Only".

The tank will meet the engine manufacturers requirement for 10 percent expansion space in the event of tank freezing.

The tank will include an integrated heater unit that utilizes engine coolant to thaw the DEF in the event of freezing.

### **AUXILIARY FUEL PUMP**

An auxiliary electric fuel pump will be added to the fuel line for priming the engine. A switch located on the cab instrument panel will be provided to operate the pump.

### **FUEL COOLER**

An air to fuel cooler will be installed in the engine fuel return line.

### **TRANSMISSION**

An Allison 5th generation, model EVS 4000PR, electronic, torque converting, automatic transmission with retarder will be provided.

The transmission will be equipped with prognostics to monitor oil life, filter life, and transmission health. A wrench icon on the shift selector's digital display will indicate when service is due.

Two (2) PTO openings will be located on left side and top of converter housing (positions 8 o'clock and 1 o'clock).

A transmission temperature gauge, with red light and audible alarm, will be installed on the cab instrument panel.

The transmission retarder control will be (RET9) activated by letting off the throttle pedal. Retarder activation is adjustable, using the dash mounted hand lever, in 1/6 increments. The retarder is also activated 100 percent at 2 psi by applying the brake pedal.

The transmission will have the 1600 ft. lb. torque (medium) spring setting for retardation force.

The transmission retarder will have a master "on/off" switch on the instrument panel. A red indicator light will be provided to warn that the transmission is being overworked.

The retarder will be wired to the brake lights so they are energized when the retarder is slowing the vehicle down.

The ABS system will automatically disengage the auxiliary braking device when required.

### **TRANSMISSION SHIFTER**

A six (6)-speed push button shift module will be mounted to right of driver on console. Shift position indicator will be indirectly lit for after dark operation.

The transmission ratio will be:

1st	3.51 to 1.00
2nd	1.91 to 1.00
3rd	1.43 to 1.00
4th	1.00 to 1.00
5th	0.75 to 1.00
6th	0.64 to 1.00

R	4.80 to 1.00
---	--------------

### **TRANSMISSION PROGRAMMING**

The transmission will be programmed to automatically shift the transmission to neutral when the parking brake is set to simplify operation and increase operational safety.

### **TRANSMISSION COOLER**

An externally mounted Modine bar plate transmission oil cooler will be provided using engine coolant to control the transmission oil temperature. The internal bar plates will be constructed of stainless steel. The cooler's housing will be constructed of 1020 steel, coated to protect from corrosion. The cooler will be tagged with information including OEM part number, vendor serial number and date / lot code.

An externally mounted Modine bar plate transmission oil cooler will be provided using engine coolant to control the transmission retarder oil temperature. The internal bar plates will be constructed of stainless steel. The cooler's housing will be constructed of 1020 steel, coated to protect from corrosion. The cooler will be tagged with information including OEM part number, vendor serial number and date / lot code.

### **DRIVELINE**

Drivelines will be a heavy-duty metal tube and be equipped with Spicer® 1810 universal joints.

The shafts will be dynamically balanced before installation.

A splined slip joint will be provided in each driveshaft where the driveline design requires it. The slip joint will be coated with Glidecoat® or equivalent.

### **STEERING**

Dual Sheppard, Model M110, steering gears, with integral heavy-duty power steering, will be provided. For reduced system temperatures, the power steering will incorporate an air to oil cooler and an Eaton, Model VN20, hydraulic pump with integral pressure and flow control. All power steering lines will have wire braded lines with crimped fittings.

A tilt and telescopic steering column will be provided to improve fit for a broader range of driver configurations.

### **STEERING WHEEL**

The steering wheel will be 18.00" in diameter, have tilting and telescoping capabilities, and a 4-spoke design.

### **LOGO AND CUSTOMER DESIGNATION ON DASH**

The dash panel will have an emblem containing the Pierce logo and customer name. The emblem will have three (3) rows of text for the customer's department name. There will be a maximum of eight (8) characters in the first row, 11 characters in the second row and 11 characters in the third row.

The first row of text will be: Santa Fe

The second row of text will be: Springs

The third row of text will be: Fire Dept.

### **BUMPER**

A one (1) piece, ten (10) gauge, 304-2B type polished stainless steel bumper, minimum of 10.00" high, will be attached to a bolted modular extension frame constructed of 50,000 psi tensile steel "C" channel mounted directly behind it to provide adequate support strength.

The bumper will be extended 16.00" from front face of cab.

### **Gravel Pan**

A gravel pan, constructed of bright aluminum treadplate, will be furnished between the bumper and cab face. The gravel pan will be properly supported from the underside to prevent flexing and vibration of the aluminum treadplate.

### **LEFT SIDE HOSE TRAY**

A hose tray will be placed in the left side of the extended bumper.

The tray will have a capacity of 100' of 1.75" double jacket cotton-polyester hose.

Black rubber grating will be provided at the bottom of the tray. Drain holes will be provided.

### **Left Side Hose Tray Restraint**

There will be one (1) pair hose tray restraint straps located over the left side mounted tray.

The restraints will be a pair of 2.00" wide black nylon straps with Velcro® fasteners provided. The strap(s) will be used to secure the hose in the tray.

### **LIFT AND TOW MOUNTS**

Mounted to the frame extension will be lift and tow mounts. The lift and tow mounts will be designed and positioned to adapt to certain tow truck lift systems.

The lift and tow mounts with eyes will be painted the same color as the frame.

### **TOW HOOKS**

No tow hooks are to be provided. This truck will be equipped with a lift and tow package with integral tow eyes.

### **CAB**

The Arrow XT cab will be designed specifically for the fire service and will be manufactured by the chassis builder.

The cab will be built by the apparatus manufacturer in a facility located on the manufacturer's premises.

For reasons of structural integrity and enhanced occupant protection, the cab will be of heavy duty design, constructed to the following minimal standards.

The cab will have 12 main vertical structural members located in the A-pillar (front cab corner posts), B-pillar (side center posts), C-pillar (rear corner posts) and rear wall areas. The A-pillar will be constructed of solid A356-T5 aluminum. The B-pillar and C-pillar will be constructed from 0.25" heavy wall extrusions. The rear wall will be constructed of two (2) 4.00" x 2.00" outer aluminum extrusions and two (2) 3.00" x 2.00" inner aluminum extrusions. All main vertical structural members will run from the floor to 6.50" x 4.875" x 0.1875" thick roof extrusions to provide a cage-like structure with the A-pillar and roof extrusions being welded into a 0.36" thick corner casting at each of the front corners of the roof assembly.

The front of the cab will be constructed of a 0.25" thick gusset plate, covered with a 0.090" front skin (for a total thickness of 0.34"), and reinforced with a 95.00" wide x 11.13" deep x 0.50" thick cross-cab support located just below the windshield. The cross-cab support will run the full width of the cab and weld to each A-pillar, the 0.25" thick gusset plate and the front skin.

The cab floors will be constructed of 0.1875" thick aluminum plate and reinforced at the firewall with an additional 0.50" thick cross-floor support providing a total thickness of 0.6875" of structural material at the front floor area. The front floor area will also be supported with one (1) 0.50" plate bolted to one (1) 0.78" plate that also provides the mounting point for the cab lift. This tubing will run from the front of the cab to the 0.187" thick engine tunnel, creating the structure to support the forces created when lifting the cab.

The cab will be 94.75" wide (outside door skin to outside door skin) to maintain maximum maneuverability.

The forward cab section will have an overall height (from the cab roof to the ground) of approximately 103.00". The crew cab section will have a 10.00" raised roof, with an overall cab height of approximately 113.00". The overall height listed will be calculated based on a truck configuration with the lowest suspension weight ratings, the smallest diameter tires for the suspension, no water weight, no loose equipment weight, and no personnel weight. Larger tires, wheels, and suspension will increase the overall height listed.

The raised roof section of the crew cab will have a 58.00" wide x 10.00" high square notch in the center section of the roof. This will allow the aerial device to be bedded in the same location as a non-raised roof.

The floor to ceiling height inside the crew cab will be 52.00" in the center and 69.25" in the outboard positions.

The crew cab floor will measure 40.12" from rear wall to the back side of engine tunnel.

The engine tunnel, at the rearward highest point (knee level), will measure 47.75" to the back wall.

The crew cab will be of the totally enclosed design with access doors constructed in the same manner as the driver and passenger doors.

The cab will be a full tilt cab style.

A 3-point cab mount system with rubber isolators will improve ride quality by isolating chassis vibrations from the cab.

#### **CAB ROOF DRIP RAIL**

For enhanced protection from inclement weather, a drip rail will be furnished on the sides of the cab. The drip rail will be constructed of bright polished extruded aluminum, and be bonded to the sides of the cab. The drip rail will extend the full length of the cab roof.

#### **CAB PUMP ENCLOSURE**

The rear of the cab will be made to house the fire pump below the forward facing crew cab seats. The cab side panels will be notched to accommodate the pump panel.

#### **INTERIOR CAB INSULATION**

The cab will include 1.50" insulation in the ceiling and side walls, and 2.00" insulation in the rear wall to maximize acoustic absorption and thermal insulation.

#### **FENDER LINERS**

Full circular inner fender liners in the wheel wells will be provided.

#### **WINDSHIELD**

A curved safety glass windshield will be provided with over 2,754 square inches of clear viewing area. The cab windshield will have bright trim inserts in the rubber molding holding the glass in place. Economical windshield replacement glass will be readily available from local auto glass suppliers.

All cab glass will be tinted.

#### **WINDSHIELD WIPERS**

Two (2) electric windshield wipers with washer will be provided that meet FMVSS and SAE requirements.

The washer reservoir will be able to be filled without raising the cab.

#### **GLOVE BOX**

A glove box with a drop-down door will be installed in the front dash panel in front of the officer's position.

#### **ENGINE TUNNEL**

Engine hood side walls will be constructed of 0.50" aluminum. The top will be constructed of 0.19" aluminum and will be tapered at the top to allow for more driver and passenger elbow room.

The engine hood will be insulated for protection from heat and sound. The noise insulation keeps the dBA level within the limits stated in the current NFPA 1901 standards.

### **CAB REAR WALL EXTERIOR COVERING**

The exterior surface of the rear wall of the cab will be overlaid with bright aluminum treadplate except for areas that are not typically visible when the cab is lowered.

### **CAB LIFT**

A hydraulic cab lift system will be provided consisting of an electric powered hydraulic pump, dual lift cylinders, and necessary hoses and valves.

The hydraulic pump will have a manual override for backup in the event of electrical failure.

Lift controls will be on a panel located on the right side pump panel or front area of the body in a convenient location.

The engine will be easily accessible and capable of being removed with the cab tilted. The cab will be capable of tilting 45 degrees and 90 degrees with crane assist.

Cab will be locked down by a 2-point automatic spring-loaded hook mechanism that actuates after the cab has been lowered.

The hydraulic cylinders will be equipped with a velocity fuse that protects the cab from accidentally descending when the control is located in the tilt position.

For increased safety, a redundant mechanical stay arm will be provided that must be manually put in place on the driver side between the chassis and cab frame when the cab is in the raised position. This device will be manually stowed to its original position before the cab can be lowered.

### **Cab Lift Interlock**

The cab lift system will be interlocked to the parking brake. The cab tilt mechanism will be active only when the parking brake is set and the ignition switch is in the on position. If the parking brake is released, the cab tilt mechanism will be disabled.

### **GRILLE**

A bright finished aluminum mesh grille screen, inserted behind a bright finished grille surround, will be provided on the front center of the cab.

### **DOOR JAMB SCUFFPLATES**

All cab door jambs will be furnished with a polished stainless steel scuffplate, mounted on the striker side of the jamb.

### **MIRRORS**

Ramco, Model 6001FFR-750, polished aluminum 9.25" wide x 13.50" high mirrors, with a full flat glass section, will be mounted on each side of the front cab corner.

A convex section will be bolted to the top of each mirror.

The flat glass in each mirror will be adjustable with remote controls that are convenient to the driver.

The convex section in each mirror will be adjusted manually.

## **DOORS**

To enhance entry and egress to the cab, the forward cab doors will be a minimum of 37.50" wide x 61.75" high. The crew cab doors will be located on the sides of the cab and will be constructed in the same manner as the forward cab doors. The crew cab doors will measure a minimum of 34.88" wide x 71.75" high.

The forward cab and crew cab doors will be constructed of extruded aluminum with a nominal material thickness of 0.125". The exterior door skins will be constructed from 0.090" aluminum.

A flush mounted, chrome plated paddle type door handle will be provided on the exterior of each cab door. Each door will also be provided with an interior flush paddle handle.

The cab doors will be provided with both interior (rotary knob) and exterior (keyed) locks as required by FMVSS 206. The locks will be capable of activating when the doors are open or closed. The doors will remain locked if locks are activated when the doors are opened, then closed.

A full length, heavy duty, stainless steel, piano-type hinge with a 0.38" pin and 11 gauge leaf will be provided on all cab doors. There will be double automotive-type rubber seals around the perimeter of the door framing and door edges to ensure a weather-tight fit.

A chrome grab handle will be provided on the inside of each cab and crew cab door.

The cab steps at each door location will be located below the cab doors and will be exposed to the exterior of the cab.

## **Door Panels**

There will be a full height brushed stainless steel door panel installed on the inside of all cab doors. The cab door panels will be removable without disconnecting door and window mechanisms.

## **ELECTRIC OPERATED CAB DOOR WINDOWS**

All four (4) cab doors will be equipped with electric operated windows with flush mounted automotive style switches.

The driver's side lower instrument panel will also have three (3) controls, officer's door window and both crew cab door windows.

## **ELECTRIC CAB DOOR LOCKS**

The front driver and officer doors will have a door lock master switch that will control all front and rear crew cab door locks. Each rear crew cab door will have its own lock control.

There will be one (1) concealed switch located in an easily accessible chassis specific location that will unlock all the doors.

The lock system will include two (2) key FOBs that allow for keyless entry into the vehicle. The key FOB system will use code hopping technology for high security and be FCC part 15 compliant.



### **KEY PAD FOR ELECTRIC DOOR LOCKS**

For improved convenience, the cab door locks will include a Trimark keypad entry system to provide complete keyless entry to the cab. There will be two (2) keypads provided, located one (1) each side of the cab behind the front cab doors. The keypads will include visual and audio feedback to confirm activation and acknowledge correct entry code. For enhanced night time use, the keypads will be lighted. For increased security, the system will allow over 3,000 possible code combinations.

### **CAB STEPS**

The forward cab and crew cab access steps will be a full size two (2) step design to provide largest possible stepping surfaces for safe ingress and egress. The bottom steps will be designed with a grip pattern punched into bright aluminum treadplate material to provide support, slip resistance, and drainage. The bottom steps will be a bolt-in design to minimize repair costs should they need to be replaced. The forward cab steps will be a minimum 24.75" wide, and the crew cab steps will be 21.25" wide with an 8.00" minimum depth. The inside cab steps will not exceed 18.00" in height and be limited to two (2) steps.

### **CAB EXTERIOR HANDRAILS**

A Hansen knurled aluminum handrail will be provided adjacent to each cab and crew cab door opening to assist during cab ingress and egress. Each handrail will be provided with blue LED lights. The lights will be activated when the parking brake is applied. The LED lights may be load managed.

### **STEP LIGHTS**

For reduced overall maintenance costs compared to incandescent lighting, there will be four (4) white LED step lights provided. The lights will be installed at each cab and crew cab door, one (1) per step. The lights will be located in the driver side front doorstep, driver side crew cab doorstep, passenger side front doorstep and passenger side crew cab doorstep.

In order to ensure exceptional illumination, each light will provide a minimum of 25 foot-candles (fc) covering an entire 15.00" x 15.00" square placed 10.00" below the light and a minimum of 1.5 fc covering an entire 30.00" x 30.00" square at the same 10.00" distance below the light.

The lights will be activated when the adjacent door is opened.

### **FENDER CROWNS**

Stainless steel fender crowns will be installed at the cab wheel openings. The fender crowns will have a radius outside corner that will allow the fender crown to extend out further than the standard width crown, thus extending beyond the sidewall of the front tires and allow the crew cab doors to open fully.

### **LEFT SIDE UPPER CREW CAB DOOR WINDOW TINT**

The upper window in the left side crew cab door will be tinted privacy dark gray.

### **LEFT SIDE ROLLUP CREW CAB DOOR WINDOW TINT**

The rollup window in the left side crew cab door will be tinted privacy dark gray.

### **RIGHT SIDE UPPER CREW CAB DOOR WINDOW TINT**

The upper window in the right side crew cab door will be tinted privacy dark gray.

### **RIGHT SIDE ROLLUP CREW CAB DOOR WINDOW TINT**

The rollup window in the right side crew cab door will be tinted privacy dark gray.

### **CUP HOLDER**

There will be four (4) cup holder(s) provided. Each cup holder will have self-adjusting fingers that automatically grip beverage containers of various sizes. A recess in the cup holder will allow it to hold beverage containers with handles.

The cup holder(s) will be located at customer pick-up.

### **CAB INTERIOR**

The left and right side dash and center console will be a flat faced design to provide easy maintenance and will be constructed out of painted aluminum.

The engine tunnel will be padded and covered with leather grain vinyl resistant to oil, grease and mildew.

For durability and ease of maintenance, the cab interior side walls will be painted aluminum. The rear wall will be painted aluminum.

The headliner will be installed in both forward and rear cab sections. Headliner material will be vinyl. A sound barrier will be part of its composition. Material will be installed on aluminum sheet and securely fastened to interior cab ceiling.

Forward portion of cab headliner will provide easy access for servicing electrical wiring or for other maintenance needs without removing the entire unit.

### **CAB INTERIOR UPHOLSTERY**

The cab interior upholstery will be 36 oz dark silver gray vinyl.

### **CAB INTERIOR PAINT**

The following metal surfaces will be painted black, vinyl textured paint:

- Modesty panel in front of driver
- Vertical surface of dash in front of the officer (not applicable for recessed dash)
- Power distribution in front of the officer
- Rear heater vent panels

The remaining cab interior metal surfaces will be painted fire smoke gray, vinyl texture paint.

### **CAB FLOOR**

The cab and crew cab floor areas will be covered with Polydamp™ acoustical floor mat consisting of a black pyramid rubber facing and closed cell foam decoupler.

The top surface of the material has a series of raised pyramid shapes evenly spaced, which offer a superior grip surface. Additionally, the material has a 0.25" thick closed cell foam, no water absorption, which offers a sound dampening material for reducing sound levels.

### **CAB DEFROSTER**

There will be a 41,000 BTU defroster in the cab located under the engine tunnel.

The defroster ventilation will be built into the design of the cab dash instrument panel and will be easily removable for maintenance.

The defroster will have a 3-speed blower and temperature controls accessible to the driver and officer.

The defroster ducts will be designed to provide maximum defrosting capabilities for the front cab windows.

### **CAB/CREW CAB HEATER**

Two (2) auxiliary heaters with 32,000 BTU each will be provided in the cab. The heaters will have a 3-speed blower and temperature controls accessible to the driver and officer. There will also be louvers located below the rear facing seat riser and below the driver and officer positions for airflow.

The heaters will be mounted, one (1) within each rear facing seat riser.

### **AIR CONDITIONING**

A high-performance, customized air conditioning system will be furnished inside the cab and crew cab. A 19.10 cubic inch compressor will be installed on the engine.

The air conditioning system will be capable of cooling the average cab temperature from 100 degrees Fahrenheit to 72 degrees Fahrenheit at 50 percent relative humidity within 30 minutes. The cooling performance test will be run only after the cab has been heat soaked at 100 degrees Fahrenheit for a minimum of 4 hours.

A roof-mounted condenser that meets and exceeds the performance specification will be installed on the cab roof. The condenser cover and mounting legs to be painted white as provided by the A/C manufacturer.

An evaporator unit that meets and exceeds the performance specification will be installed in the cab, located in the center of the cab ceiling over the engine tunnel. The evaporator will include two (2) high performance cores and plenums with multiple outlets, one (1) plenum directed to the front and one (1) plenum directed to the rear of the cab.

The evaporator unit will be provided with adjustable air outlets strategically located to direct air flow to the driver, officer and crew cab area.

All hose used will be class 1 type to reduce moisture ingress into the air conditioning system.

The air conditioner refrigerant will be R-134A and will be installed by a certified technician.

The air conditioner will be controlled by a single electronic control panel. For ease of operation, the control panel will include variable adjustment for temperature and fan control and be conveniently located on the dash in clear view of the driver.

### **GRAVITY DRAIN TUBES**

Two (2) condensate drain tubes will be provided for the air conditioning evaporator. The drip pan will have two (2) drain tubes plumbed separately to allow for the condensate to exit the drip pan.

### **SUN VISORS**

Two (2) smoked Lexan™ sun visors provided. The sun visors will be located above the windshield with one (1) mounted on each side of the cab.

There will be no retention bracket provided to help secure each sun visor in the stowed position.

### **GRAB HANDLE**

A black rubber covered grab handle will be mounted on the lower portion of the driver's side cab entrance to assist in entering the cab. The grab handle will be securely mounted to the post area between the door and steering wheel column.

An additional black rubber covered grab handle will be mounted on the driver's side door post of the driver's side cab door to assist in entering the cab. The grab handle will be securely mounted to the post area between the door and windshield.

A black rubber covered grab handle will be mounted on the passenger's side door post, above the instrument panel.

### **ENGINE COMPARTMENT LIGHTS**

There will be one (1) Whelen, Model 3SC0CDCR, 12 volt DC, 3.00" white LED light(s) with Whelen, Model 3FLANGECEC, chrome flange kit(s) installed under the cab to be used as engine compartment illumination.

These light(s) will be activated automatically when the cab is raised.

### **ACCESS TO ENGINE DIPSTICKS**

For access to the engine oil and transmission fluid dipsticks, there will be a door on the engine tunnel, inside the crew cab. The door will be on the rear wall of the engine tunnel, on the vertical surface.

The engine oil dipstick will allow for checking only. The transmission dipstick will allow for both checking and filling.

The door will have a rubber seal for thermal and acoustic insulation. One (1) flush latch will be provided on the access door.

### **MAP BOX**

A special map box with nine (9) bins, open from top, will be supplied and installed to be determined. The map box will be 20.25" wide x 8.00" high (tapered down at sides and rear) and 23.25" front to

back. The map box will be constructed of 0.125" aluminum and will be painted to match the cab interior.

### **SEATING CAPACITY**

The seating capacity in the cab will be four (4).

### **DRIVER SEAT**

A USSC, Model P1A, air suspension seat will be provided in the cab for the driver. For increased convenience, the seat will include a manual control to adjust the height (2.50" travel) and horizontal position (6.00" travel). To provide flexibility for multiple driver configurations, the seat will have a reclining back, adjustable from 90 degrees to 45 degrees rearward. To ensure safe operation, the seat will be equipped with seat belt sensors in the seat cushion and belt receptacle that will activate an alarm indicating a seat is occupied but not buckled.

The seat will be furnished with a 3-point, shoulder type seat belt. The seat belt will be furnished with dual automatic retractors that will provide ease of operation in the normal seating position.

### **OFFICER SEAT**

A USSC, air suspension seat will be provided in the cab for the officer. The seat will have a reclining, R-back style seat back. For increased convenience, the seat will include a manual control to adjust the height (3.00" travel) and horizontal position (6.00" travel). To ensure safe operation, the seat will be equipped with seat belt sensors in the seat cushion and belt receptacle that will activate an alarm indicating a seat is occupied but not buckled.

The seat will be furnished with a 3-point, shoulder type seat belt. The seat belt will be furnished with dual automatic retractors that will provide ease of operation in the normal seating position.

There will be no additional contaminant mitigation vinyl covers shipped loose with the seat.

### **REAR FACING LEFT SIDE CABINET**

A rear facing cabinet will be provided in the crew cab at the left side outboard position with interior and exterior access.

The cabinet will be 23.00" wide x 30.00" high x 26.00" deep with one (1) ROM Series IV rollup door with anodized finish, locking with #751 key. The frame to frame will be 17.00" wide x 24.75" high. The minimum clear door opening will be 14.25" wide x 18.87" high.

The cabinet will include one (1) infinitely adjustable shelf with a 0.75" up-turned lip painted to match the cab interior.

The cabinet will include no louvers.

The cabinet will have exterior access with one (1) double pan door painted to match the cab exterior with a locking D-ring latch with #751 key. The clear door opening will be 14.00" wide x 26.75" high. The door will be located on the side of the cab over the wheelwell. A rubber bumper will be used as a door stop.

The exterior access will be provided with a polished stainless steel scuffplate on the lower door frame.

The cabinet will be constructed of smooth aluminum and painted to match the cab interior.

#### **Cabinet Light**

There will be one (1) white LED strip light installed on the right side of the exterior cabinet door opening. The lights will be controlled by an automatic door switch.

#### **REAR FACING RIGHT SIDE CABINET**

A rear facing cabinet will be provided in the crew cab at the right side outboard position.

The cabinet shall be 21.50" wide x 30.00" high x 24.00" deep with one (1) Amdor rollup door with anodized finish, locking with #751 key. The frame to frame opening shall be 15.50" wide x 24.75" high. The minimum clear door opening of the cabinet shall be 12.75" wide x 18.87" high.

The cabinet shall include one (1) infinitely adjustable shelf with a 0.75" up-turned lip painted to match the cab interior.

The cabinet shall include no louvers.

The cabinet shall also provide access from outside the cab with one (1) double pan door painted to match the cab exterior with a locking D-ring latch with #751 key. A rubber bumper shall be provided as a door stop. The exterior clear door opening shall be 10.00" wide x 22.25" high.

The exterior access will be provided with a polished stainless steel scuffplate on the lower door frame.

The cabinet will be constructed of smooth aluminum, and painted to match the cab interior.

#### **Cabinet Light**

There will be one (1) white LED strip light installed on the left side of the interior cabinet door opening. The lights will be controlled by an automatic door switch.

#### **FORWARD FACING DRIVER SIDE OUTBOARD SEAT**

There will be one (1) forward facing, USSC foldup high back seat provided in the driver side outboard position in the crew cab. The seat back will be a R-back style with an adjustable recline angle. For optimal comfort, the seat will be provided with 17.00" deep cushion. To ensure safe operation, the seat will be equipped with a sensor in the seat cushion and belt receptacle that will activate an alarm indicating the seat is occupied but not buckled.

The seat will be furnished with a 3-point, shoulder type seat belt. The seat belt will be furnished with dual automatic retractors that will provide ease of operation in the normal seating position.

There will be no additional contaminant mitigation vinyl covers shipped loose with the seat.

#### **FORWARD FACING CENTER CABINET**

A forward facing cabinet will be provided in the crew cab at the center position.

The cabinet will be 38.00" wide x 35.00" high x 22.50" deep with one (1) ROM Series IV rollup door with anodized finish, locking with #751 key. The frame to frame opening of the cabinet will be 35.50" wide x 29.75" high. The minimum clear door opening will be 32.75" wide x 23.87" high.

The cabinet will include one (1) infinitely adjustable shelf with a 0.75" up-turned lipped to match the cab interior.

The cabinet will include no louvers.

The cabinet will be constructed of smooth aluminum, and painted to match the cab interior.

### **Cabinet Light**

There will be one (1) white LED strip light installed on the right side of the interior cabinet door opening and one (1) white LED strip light installed on the left side of the interior cabinet door opening. The lighting will be controlled by an automatic door switch.

### **FORWARD FACING PASSENGER SIDE OUTBOARD SEAT**

There will be one (1) forward facing, USSC, foldup high back seat provided in the passenger side outboard position in the crew cab. The seat back will be a R-back style with an adjustable recline angle. For optimal comfort, the seat will be provided with 17.00" deep cushion. To ensure safe operation, the seat will be equipped with a sensor in the seat cushion and belt receptacle that will activate an alarm indicating the seat is occupied but not buckled.

The seat will be furnished with a 3-point, shoulder type seat belt. The seat belt will be furnished with dual automatic retractors that will provide ease of operation in the normal seating position.

There will be no additional contaminant mitigation vinyl covers shipped loose with the seat.

### **SEAT UPHOLSTERY**

All seat upholstery will be leather grain black vinyl resistant to oil, grease and mildew. The cab will have four (4) seating positions.

### **SEAT BELTS**

All seating positions in the cab, crew cab and tiller cab (if applicable) will have red seat belts.

To provide quick, easy use for occupants wearing bunker gear, the female buckle and seat belt webbing length will meet or exceed the current edition of NFPA 1901 and CAN/ULC - S515 standards.

The 3-point shoulder type seat belts will also include the ReadyReach D-loop assembly to the shoulder belt system. The ReadyReach feature adds an extender arm to the D-loop location placing the D-loop in a closer, easier to reach location.

Any flip up seats will include a 3-point shoulder type belts only.

### **SHOULDER HARNESS HEIGHT ADJUSTMENT**

All seating positions furnished with 3-point shoulder type seat belts will include a height adjustment. This adjustment will optimize the belts effectiveness and comfort for the seated firefighter.

### **HELMET STORAGE PROVIDED BY FIRE DEPARTMENT**

NFPA 1901, 2016 edition, section 14.1.7.4.1 requires a location for helmet storage be provided.

There is no helmet storage on the apparatus as manufactured. The fire department will provide a location for storage of helmets.

### **CAB DOME LIGHTS**

There will be four (4) dual LED dome lights with black bezels provided. Two (2) lights will be mounted above the inside shoulder of the driver and officer and two (2) lights will be installed and located, one (1) on each side of the crew cab.

The color of the LED's will be red and white.

The white LED's will be controlled by the door switches and the lens switch.

The color LED's will be controlled by the lens switch.

In order to ensure exceptional illumination, each white LED dome light will provide a minimum of 10.1 foot-candles (fc) covering an entire 20.00" x 20.00" square seating position when mounted 40.00" above the seat.

### **OVERHEAD MAP LIGHTS**

There will be two (2) Peterson, Model M371S, rectangular LED adjustable map lights installed in the cab:

- One (1) overhead in front of the driving position.
- One (1) overhead in front of the passenger's position.

Each light will include a switch on the light housing.

The light switches will be connected directly to the battery switched power.

### **PORTABLE HAND LIGHTS PROVIDED BY FIRE DEPARTMENT**

CAN/ULC-S515, current edition, section 5.8.2 requires four portable hand lights.

The hand lights are not on the apparatus as manufactured. The fire department will provide these hand lights.

### **CAB INSTRUMENTATION**

The cab instrument panel will consist of gauges, an LCD display, telltale indicator lights, alarms, control switches, and a diagnostic panel. The function of instrument panel controls and switches will be identified by a label adjacent to each item. Actuation of the headlight switch will illuminate the labels in low light conditions. Telltale indicator lamps will not be illuminated unless necessary. The cab instruments and controls will be conveniently located within the forward cab section directly forward of the driver. Gauge and switch panels will be designed to be removable for ease of service and low cost of ownership.



## **Cab Interior**

The wrap-around style high impact ABS plastic cab dash fascia will be designed to provide unobstructed visibility to instrumentation. The dash layout will provide the driver with a quick reference to gauges that allows more time to focus on the road.

## **Gauges**

The gauge panel will include the following ten (10) ivory gauges with chrome bezels to monitor vehicle performance:

- Voltmeter Gauge (Volts):
  - Low volts (11.8 VDC)
    - Amber indicator on gauge assembly with alarm
  - High volts (15 VDC)
    - Amber indicator on gauge assembly with alarm
  - Very low volts (11.3 VDC)
    - Amber indicator on gauge assembly with alarm
  - Very high volts (16 VDC)
    - Amber indicator on gauge assembly with alarm
- Tachometer (RPM)
- Speedometer (Primary (outside) MPH, Secondary (inside) Km/H)
- Fuel Level Gauge (Empty - Full in fractions):
  - Low fuel (1/8 full)
    - Amber indicator on gauge assembly with alarm
  - Very low fuel (1/32) fuel
    - Amber indicator on gauge assembly with alarm
- Engine Oil Pressure Gauge (PSI):
  - Low oil pressure to activate engine warning lights and alarms
    - Red indicator on gauge assembly with alarm
- Front Air Pressure Gauge (PSI):
  - Low air pressure to activate warning lights and alarm
    - Red indicator on gauge assembly with alarm
- Rear Air Pressure Gauge (PSI):
  - Low air pressure to activate warning lights and alarm.
    - Red indicator on gauge assembly with alarm
- Transmission Oil Temperature Gauge (Fahrenheit):
- High transmission oil temperature activates warning lights and alarm
  - Amber indicator on gauge assembly with alarm
- Engine Coolant Temperature Gauge (Fahrenheit):
  - High engine temperature activates an engine warning light and alarm
    - Red indicator on gauge assembly with alarm
- Diesel Exhaust Fluid Level Gauge (Empty - Full in fractions):
  - Low fluid (1/8 full)
    - Amber indicator on gauge assembly with alarm

All gauges and gauge indicators will perform prove out at initial power-up to ensure proper performance.

### **Indicator Lamps**

To promote safety, the following telltale indicator lamps will be integral to the gauge assembly and are located above and below the center gauges. The indicator lamps will be "dead-front" design that is only visible when active. The colored indicator lights will have descriptive text or symbols.

The following amber telltale lamps will be present:

- Low coolant
- Trac cntl (traction control) (where applicable)
- Check engine
- Check trans (check transmission)
- Aux brake overheat (Auxiliary brake overheat)
- Air rest (air restriction)
- Caution (triangle symbol)
- Water in fuel
- DPF (engine diesel particulate filter regeneration)
- Trailer ABS (where applicable)
- Wait to start (where applicable)
- HET (engine high exhaust temperature) (where applicable)
- ABS (antilock brake system)
- MIL (engine emissions system malfunction indicator lamp) (where applicable)
- SRS (supplemental restraint system) fault (where applicable)
- DEF (low diesel exhaust fluid level)
- The following red telltale lamps will be present:
- Warning (stop sign symbol)
- Seat belt
- Parking brake
- Stop engine
- Rack down

The following green telltale lamps will be provided:

- Left turn
- Right turn
- Battery on

The following blue telltale lamp will be provided:

- High beam

## **Alarms**

Audible steady tone warning alarm: A steady audible tone alarm will be provided whenever a warning message is present.

Audible pulsing tone caution alarm: A pulsing audible tone alarm (chime/chirp) will be provided whenever a caution message is present without a warning message being present.

Alarm silence: Any active audible alarm will be able to be silenced by holding the ignition switch at the top position for three (3) to five (5) seconds. For improved safety, silenced audible alarms will intermittently chirp every 30 seconds until the alarm condition no longer exists. The intermittent chirp will act as a reminder to the operator that a caution or warning condition still exists. Any new warning or caution condition will enable the steady or pulsing tones respectively.

## **Indicator Lamp and Alarm Prove-Out**

Telltale indicators and alarms will perform prove-out at initial power-up to ensure proper performance.

## **Control Switches**

For ease of use, the following controls will be provided immediately adjacent to the cab instrument panel within easy reach of the driver:

- Emergency master switch: A molded plastic push button switch with integral indicator lamp will be provided. Pressing the switch will activate emergency response lights and siren control. A green lamp on the switch provides indication that the emergency master mode is active. Pressing the switch again disables the emergency master mode.
- Headlight / Parking light switch: A three (3)-position maintained rocker switch will be provided. The first switch position will deactivate all parking lights and the headlights. The second switch position will activate the parking lights. The third switch position will activate the headlights.
- Panel back lighting intensity control switch: A three (3)-position momentary rocker switch will be provided. The first switch position decreases the panel back lighting intensity to a minimum level as the switch is held. The second switch position is the default position that does not affect the back lighting intensity. The third switch position increases the panel back lighting intensity to a maximum level as the switch is held.

The following standard controls will be integral to the gauge assembly and are located below the right hand gauges. All switches have backlit labels for low light applications:

- High idle engagement switch: A two (2)-position momentary rocker switch with integral indicator lamp will be provided. The first switch position is the default switch position. The second switch position will activate and deactivate the high idle function when pressed and released. The "Ok To Engage High Idle" indicator lamp must be active for the high idle function to engage. A green indicator lamp integral to the high idle engagement switch will indicate when the high idle function is engaged.

- "Ok To Engage High Idle" indicator lamp: A green indicator light will be provided next to the high idle activation switch to indicate that the interlocks have been met to allow high idle engagement.
- The following standard controls will be provided adjacent to the cab gauge assembly within easy reach of the driver. All switches will have backlit labels for low light applications.
- Ignition switch: A three (3)-position maintained/momentary rocker switch will be provided. The first switch position will deactivate vehicle ignition. The second switch position will activate vehicle ignition. The third momentary position will disable the Command Zone audible alarm if held for three (3) to five (5) seconds. A green indicator lamp will be activated with vehicle ignition.
- Engine start switch: A two (2)-position momentary rocker switch will be provided. The first switch position is the default switch position. The second switch position will activate the vehicle's engine. The switch actuator is designed to prevent accidental activation.
- 4-way hazard switch: A two (2)-position maintained rocker switch will be provided. The first switch position will deactivate the 4-way hazard switch function. The second switch position will activate the 4-way hazard function. The switch actuator will be red and includes the international 4-way hazard symbol.
- Turn signal arm: A self-canceling turn signal with high beam headlight and windshield wiper/washer controls will be provided. The windshield wiper control will have high, low, and intermittent modes.
- Parking brake control: An air actuated push/pull park brake control valve will be provided.
- Chassis horn control: Activation of the chassis horn control will be provided through the center of the steering wheel.

### **Custom Switch Panels**

The design of cab instrumentation will allow for emergency lighting and other switches to be placed within easy reach of the operator thus improving safety. There will be positions for up to three (3) switch panels in the overhead console on the driver's side, up to four (4) switch panels in the engine tunnel console facing the driver, up to three (3) switch panels in the overhead console on the officer's side and up to three (3) switch panels in the engine tunnel rear facing console accessible to both driver and officer. All switches will have backlit labels for low light applications.

### **Diagnostic Panel**

A diagnostic panel will be accessible while standing on the ground and located inside the driver's side door left of the steering column. The diagnostic panel will allow diagnostic tools such as computers to connect to various vehicle systems for improved troubleshooting providing a lower cost of ownership. Diagnostic switches will allow ABS systems to provide blink codes should a problem exist. The diagnostic panel will include the following:

- Engine diagnostic port
- Transmission diagnostic port
- ABS diagnostic port
- SRS diagnostic port (where applicable)

- Command Zone USB diagnostic port
- ABS diagnostic switch (blink codes flashed on ABS telltale indicator)
- Diesel particulate filter regeneration switch (where applicable)
- Diesel particulate filter regeneration inhibit switch (where applicable)

### **Cab LCD Display**

A digital four (4)-row by 20-character dot matrix display will be integral to the gauge panel. The display will be capable of showing simple graphical images as well as text. The display will be split into three (3) sections. Each section will have a dedicated function. The upper left section will display the outside ambient temperature. The upper right section will display odometer, trip mileage, PTO hours, fuel consumption, engine hours, and other configuration specific information. The bottom section will display INFO, CAUTION, and WARNING messages. Text messages will automatically activate to describe the cause of an audible caution or warning alarm. The LCD will be capable of displaying multiple text messages should more than one caution or warning condition exist.

### **AIR RESTRICTION INDICATOR**

A high air restriction warning indicator light LCD message with amber warning indicator and audible alarm will be provided.

### **"DO NOT MOVE APPARATUS" INDICATOR**

A flashing red indicator light, located in the driving compartment, will be illuminated automatically per the current NFPA requirements. The light will be labeled "Do Not Move Apparatus If Light Is On."

The same circuit that activates the Do Not Move Apparatus indicator will activate a pulsing alarm when the parking brake is released.

### **DO NOT MOVE TRUCK MESSAGES**

Messages will be displayed on the Command Zone™, color display located within sight of the driver whenever the Do Not Move Truck light is active. The messages will designate the item or items not in the stowed for vehicle travel position (parking brake disengaged).

The following messages will be displayed (where applicable):

- Do Not Move Truck
- DS Cab Door Open (Driver Side Cab Door Open)
- PS Cab Door Open (Passenger's Side Cab Door Open)
- DS Crew Cab Door Open (Driver Side Crew Cab Door Open)
- PS Crew Cab Door Open (Passenger's Side Crew Cab Door Open)
- DS Body Door Open (Driver Side Body Door Open)
- PS Body Door Open (Passenger's Side Body Door Open)
- Rear Body Door Open
- DS Ladder Rack Down (Driver Side Ladder Rack Down)
- PS Ladder Rack Down (Passenger Side Ladder Rack Down)
- Deck Gun Not Stowed

- Lt Tower Not Stowed (Light Tower Not Stowed)
- Fold Tank Not Stowed (Fold-A-Tank Not Stowed)
- Aerial Not Stowed (Aerial Device Not Stowed)
- Stabilizer Not Stowed
- Steps Not Stowed
- Handrail Not Stowed

Any other device that is opened, extended, or deployed that creates a hazard or is likely to cause major damage to the apparatus if the apparatus is moved will be displayed as a caution message after the parking brake is disengaged.

### **SWITCH PANELS**

The emergency light switch panel will have a master switch for ease of use plus individual switches for selective control. Each switch panel will contain eight (8) membrane-type switches each rated for one million (1,000,000) cycles. Panels containing less than eight (8) switch assignments will include non-functioning black appliques. Documentation will be provided by the manufacturer indicating the rated cycle life of the switches. The switch panel(s) will be located in the overhead position above the windshield on the driver side overhead to allow for easy access.

Additional switch panel(s) will be located in the overhead position(s) above the windshield or in designated locations on the lower instrument panel layout.

The switches will be membrane-type and also act as an integral indicator light. For quick, visual indication the entire surface of the switch will be illuminated white whenever back lighting is activated and illuminated green whenever the switch is active. An active illuminated switch will flash when interlock requirements are not met or device is actively being load managed. For ease of use, a two (2)-ply, scratch resistant laser engraved Gravoply label indicating the use of each switch will be placed in the center of the switch. The label will allow light to pass through the letters for ease of use in low light conditions.

### **WIPER CONTROL**

For simple operation and easy reach, the windshield wiper control will be an integral part of the directional light lever located on the steering column. The wiper control will include high and low wiper speed settings, a one (1)-speed intermittent wiper control and windshield washer switch. The control will have a "return to park" provision, which allows the wipers to return to the stored position when the wipers are not in use.

### **HOURLMETER - AERIAL DEVICE**

An hourmeter for the aerial device will be provided and located within the cab display or instrument panel.

### **AERIAL MASTER**

There will be a master switch for the aerial operating electrical system provided.

### **AERIAL PTO SWITCH**

A PTO switch for the aerial with indicator light will be provided.

### **SPARE CIRCUIT**

There will be four (4) dual USB fast charge socket mounts installed on the apparatus.

The above wires will have the following features:

- The positive wire will be connected directly to the battery power.
- The negative wire will be connected to ground.
- Wires will be protected to 4.8 amps at 12 volts DC.
- The USB socket mount will be at all seating positions to be determined.
- Termination will be a Blue Sea Systems part number 1045 dual USB charger socket.
- Wires will be sized to 125% of the protection.

This circuit(s) may be load managed when the parking brake is applied.

### **SPARE CIRCUIT**

There will be eight (8) pair of wires, including a positive and a negative, installed on the apparatus.

The above wires will have the following features:

- The positive wire will be connected directly to the battery power
- The negative wire will be connected to ground
- Wires will be protected to 15 amps at 12 volts DC
- Power and ground will terminate officer side dash area and to be determined
- Termination will be with heat shrinkable butt splicing
- Wires will be sized to 125 percent of the protection

The circuit(s) may be load managed when the parking brake is set.

### **INSTRUMENT PANEL RECESS**

The instrument panel across from the officer will be recessed to accommodate the mounting of miscellaneous items. The glove box will be replaced with a painted sheet metal mounting platform/shelf. The recess will be 8.00" down x 8.00" back and 17.00" wide.

### **STEREO RADIO**

A Jensen, heavy duty AM/FM/CD/Weatherband stereo radio, with front auxiliary input will be installed per switch panel layout. There will be 5.25" speakers installed one (1) pair of 5.25" speakers in the cab and one (1) pair of 5.25" speakers in the crew cab. The antenna will be a roof-mounted rubber antenna located in an open space, on the cab roof.

The following features will be included:

- CD Player with Electronic Skip Protection (ESP)
- Full 7-Channel NOAA Weatherband Tuner with SAME technology

- Built-in Clock
- Audio CD, CD-R, R/W, MP3 CD compatible
- Radio Broadcast Data System Text Display
- Front panel USB input
- Front and Rear Auxiliary Audio Input
- Receives audio (A2DP/AVRCP) from Bluetooth enabled device
- Supports Bluetooth HFP to receive phone calls from BT-enabled phones
- Low battery alert (<10.8Vdc)
- Heavy Duty design with Conformal Coated Circuit Boards for maximum durability under all conditions

### **INFORMATION CENTER**

An information center employing a 7.00" diagonal touch screen color LCD display will be encased in an ABS plastic housing.

The information center will have the following specifications:

- Operate in temperatures from -40 to 185 degrees Fahrenheit
- An Optical Gel will be placed between the LCD and protective lens
- Five weather resistant user interface switches
- Grey with black accents
- Sunlight Readable
- Linux operating system
- Minimum of 1000nits rated display
- Display can be changed to an available foreign language
- A LCD display integral to the cab gauge panel will be included as outlined in the cab instrumentation area.
- Programmed to read US Customary

### **General Screen Design**

Where possible, background colors will be used to provide "At a Glance" vehicle information. If information provided on a screen is within acceptable limits, a green background will be used.

If a caution or warning situation arises the following will occur:

- An amber background/text color will indicate a caution condition
- A red background/text color will indicate a warning condition
- The information center will utilize an "Alert Center" to display text messages for audible alarm tones. The text messages will be written to identify the item(s) causing the audible alarm to sound. If more than one (1) text message occurs, the messages will cycle every second until the problem(s) have been resolved. The background color for the "Alert Center" will change to indicate the severity of the "warning" message. If a warning and a caution condition occur simultaneously, the red background color will be shown for all alert center messages.



- A label for each button will exist. The label will indicate the function for each active button for each screen. Buttons that are not utilized on specific screens will have a button label with no text or symbol.

### **Home/Transit Screen**

This screen will display the following:

- Vehicle Mitigation (if equipped)
- Water Level (if the water level system includes compatible communications to the information center)
- Foam Level (if the foam level system includes compatible communications to the information center)
- Seat Belt Monitoring Screen
- Tire Pressure Monitoring (if equipped)
- Digital Speedometer
- Active Alarms

### **On Scene Screen**

This screen will display the following and will be auto activated with pump engaged (if equipped):

- Battery Voltage
- Fuel
- Oil Pressure
- Coolant Temperature
- RPM
- Water Level (if equipped)
- Foam Level (if equipped)
- Foam Concentration (if equipped)
- Water Flow Rate (if equipped)
- Water Used (if equipped)
- Active Alarms

### **Virtual Buttons**

There will be four (4) virtual switch panel screens that match the overhead and lower lighting and HVAC switch panels.

### **Page Screen**

The page screen will display the following and allow the user to progress into other screens for further functionality:

- Diagnostics
  - Faults
    - Listed by order of occurrence
    - Allows to sort by system

- Interlock
  - Throttle Interlocks
  - Pump Interlocks (if equipped)
  - Aerial Interlocks (if equipped)
  - PTO Interlocks (if equipped)
- Load Manager
  - A list of items to be load managed will be provided. The list will provide a description of the load.
  - The lower the priority numbers the earlier the device will be shed should a low voltage condition occur.
  - The screen will indicate if a load has been shed (disabled) or not shed.
  - "At a glance" color features are utilized on this screen.
- Systems
  - Command Zone
    - Module type and ID number
    - Module Version
    - Input or output number
    - Circuit number connected to that input or output
    - Status of the input or output
    - Power and Constant Current module diagnostic information
  - Foam (if equipped)
  - Pressure Controller (if equipped)
  - Generator Frequency (if equipped)
- Live Data
  - General Truck Data
- Maintenance
  - Engine oil and filter
  - Transmission oil and filter
  - Pump oil (if equipped)
  - Foam (if equipped)
  - Aerial (if equipped)
- Setup
  - Clock Setup
  - Date & Time
    - 12 or 24 hour format
    - Set time and date
  - Backlight
    - Daytime
    - Night time
    - Sensitivity
  - Unit Selection
  - Home Screen

- Virtual Button Setup
- On Scene Screen Setup
- Configure Video Mode
  - Set Video Contrast
  - Set Video Color
  - Set Video Tint
- Do Not Move
  - The screen will indicate the approximate location and type of item that is open or is not stowed for travel. The actual status of the following devices will be indicated
    - Driver Side Cab Door
    - Passenger's Side Cab Door
    - Driver Side Crew Cab Door
    - Passenger's Side Crew Cab Door
    - Driver Side Body Doors
    - Passenger's Side Body Doors
    - Rear Body Door(s)
    - Ladder Rack (if applicable)
    - Deck Gun (if applicable)
    - Light Tower (if applicable)
    - Hatch Door (if applicable)
    - Stabilizers (if applicable)
    - Steps (if applicable)
- Notifications
  - View Active Alarms
    - Shows a list of all active alarms including date and time of the occurrence is shown with each alarm
    - Silence Alarms - All alarms are silenced
- Timer Screen
- HVAC (if equipped)
- Tire Information (if equipped)
- Ascendant Set Up Confirmation (if equipped)

Button functions and button labels may change with each screen.

### **COLLISION MITIGATION**

There will be a HAAS Alert®, Model HA5 Responder-to-Vehicle (R2V) collision avoidance system provided on the apparatus. The HA5 cellular transponder module will be installed behind the cab windshield, as high and near to the center as practical, to allow clear visibility to the sky. The module dimensions are 5.40" long x 2.70" wide x 1.30" high, and operating temperature range is -40 degree C to 85 degree C.

The transponder will be connected to the vehicle's emergency master circuit and battery direct power and ground.

While responding with emergency lights on, the HA5 transponder sends alert messages via cellular network to motorists in the vicinity of the responding truck that are equipped with the WAZE app.

While on scene with emergency lights on, the HA5 transponder sends road hazard alerts to motorists in the vicinity of the truck that are equipped with the WAZE app.

The HA5 Responder-to-Vehicle (R2V) collision avoidance system will include the transponder and a 5 year cellular plan subscription.

Activation of the HAAS Alert system requires a representative of the customer to accept the End User License Agreement (EULA) via an on-line portal.

### **VEHICLE DATA RECORDER**

There will be a vehicle data recorder (VDR) capable of reading and storing vehicle information provided.

The information stored on the VDR can be downloaded through a USB port mounted in a convenient location determined by cab model. A USB cable can be used to connect the VDR to a laptop to retrieve required information. The program to download the information from the VDR will be available to download on-line.

The vehicle data recorder will be capable of recording the following data via hardwired and/or CAN inputs:

- Vehicle Speed - MPH
- Acceleration - MPH/sec
- Deceleration - MPH/sec
- Engine Speed - RPM
- Engine Throttle Position - % of Full Throttle
- ABS Event - On/Off
- Seat Occupied Status - Yes/No by Position
- Seat Belt Buckled Status - Yes/No by Position
- Master Optical Warning Device Switch - On/Off
- Time - 24 Hour Time
- Date - Year/Month/Day

### **Seat Belt Monitoring System**

A seat belt monitoring system (SBMS) will be provided on the Command Zone™ color display and in the center overhead of the cab instrument panel. The SBMS will be capable of monitoring up to 10 seating positions indicating the status of each seat position per the following:

- Seat Occupied & Buckled = Green LED indicator illuminated
- Seat Occupied & Unbuckled = Red LED indicator with audible alarm
- No Occupant & Buckled = Red LED indicator with audible alarm
- No Occupant & Unbuckled = No indicator and no alarm

The seat belt monitoring screen will become active on the Command Zone color display when:

- The home screen is active:
  - and there is any occupant seated but not buckled or any belt buckled with an occupant.
  - and there are no other Do Not Move Apparatus conditions present. As soon as all Do Not Move Apparatus conditions are cleared, the SBMS will be activated.

The SBMS will include an audible alarm that will warn that an unbuckled occupant condition exists and the parking brake is released, or the transmission is not in park.

### **INTERCOM SYSTEM**

An eight (8) position Sigtronics, Model US-12S, intercom system with single radio interface capability at the driver, officer, and pump operator positions will be provided. Four (4) crew positions [location, intercom, C Cab] and the rear of the vehicle will have intercom / radio listen only.

System includes:

- One (1) US-12S Single Radio Intercom
- Six (6) interior headset jacks
- Two (2) exterior headset jacks
- Three (3) push to transmit buttons
- All necessary cabling

### **RADIO INTERFACE NOT REQUIRED**

The apparatus manufacturer will not provide a radio/intercom interface.

### **HEADSET, OVER THE HEAD**

There will be four (4) Sigtronics, Model SE-48, over the head, standard headset(s) provided Shipped loose.

Each headset will feature:

- Coiled cord with single nickel coated plug
- Noise cancelling electret microphone with wind muff
- Flexible microphone boom rotates 180 degrees for left or right dress
- Foam earseals
- Volume control
- 24 dB noise reduction

### **COMPLETE MDT INSTALLATION**

There will be one (1) customer supplied Mobile Data Terminal (MDT), Docking station, Mounting bracket, power supply, antenna, GPS, modem, and all cabling sent to the apparatus manufacturers preferred installer to be installed to be determined. Specific shipping requirements will be followed.

### **PORTABLE RADIO CHARGER INSTALLATION**

There will be six (6) customer supplied portable two-way radio chargers(s) sent to the apparatus manufacturers preferred radio installer to be installed to be determined. Specific shipping requirements will be followed.

### **TWO WAY RADIO INSTALLATION**

There will be two (2) customer supplied two way radio(s) sent to the apparatus manufacturers preferred radio installer to be installed to be determined per the shipping document.

No antenna mount or whip will be included in this option.

Specific radio shipping requirements will be followed.

### **RADIO ANTENNA MOUNT**

There will be three (3) standard 1.125", 18 thread antenna-mounting base(s) installed on the right side on the cab roof with high efficiency, low loss, coaxial cable(s) routed to the instrument panel area. A weatherproof cap will be installed on the mount.

### **VEHICLE CAMERA SYSTEM**

There will be a color vehicle camera system provided with the following:

- One (1) camera located at the rear of the apparatus, pointing rearward, displayed automatically with the vehicle in reverse.
- One (1) camera located on the right side of the apparatus, pointing rearward, displayed automatically with the right side turn signal.
- One (1) camera located on the left side of the apparatus, pointing rearward, displayed automatically with the left side turn signal.

The camera images will be displayed on the driver's vehicle information center display. Audio from the microphone on the rear camera will be emitted by an amplified speaker with volume control located behind the driver seat.

The following components will be included:

- One (1) SV-CW134639CAI Camera
- Two (2) CS134404CI Side cameras
- One (1) Amplified speaker (if applicable)
- All necessary cables

### **ELECTRICAL POWER CONTROL SYSTEM**

The primary power distribution will be located forward of the officer's seating position and be easily accessible while standing on the ground for simplified maintenance and troubleshooting. Additional electrical distribution centers will be provided throughout the vehicle to house the vehicle's electrical power, circuit protection, and control components. The electrical distribution centers will be located strategically throughout the vehicle to minimize wire length. For ease of maintenance, all electrical

distribution centers will be easily accessible. All distribution centers containing fuses, circuit breakers and/or relays will be easily accessible.

Distribution centers located throughout the vehicle will contain battery powered studs for supplying customer installed equipment thus providing a lower cost of ownership.

Circuit protection devices, which conform to SAE standards, will be utilized to protect electrical circuits. All circuit protection devices will be rated per NFPA requirements to prevent wire and component damage when subjected to extreme current overload. General protection circuit breakers will be Type-I automatic reset (continuously resetting). When required, automotive type fuses will be utilized to protect electronic equipment. Control relays and solenoid will have a direct current rating of 125 percent of the maximum current for which the circuit is protected per NFPA.

### **SOLID-STATE CONTROL SYSTEM**

A solid-state electronics based control system will be utilized to achieve advanced operation and control of the vehicle components. A fully computerized vehicle network will consist of electronic modules located near their point of use to reduce harness lengths and improve reliability. The control system will comply with SAE J1939-11 recommended practices.

The control system will operate as a master-slave system whereas the main control module instructs all other system components. The system will contain patented Mission Critical software that maintains critical vehicle operations in the unlikely event of a main controller error. The system will utilize a Real Time Operating System (RTOS) fully compliant with OSEK/VDX™ specifications providing a lower cost of ownership.

For increased reliability and simplified use the control system modules will include the following attributes:

- Green LED indicator light for module power
- Red LED indicator light for network communication stability status
- Control system self test at activation and continually throughout vehicle operation
- No moving parts due to transistor logic
- Software logic control for NFPA mandated safety interlocks and indicators
- Integrated electrical system load management without additional components
- Integrated electrical load sequencing system without additional components
- Customized control software to the vehicle's configuration
- Factory and field re programmable to accommodate changes to the vehicle's operating parameters
- Complete operating and troubleshooting manuals
- USB connection to the main control module for advanced troubleshooting

To assure long life and operation in a broad range of environmental conditions, the solid-state control system modules will meet the following specifications:

- Module circuit board will meet SAE J771 specifications

- Operating temperature from -40C to +70C
- Storage temperature from -40C to +70C
- Vibration to 50g

IP67 rated enclosure (Totally protected against dust and also protected against the effect of temporary immersion between 15 centimeters and one (1) meter)

Operating voltage from eight (8) volts to 16 volts DC

The main controller will activate status indicators and audible alarms designed to provide warning of problems before they become critical.

### **CIRCUIT PROTECTION AND CONTROL DIAGRAM**

Copies of all job-specific, computer network input and output (I/O) connections will be provided with each chassis. The sheets will indicate the function of each module connection point, circuit protection information (where applicable), wire numbers, wire colors and load management information.

### **ON-BOARD ADVANCED/VISUAL ELECTRICAL SYSTEM DIAGNOSTICS**

The on-board information center will include the following diagnostic information:

- Text description of active warning or caution alarms
- Simplified warning indicators
- Amber caution indication with intermittent alarm
- Red warning indication with steady tone alarm

All control system modules, with the exception of the main control module, will contain on-board visual diagnostic LEDs that assist in troubleshooting. The LEDs will be enclosed within the sealed, transparent module housing near the face of the module. One LED for each input or output will be provided and will illuminate whenever the respective input or output is active. Color-coded labels within the modules will encompass the LEDs for ease of identification. The LED indicator lights will provide point of use information for reduced troubleshooting time without the need for an additional computer.

### **TECH MODULE WITH WIFI**

An in cab module will provide WiFi wireless interface and data logging capability. The WiFi interface will comply with IEEE 802.11 b/g/n capabilities while communicating at 2.4 Gigahertz. The module will provide an external antenna connection allowing a line of site communication range of up to 300 feet with a roof mounted antenna.

The module will transmit a password protected web page to a WiFi enabled device (i.e. most smart phones, tablets or laptops) allowing two levels of user interaction. The firefighter level will allow vehicle monitoring of the vehicle and firefighting systems on the apparatus. The technician level will allow diagnostic access to inputs and outputs installed on the Command Zone™, control and information system.



The data logging capability will record faults from the engine, transmission, ABS and Command Zone™, control and information systems as they occur. No other data will be recorded at the time the fault occurs. The data logger will provide up to 2 Gigabytes of data storage.

A USB connection will be provided on the Tech Module. It will provide a means to download data logger information and update software in the device.

### **PROGNOSTICS**

A software based vehicle tool will be provided to predict remaining life of the vehicles critical fluid and events.

The system will send automatic indications to the Command Zone, color display and/or wireless enabled device to proactively alert of upcoming service intervals.

Prognostics will include:

- Engine oil and filter
- Transmission oil and filter
- Pump oil (if equipped)
- Foam oil (if equipped)
- Aerial oil and filter (if equipped)

### **ADVANCED DIAGNOSTICS**

An advanced, Windows-based, diagnostic software program will be provided for this control system. The software will provide troubleshooting tools to service technicians equipped with a Windows-based computer or wireless enabled device.

The service and maintenance software will be easy to understand and use and have the ability to view system input/output (I/O) information.

### **INDICATOR LIGHT AND ALARM PROVE-OUT SYSTEM**

A system will be provided which automatically tests basic indicator lights and alarms located on the cab instrument panel.

### **VOLTAGE MONITOR SYSTEM**

A voltage monitoring system will be provided to indicate the status of the battery system connected to the vehicle's electrical load. The system will provide visual and audible warning when the system voltage is below or above optimum levels.

The alarm will activate if the system falls below 11.8 volts DC for more than two (2) minutes.

### **DEDICATED RADIO EQUIPMENT CONNECTION POINTS**

There will be three (3) studs provided in the primary power distribution center located in front of the officer for two-way radio equipment.

- The studs will consist of the following:

- 12-volt 40-amp battery switched power
- 12-volt 60-amp ignition switched power
- 12-volt 60-amp direct battery power

There will also be a 12-volt 100-amp ground stud located in or adjacent to the power distribution center.

### **ENHANCED SOFTWARE**

The solid-state control system will include the following software enhancements:

All perimeter lights and scene lights (where applicable) will be deactivated when the parking brake is released.

Cab and crew cab dome lights will remain on for ten (10) seconds for improved visibility after the doors close. The dome lights will dim after ten (10) seconds or immediately if the vehicle is put into gear.

Cab and crew cab perimeter lights will remain on for ten (10) seconds for improved visibility after the doors close. The dome lights will dim after ten (10) seconds or immediately if the vehicle is put into gear.

### **EMI/RFI PROTECTION**

To prevent erroneous signals from crosstalk contamination and interference, the electrical system will meet, at a minimum, SAE J551/2, thus reducing undesired electromagnetic and radio frequency emissions. An advanced electrical system will be used to ensure radiated and conducted electromagnetic interference (EMI) or radio frequency interference (RFI) emissions are suppressed at their source.

The apparatus will have the ability to operate in the electromagnetic environment typically found in fire ground operations to ensure clean operations. The electrical system will meet, without exceptions, electromagnetic susceptibility conforming to SAE J1113/25 Region 1, Class C EMR for 10KHz-1GHz to 100 Volts/Meter. The vehicle OEM, upon request, will provide EMC testing reports from testing conducted on an entire apparatus and will certify that the vehicle meets SAE J551/2 and SAE J1113/25 Region 1, Class C EMR for 10KHz-1GHz to 100 Volts/Meter requirements.

EMI/RFI susceptibility will be controlled by applying appropriate circuit designs and shielding. The electrical system will be designed for full compatibility with low-level control signals and high-powered two-way radio communication systems. Harness and cable routing will be given careful attention to minimize the potential for conducting and radiated EMI/RFI susceptibility.

### **ELECTRICAL**

All 12-volt electrical equipment installed by the apparatus manufacturer will conform to modern automotive practices. All wiring will be high temperature crosslink type. Wiring will be run, in loom or conduit, where exposed and have grommets where wire passes through sheet metal. Automatic reset circuit breakers will be provided which conform to SAE Standards. Wiring will be color, function and number coded. Function and number codes will be continuously imprinted on all wiring harness

conductors at 2.00" intervals. Exterior exposed wire connectors will be positive locking, and environmentally sealed to withstand elements such as temperature extremes, moisture and automotive fluids.

Electrical wiring and equipment will be installed utilizing the following guidelines:

1. All holes made in the roof will be caulked with silicon. Large fender washers, liberally caulked, will be used when fastening equipment to the underside of the cab roof.
2. Any electrical component that is installed in an exposed area will be mounted in a manner that will not allow moisture to accumulate in it. Exposed area will be defined as any location outside of the cab or body.
3. Electrical components designed to be removed for maintenance will not be fastened with nuts and bolts. Metal screws will be used in mounting these devices. Also a coil of wire will be provided behind the appliance to allow them to be pulled away from mounting area for inspection and service work.
4. Corrosion preventative compound will be applied to all terminal plugs located outside of the cab or body. All non-waterproof connections will require this compound in the plug to prevent corrosion and for easy separation (of the plug).
5. All lights that have their sockets in a weather exposed area will have corrosion preventative compound added to the socket terminal area.
6. All electrical terminals in exposed areas will have silicon (1890) applied completely over the metal portion of the terminal.

All lights and reflectors, required to comply with Federal Motor Vehicle Safety Standard #108, will be furnished. Rear identification lights will be recessed mounted for protection. Lights and wiring mounted in the rear bulkheads will be protected from damage by installing a false bulkhead inside the rear compartments.

An operational test will be conducted to ensure that any equipment that is permanently attached to the electrical system is properly connected and in working order.

The results of the tests will be recorded and provided to the purchaser at time of delivery.

### **BATTERY SYSTEM**

Five-(5) Optima 1000M 12 volt, 800 CCA, 110 min reserve capacity, batteries with a system rating of 4000 CCA at 0 degrees Fahrenheit and 550 minutes of reserve capacity. The batteries will be provided with SAE posts.

### **ISOLATED BATTERY**

One (1)-12 volt, Optima 1000M battery will be provided for voltage sensitive components. A battery isolator that is appropriately suited for the battery capacity will be supplied.

### **BATTERY SYSTEM**

There will be a single starting system with an ignition switch and starter button provided and located on the cab instrument panel.

### **MASTER BATTERY SWITCH**

There will be a master battery switch provided within the cab within easy reach of the driver to activate the battery system.

An indicator light will be provided on the instrument panel to notify the driver of the status of the battery system.

### **BATTERY COMPARTMENTS**

Batteries will be stored in well-ventilated compartments that are located under the cab and bolted directly to the chassis frame. The battery compartments will be constructed of 0.188" steel plate and be designed to accommodate a maximum of three (3) group 31 batteries in each compartment. The battery hold-downs will be of a non-corrosive material. All bolts and nuts will be stainless steel.

The compartments will include formed fit heavy duty roto-molded polyethylene battery trays with drain tubes for the batteries to sit in.

Heavy-duty battery cables will be used to provide maximum power to the electrical system. Cables will be color-coded.

Battery terminal connections will be coated with anti-corrosion compound. Battery solenoid terminal connections will be encapsulated with semi-permanent rubberized compound.

### **JUMPER STUDS**

One (1) set of battery jumper studs with plastic color-coded covers will be installed on the bottom of the driver's side battery box. This will provide for easy jumper cable access.

### **BATTERY CHARGER**

There will be a Kussmaul 1200, Model 091-187-12-Remote, battery charger provided. A Kussmaul, Model 091-194-IND-WT-\*\*, water tight auto charge status center indicating the state of charge will be included. The color of the charge indicator will be black.

The charger will have a maximum output of 40 amps and a fully automatic regulation.

The battery charger will be wired to the AC shoreline inlet through an AC receptacle adjacent to the battery charger.

The battery charger will be located in the left body compartment mounted on the left wall as high as possible.

The battery charger indicator will be located in the driver's step area.

### **KUSSMAUL AUTO EJECT FOR SHORELINE**

There will be one (1) Kussmaul Model 091-20WP-120, 20 amp 120 volt AC shoreline inlet(s) provided to operate the dedicated 120 volt AC circuits on the apparatus.

The shoreline inlet(s) will include red weatherproof flip up cover(s).

There will be a release solenoid wired to the vehicle's starter to eject the AC connector when the engine is starting.

The shoreline(s) will be connected to battery charger.

There will be a mating connector body supplied with the loose equipment.

There will be a label installed near the inlet(s) that state the following:

- Line Voltage
- Current Rating (amps)
- Phase
- Frequency

The shoreline receptacle will be located on the driver side of cab, above wheel.

### **SHORELINE TO SHORELINE TRANSFER SWITCH**

There will be an automatic transfer switch between the shoreline to the second shoreline inlet. The loads connected to the transfer switch from the first shoreline inlet will be power from the second shoreline inlet when the second shoreline inlet is energized.

### **ALTERNATOR**

A Delco Remy®, Model 55SI, alternator will be provided. It will have a rated output current of 430 amps, as measured by SAE method J56. The alternator will feature an integral regulator and rectifier system that has been tested and qualified to an ambient temperature of 257 degrees Fahrenheit (125 degrees Celsius). The alternator will be connected to the power and ground distribution system with heavy-duty cables sized to carry the full rated alternator output.

### **ELECTRONIC LOAD MANAGER**

An electronic load management (ELM) system will be provided that monitors the vehicle's 12-volt electrical system, automatically reducing the electrical load in the event of a low voltage condition, and automatically restoring the shed electrical loads when a low voltage condition expires. This ensures the integrity of the electrical system.

For improved reliability and ease of use, the load manager system will be an integral part of the vehicle's solid state control system requiring no additional components to perform load management tasks. Load management systems which require additional components will not be allowed.

The system will include the following features:

- System voltage monitoring.
- A shed load will remain inactive for a minimum of five minutes to prevent the load from cycling on and off.
- Sixteen available electronic load shedding levels.
- Priority levels can be set for individual outputs.
- High Idle to activate before any electric loads are shed and deactivate with the service brake.

- If enabled:
  - "Load Man Hi-Idle On" will display on the information center.
  - Hi-Idle will not activate until 30 seconds after engine start up.
- Individual switch "on" indicator to flash when the particular load has been shed.
- The information center indicates system voltage.

The information center, where applicable, includes a "Load Manager" screen indicating the following:

- Load managed items list, with priority levels and item condition.
- Individual load managed item condition:
  - ON = not shed
  - SHED = shed

### **SEQUENCER**

A sequencer will be provided that automatically activates and deactivates vehicle loads in a preset sequence thereby protecting the alternator from power surges. This sequencer operation will allow a gradual increase or decrease in alternator output, rather than loading or dumping the entire 12 volt load to prolong the life of the alternator.

For improved reliability and ease of use, the load sequencing system will be an integral part of the vehicle's solid state control system requiring no additional components to perform load sequencing tasks. Load sequencing systems which require additional components will not be allowed.

Emergency light sequencing will operate in conjunction with the emergency master light switch. When the emergency master switch is activated, the emergency lights will be activated one by one at half-second intervals. Sequenced emergency light switch indicators will flash while waiting for activation.

When the emergency master switch is deactivated, the sequencer will deactivate the warning light loads in the reverse order.

Sequencing of the following items will also occur, in conjunction with the ignition switch, at half-second intervals:

- Cab Heater and Air Conditioning
- Crew Cab Heater (if applicable)
- Crew Cab Air Conditioning (if applicable)
- Exhaust Fans (if applicable)
- Third Evaporator (if applicable)

### **HEADLIGHTS**

There will be a HiViz part number FT-4X6-4KIT, that includes four (4) 4.00" high x 6.00" long rectangular LED lights with parking lamp illumination around the outside of the lamps mounted in the front quad style, chrome housing on each side of the cab grille:

- the outside lamp on each side will contain a part number FT-4X6-HL with low beam LEDs

- the inside lamp on each side will contain a part number FT-4X6-H with high beam LEDs
- the lights will be controlled through the headlight switch

### **DIRECTIONAL LIGHTS**

There will be two (2) Whelen 600® series, LED combination directional/marker lights provided. The lights will be located on the outside cab corners, next to the headlights.

The color of the lenses will be the same color as the LED's.

### **INTERMEDIATE LIGHT**

There will be two (2) Weldon, Model 9186-8580-29, amber LED turn signal marker lights furnished, one (1) each side, in the rear fender panel. The light will double as a turn signal and marker light.

### **CAB CLEARANCE/MARKER/ID LIGHTS**

There will be seven (7) amber LED lights provided to indicate the presence and overall width of the vehicle in the following locations:

- Three (3) amber LED identification lights will be installed in the center of the cab above the windshield.
- Two (2) amber LED clearance lights will be installed, one (1) on each outboard side of the cab above the windshield.
- Two (2) amber LED marker lights will be installed, one (1) on each side above the cab doors.

### **PLATFORM CLEARANCE/MARKER/ID LIGHTS**

There will be five (5) amber LED lights provided to indicate the presence and overall width of the vehicle in the following locations:

- Three (3) amber LED identification lights will be installed on the front of the aerial basket, centered.
- Two (2) amber LED clearance/marker lights will be installed, one (1) on each corner of the aerial basket visible from the side and the front of the vehicle.

### **FRONT CAB SIDE DIRECTIONAL/MARKER LIGHTS**

There will be two (2) Truck-Lite®, Model 19036Y, amber LED lights installed to the outside of the chrome wrap around bezel, one (1) on each side of the cab.

The lights will activate as marker lights with the headlight switch and directional lights with the corresponding directional circuit.

### **REAR CLEARANCE/MARKER/ID LIGHTING**

There will be three (3) LED identification lights located at the rear installed per the following:

- As close as practical to the vertical centerline

- Centers spaced not less than 6.00" or more than 12.00" apart
- Red in color
- All at the same height

There will be two (2) LED lights installed at the rear of the apparatus used as clearance lights located at the rear of the apparatus per the following:

- To indicate the overall width of the vehicle
- One (1) each side of the vertical centerline
- As near the top as practical
- Red in color
- To be visible from the rear
- All at the same height

There will be two (2) LED lights installed on the side of the apparatus used as marker lights as close to the rear as practical per the following:

- To indicate the overall length of the vehicle
- One (1) each side of the vertical centerline
- As near the top as practical
- Red in color
- To be visible from the side
- All at the same height

The lights will be mounted with no guard.

There will be two (2) red reflectors located on the rear of the truck facing to the rear. One (1) each side, as far to the outside as practical, at a minimum of 15.00", but no more than 60.00", above the ground.

There will be two (2) red reflectors located on the side of the truck facing to the side. One (1) each side, as far to the rear as practical, at a minimum of 15.00", but no more than 60.00", above the ground.

Per FMVSS 108 and CMVSS 108 requirements.

### **MARKER LIGHTS**

There will be one (1) pair of amber and red LED marker lights with rubber arm, located at the rear most lower corner of the body. The amber lens will face the front and the red lens will face the rear of the truck.

These lights will be activated with the running lights of the vehicle.

### **REAR FMVSS LIGHTING**

The rear stop/tail and directional LED lighting will consist of the following:



- Two (2) Whelen®, Model M6BTT, red LED stop/tail lights
- Two (2) Whelen, Model M6T, amber LED arrow turn lights

The lights will be provided with color lenses.

The lights will be mounted in a polished combination housing.

There will be two (2) Whelen Model M6BUW, LED backup lights provided in the tail light housing.

#### **LICENSE PLATE BRACKET**

There will be one (1) license plate bracket mounted on the rear of the body.

A white LED light will illuminate the license plate. A stainless steel light shield will be provided over the light that will direct illumination downward, preventing white light to the rear.

#### **LIGHTING BEZEL**

There will be two (2) Whelen, Model M6FCV4P, four (4) place chromed ABS housings with Pierce logos provided for the rear M6 series stop/tail, directional, back up, scene lights or warning lights.

#### **BACK-UP ALARM**

A PRECO, Model 1040, solid-state electronic audible back-up alarm that actuates when the truck is shifted into reverse will be provided. The device will sound at 60 pulses per minute and automatically adjust its volume to maintain a minimum ten (10) dBA above surrounding environmental noise levels.

#### **CAB PERIMETER SCENE LIGHTS**

There will be four (4) Amdor, Model AY-LB-12HW020, 350 lumens each, 20.00" white LED strip lights provided, one (1) for each cab door.

These lights will be activated automatically when the battery switch is on and the exit doors are opened or by the same means as the body perimeter scene lights.

#### **PUMP HOUSE PERIMETER LIGHTS**

There will be two (2) Amdor, Model AY-LB-12HW020, 350 lumens each, 20.00" LED weatherproof strip lights with brackets provided under the pump panel running boards, one (1) each side.

If the combination of options in the vehicle does not permit clearance for a 20.00" light, a 12.00" version of the Amdor light will be installed.

The lights will be controlled by the same means as the body perimeter lights.

#### **BODY PERIMETER SCENE LIGHTS**

There will be two (2) Amdor, Model AY-LB-12HW020, 350 lumens, 20.00" long, with white LED's, 12 volt lights provided.

The lights will be mounted in the following locations:

- One (1) light under the driver's side turntable access steps

- One (1) light under the passenger's side turntable access steps

The perimeter scene lights will be activated when the battery switch is on and the parking brake is applied.

### **ADDITIONAL PERIMETER LIGHTS**

There will be two (2) lights - Amdor® Model AY-LB-12HW020, 350 lumens, 20.00" long, with white LED's installed with one (1) light under compartment D1 and one (1) light under compartment P1.

With the chassis battery switch energized, the lights will be activated by the same means as the body perimeter lights.

### **ADDITIONAL PERIMETER LIGHTS**

There will be two (2) lights Amdor®, Model AY-LB-12HW012, 190 lumens each, 12.00" white LED perimeter light(s) provided one (1) light under each side of the front bumper spaced evenly.

These lights will be activated the same as the body perimeter lights.

### **STEP LIGHTS**

There will be four (4) white LED step lights will be provided at the rear to illuminate the tailboard/step area.

In order to ensure exceptional illumination, each light will provide a minimum of 25 foot-candles (fc) covering an entire 15" x 15" square placed ten (10) inches below the light and a minimum of 1.5 fc covering an entire 30" x 30" square at the same ten (10) inch distance below the light.

These step lights will be actuated with the perimeter scene lights.

All other steps on the apparatus will be illuminated per the current edition of NFPA 1901.

### **12 VOLT LIGHTING**

There will one (1) Whelen® Model P\*H2\*, 17,750 lumens 12 volt DC LED light(s) with a combination of flood and spot optics installed on the apparatus located, on top of the body, over the forward rear axle on the driver side.

The painted parts of this light assembly to be white

The light(s) to be installed on adjustable bracket(s).

The lights will be controlled by a switch at the driver's side switch panel.

The light(s) may be load managed when the parking brake is applied.

### **12 VOLT LIGHTING**

There will one (1) Whelen® Model P\*H2\*, 17,750 lumens 12 volt DC LED light(s) with a combination of flood and spot optics installed on the apparatus located, on top of the body, over the forward rear axle on the passenger side.

The painted parts of this light assembly to be white

The light(s) to be installed on adjustable bracket(s).

The lights will be controlled by a switch at the driver's side switch panel.

The light(s) may be load managed when the parking brake is applied.

### **12 VOLT DC SCENE LIGHTS**

There will be one (1) Whelen® Model P\*H1\*, 8,875 lumens 12 volt DC powered lights with white LEDs and a combination of flood and spot optics installed on the apparatus located, on the passenger side, behind the crew cab doors.

The light(s) to be installed in a 15 degree vertical recessed bracket.

The painted parts of this light assembly to be white.

The lights will be activated by a switch at the driver's side switch panel.

The light(s) may be load managed when the parking brake is applied.

### **12 VOLT DC SCENE LIGHTS**

There will be one (1) Whelen® Model P\*H1\*, 8,875 lumens 12 volt DC powered lights with white LEDs and a combination of flood and spot optics installed on the apparatus located, on the driver side, behind the crew cab door.

The light(s) to be installed in a 15 degree vertical recessed bracket.

The painted parts of this light assembly to be white.

The lights will be activated by a switch at the driver's side switch panel.

The light(s) may be load managed when the parking brake is applied.

### **DECK LIGHTS**

There shall be two (2) Whelen®, Model MPBW, white 12 volt DC LED floodlights with stud bail mount provided at the rear of the hose bed, one (1) each side.

The lights will be activated by a control from a switch at the rear of the truck and a switch located at the driver side switch panel.

### **WALKING SURFACE LIGHT**

There will be Model FRP, 4" round black 12 volt DC LED floodlight(s) with bolt mount provided to illuminate the entire designated walking surface on top of the body.

The light(s) will be activated when the body step lights are on.

## **WATER TANK**

It will have a capacity of 200 gallons and will be constructed of polypropylene plastic in a rectangular shape.

The joints and seams will be nitrogen welded inside and out.

The tank will be baffled in accordance with NFPA Bulletin 1901 requirements.

The baffles will have vent openings at both the top and bottom of each baffle to permit movement of air and water between compartments.

The longitudinal partitions will be constructed of .38" polypropylene plastic and extend from the bottom of the tank through the top cover to allow positive welding.

The transverse partitions extend from 4" off the bottom to the underside of the top cover.

All partitions interlock and will be welded to the tank bottom and sides.

The tank top will be constructed of .50" polypropylene.

It will be recessed .38" and will be welded to the tank sides and the longitudinal partitions.

It will be supported to keep it rigid during fast filling conditions.

Construction will include 2.00" polypropylene dowels spaced no more than 30.00" apart and welded to the transverse partitions.

Two of the dowels will be drilled and tapped (.50" diameter, 13.00" deep) to accommodate lifting eyes.

A sump will be provided at the bottom of the water tank. The sump will include a drain plug and the tank outlet.

Tank will be installed in a fabricated "cradle" assembly constructed of structural steel.

Sufficient crossmembers are provided to properly support bottom of tank.

Crossmembers are constructed of steel bar channel or rectangular tubing.

Tank "floats" in cradle to avoid torsional stress caused by chassis frame flexing.

Rubber cushions, .50" thick x 3.00" wide, will be placed on all horizontal surfaces that the tank rests on.

Stops are provided to prevent an empty tank from bouncing excessively while moving vehicle.

Tank mounting system is approved by the manufacturer.

Fill tower will be constructed of .50" polypropylene and will be a minimum of 8.00" wide x 14.00" long.

Fill tower will be furnished with a .25" thick polypropylene screen and a hinged cover.

An overflow pipe, constructed of 4.00" schedule 40 polypropylene, will be installed approximately halfway down the fill tower and extend through the water tank and exit to the rear of the rear axle.

### **HOSE BED**

The hose bed will be fabricated of 0.125" thick 5052-H32 aluminum with a tensile strength of 31,000.

The sides of the hose bed will not form any portion of the fender compartments.

The hose bed will be located ahead of the ladder turntable between the tank and side body compartments.

Hose removal will be at the rear of the body via "chutes" under the turntable on the right side. Each chute will be enclosed with a full height smooth aluminum door. There will be a lift and turn latch and a pneumatic cylinder at the top of the door (if applicable).

The hose bed flooring will consist of removable aluminum grating with a top surface that is corrugated to aid in hose aeration.

The grating slats will be 0.50" wide x 4.50" long with spacing between the slats for hose ventilation.

Hose capacity will be a minimum of 500' of 5".

### **AERIAL HOSE BED HOSE RESTRAINT**

The hose in the hose bed will be restrained by one (1) black nylon Velcro® strap at the top of the hose bed. The strap will be installed to the top of the hose bed side sheets.

### **RUNNING BOARDS**

A running board will be provided on each side of the front body to allow access to the backboard/crosslay storage area. The running boards will be designed with a grip pattern punched into .125" bright aluminum treadplate material providing support, slip resistance, and drainage.

### **HANDRAILS**

The handrails will be 1.25" diameter anodized aluminum extrusion, with a ribbed design, to provide a positive gripping surface.

Chrome plated end stanchions will support the handrail. Plastic gaskets will be used between end stanchions and any painted surfaces.

Drain holes will be provided in the bottom of all vertically mounted handrails.

- Two (2) handrails will be provided, one above each running board.

### **TURNTABLE STEPS**

Steps to access the turntable from the left side and right side will be provided just behind the compartmentation. There shall be no bottom flip step provided. The bottom step will have a step

height not exceeding 24.00" from the ground to the top surface of the step at any time. All steps will have a height no greater than 14.00" from top surface to top surface.

The steps will be a swing-down design, with the stepping area made of Morton Tread-Grip® channel.

The stepwell will be lined with bright aluminum treadplate to act as scuffplates.

A Hansen illuminated knurled aluminum handrail will be provided on each side of the access steps. The handrails to the rear of the access steps will consist of one (1) vertical handrail on the body and one (1) horizontal handrail on the top of the body. The end stanchions will be provided by Hansen. The lights will be activated by the same means as the body perimeter scene lights. The light will be red.

The steps will be connected to the "Do Not Move Truck" indicator.

A hand hold will be provided in the left and right side of each set of access steps.

### **STEP LIGHTS**

There will be three (3) white LED step lights provided for each set of aerial turntable access steps.

In order to ensure exceptional illumination, each light will provide a minimum of 25 foot-candles (fc) covering an entire 15" x 15" square placed ten (10) inches below the light and a minimum of 1.5 fc covering an entire 30" x 30" square at the same ten (10) inch distance below the light.

The step lights will be actuated by the aerial master switch in the cab.

### **SMOOTH ALUMINUM REAR WALL**

The rear wall will be smooth aluminum.

### **TOW EYES**

Two (2) rear painted tow eyes will be located at the rear of the apparatus and will be mounted directly to the torque box. The inner and outer edges of the tow eyes will be radiused.

### **COMPARTMENTATION**

Compartmentation will be fabricated of 0.125" 5052 aluminum. The side compartments are an integral assembly with the rear fenders. Fully enclosed rear wheel housings will be provided to prevent rust pockets and for ease of maintenance. Due to the severe loading requirements of this aerial, a method of compartment body support suitable for the intended load will be provided.

The backbone of the support system will be the chassis frame rail, which is the strongest component of the chassis and is designed for sustaining maximum loads.

A support system will be used which will incorporate a floating substructure by using Neoprene Elastomer isolators to allow the body to remain rigid while the chassis goes through its natural flex. The isolators will have a broad range of proven viability in vehicular applications, be of a fail safe design, and allow for all necessary movement in three (3) transitional and rotational modes. This will result in a 500 lb equipment rating for each lower compartment of the body.

The compartmentation in front of the rear axle will include a 3.00" steel support assemblies which are bolted to the chassis frame rails. A steel framework will be mounted to the body above these support assemblies connected to the support assemblies with isolators. There will be one (1) support assembly mounted to each chassis frame rail.

The compartmentation behind the rear axle will include 3.00" steel support assemblies which are bolted to the chassis frame rails and extend underneath to the outside edge of the body. The support assembly will be coated to isolate the dissimilar metals before it is bolted to the body. There will be one (1) support assembly mounted to each chassis frame rail.

Compartment flooring will be of the sweep out design with the floor higher than the compartment door lip. The compartment door openings are framed by flanging the edges in 1.75" and bending out again 0.75" to form an angle. Drip protection is provided over all door openings by means of bright aluminum extrusion or formed bright aluminum treadplate. Side compartment tops will be covered with bright aluminum treadplate with a 1.00" rolled over edge on the front, rear and outward side. The covers are fabricated in one (1) piece and have the corners welded. A bright aluminum treadplate cover will be provided on the front wall of each side compartment. All screws and bolts which protrude into a compartment will have acorn nuts at the ends to prevent injury.

The body design has been fully tested. Proven engineering and test techniques such as finite element analysis, model analysis, stress coating and strain gauging have been performed with special attention given to fatigue life and structural integrity of the compartment body and substructure.

#### **AGGRESSIVE WALKING SURFACE**

All exterior surfaces designated as stepping, standing, and walking areas will comply with the required average slip resistance of the current NFPA standards.

#### **LOUVERS**

All body compartments will have a minimum of one (1) set of louvers stamped into a wall to provide the proper airflow inside the compartment and to prevent water from dripping into the compartment. These louvers will be formed into the metal and not added to the compartment as a separate plate.

#### **LEFT SIDE COMPARTMENTATION**

A full height rollup door compartment ahead of the rear wheels will be provided. The compartment will be 41.75" wide x 56.38" high x 24.25" deep inside with a clear door opening of 38.75" wide x 56.38" high.

One (1) rollup door compartment will be located above the fender compartments and over the rear axles. The compartment will be 72.13" wide x 33.25" high x 24.25" deep inside with a clear door opening of 63.75" wide x 25.50" high.

A compartment with a single pan stainless steel lift up door will be located above the front stabilizer. The compartment will be 24.25" wide x 15.50" high x 24.25" deep with a door opening of 18.50" wide x 12.75" high. The compartment will have an aluminum treadplate cover with access to the top of the cord reel and will be extended above the catwalk to accommodate the reel. A top hinged horizontal lift

up stainless steel door will be provided with pneumatic cylinders for payout of the cord. The three (3) sides of the door opening will have stainless steel scuffplates.

There will be one (1) compartment located below the turntable with a lift-up door. The compartment will be 39.38" wide x 18.38" high x 21.25" deep with a door opening of 35.00" wide x 14.88" high.

A full height roll-up door compartment behind the rear wheels will be 43.75" wide x 49.25" high x 21.25" deep. The clear door opening will be 40.75" wide x 41.62" high.

#### **PASSENGER SIDE COMPARTMENTATION**

A full height roll-up door compartment ahead of the rear wheels will be provided. The compartment will be 41.75" wide x 56.38" high x 24.25" deep inside with a clear door opening of 38.75" wide x 56.38" high.

One (1) roll-up door compartment will be located above the fender compartments and over the rear axles. The compartment will be 72.13" wide x 33.25" high x 12.00" deep inside with a clear door opening of 63.75" wide x 25.50" high.

A compartment with a single pan stainless steel lift up door will be located above the front stabilizer. The compartment will be 24.25" wide x 15.50" high x 24.25" deep with a door opening of 18.50" wide x 12.75" high. The compartment will have an aluminum 4-way cover with access to the top of the cord reel and will be extended above the catwalk to accommodate the reel.

A trough style hose bed will be located behind the compartments. This hose bed will not extend into the compartment above the front stabilizers.

There will be one (1) compartment located below the turntable with a lift-up door. The compartment will be 39.38" wide x 18.38" high x 12.00" deep with a door opening of 35.00" wide x 14.88" high.

A full height roll-up door compartment behind the rear wheels will be 43.75" wide x 49.25" high x 21.25" deep inside the lower 29.75" and 12.00" deep in the upper portion. The clear door opening will be 40.75" wide x 41.62" high.

#### **SIDE COMPARTMENT ROLLUP DOORS**

There will be one (1) compartment door installed on the side compartments. The doors will be double faced aluminum construction, painted one (1) color to match the lower portion of the body and manufactured by R-O-M Corporation.

Every slat will have interlocking end shoes to prevent slat from moving side-to-side and binding the door.

Slats will have interlocking joints with a folding locking flange to provide security and prevent penetration by sharp objects.

Slats will be double-wall extrusion 1.366" high by .315" thick.



Between each slat will be a co-extruded PVC inner seal to prevent metal-to-metal contact and to repel moisture. This inner seal is not visible to detract from appearance of door.

Mounting and adjusting the curtain will be done with a clip system that connects the curtain slats to the operator drum allowing for easy tension adjustment without tools.

A lift bar with locking key latches to be provided for each roll-up door. The keys to be Model 751 to match all compartment and cab doors. The lift bar will be located at the bottom of the door and have latches on the outer extrusion of the door frame. A ledge will be supplied over the lift bar as additional area to aid in closing the door.

Each door will be constructed from an aluminum box section. The exterior surface of each slat will be flat. The interior surfaces will be concave to provide strength and prevent loose equipment from jamming the door from inside.

Each roll-up door will have a 4.00" diameter counterbalance operator drum to assist in lifting the door.

The header for the roll-up door assembly will not exceed 4.00".

A heavy-duty magnetic switch will be used for control of open compartment door warning lights.

#### **SIDE COMPARTMENT LAP DOORS**

All hinged compartment doors will be lap style with double panel construction and fabricated of 0.09" 5052H32 aluminum. Doors will be a minimum of 1.50" thick. To provide additional door strength, a "C" section reinforcement will be installed between the outer and interior panels.

Doors will be provided with a closed cell rubber gasket around the surface that laps onto the body. A second heavy-duty automotive rubber molding with a hollow core will be installed on the door framing that seals onto the interior panel, to ensure a weather resisting compartment.

All compartment doors will have polished stainless steel continuous hinge with a pin diameter of 0.25", that is bolted or screwed on with stainless steel fasteners. (Hinges which are welded on will not be acceptable.) A dielectric substance will be applied to each hinge fastener.

All door lock mechanisms will be fully enclosed within the door panels to prevent fouling of the lock in the event equipment inside shifts into the lock area.

Doors will be latched with recessed, polished stainless steel D-ring handles and Eberhard 106 locks.

To prevent corrosion caused by dissimilar metals, compartment door handles will not be attached to outer door panel with screws. A rubber gasket will be provided between the D-ring handle and the door.

#### **REAR BUMPER**

A 5.00" rear bumper will be furnished. Bumper will be constructed of steel framework and will be covered with polished aluminum treadplate. The bumper will be 4.00" deep x 5.00" high and will be spaced away from the body approximately 1.00". It will extend the full width of the body.

### **DOOR GUARD**

There will be one (1) compartment door that will include a guard/drip pan designed to protect the rollup door from damage when in the retracted position and contain any water spray. The guard will be fabricated from stainless steel and installed on the left side rearward compartment, left side forward over the wheel compartment, left side forward compartment, right side rearward compartment, right side forward over the wheel compartment, right side forward compartment and rear compartment.

### **ELECTRIC DOOR LOCKS**

There will be ten (10) door(s) located All Roll up Rom Doors on the sides of the body equipped with electric locks. The switch for control will be located all body compartments. In the event of loss of power, a manual override is available.

### **ROLL-UP DOOR TRIM**

The exterior of the aluminum trim around the door opening will be painted job color.

There will be ten (10) compartments with the trim painted.

### **COMPARTMENT LIGHTING**

There will be nine (9) compartment(s) with two (2) white 12 volt DC LED compartment light strips. The dual light strips will be centered vertically along each side of the door framing. There will be two (2) light strips per compartment. The dual light strips will be in all body compartment(s).

Any remaining compartments without light strips will have a 6.00" diameter Truck-Lite, Model: 79384 light. Each light will have a number 1076 one filament, two wire bulb.

Opening the compartment door will automatically turn the compartment lighting on.

### **MOUNTING TRACKS**

There will be six (6) sets of tracks for mounting shelf(s) in LS1, LS3, LS4, RS1, RS3 and RS4. These tracks will be installed vertically to support the adjustable shelf(s), and will be full height of the compartment. The tracks will be painted to match the compartment interior.

### **ADJUSTABLE SHELVES**

There will be 14 shelves with a capacity of 500 lb provided.

The shelf construction will consist of .188" aluminum painted spatter gray with 2.00" sides.

Each shelf will be infinitely adjustable by means of a threaded fastener, which slides in a track.

The shelves will be held in place by .12" thick stamped plated brackets and bolts.

The location(s) will be determined at a later date.

### **SLIDE-OUT ADJUSTABLE HEIGHT TRAY**

There will be two (2) slide-out trays provided.

Each tray will have 2.00" high sides and a minimum capacity rating of 250 lb in the extended position.

Each tray will be constructed of aluminum painted spatter gray.

Each tray will be mounted on a pair of side mounted slides. The slide mechanisms will have ball bearings for ease of operation and years of dependable service. The slides will be mounted to shelf tracks to allow the tray to be adjustable up and down within the designated mounting location.

An automatic lock will be provided for both the in and out tray positions. The lock trip mechanism will be located at the front of the tray and will be easily operated with a gloved hand.

The location(s) will be determined at a later date

#### **SLIDE-OUT/TILT-DOWN TRAY**

There will be two (2) slide-out trays provided.

The bottom of each tray will be constructed of 0.188" thick aluminum painted spatter gray while special aluminum extrusions will be utilized for the tray sides, ends, and tracks. The corners will be welded to form a rigid unit.

A spring loaded lock will be provided on each side at the front of the tray. Releasing the locks will allow the tray to slide out approximately two-thirds (2/3) of its length from the stowed position and tip 30 degrees down from horizontal. The tray will be equipped with ball bearing rollers for smooth operation.

Rubber padded stops will be provided for the tray in the extended position.

The capacity rating of the tray will be a minimum of 215 lb in the extended position.

The vertical position of the tray within the compartment will be adjustable.

The location(s) will be determined at a later date.

#### **SLIDE-OUT FLOOR MOUNTED TRAY**

There will be six (6) floor mounted slide-out tray(s) provided.

Each tray will have 2.00" high sides and a minimum capacity rating of 500 lb in the extended position.

Each tray will be constructed of aluminum painted spatter gray

There will be two undermount-roller bearing type slides rated at 250lb each provided. The pair of slides will have a safety factor rating of 2.

To ensure years of dependable service, the slides will be coated with a finish that is tested to withstand a minimum of 1,000 hours of salt spray per ASTM B117.

To ensure years of easy operation, the slides will require no more than a 50lb force for push-in or pull-out movement when fully loaded after having been subjected to a 40 hour vibration (shaker) test under full load. The vibration drive file will have been generated from accelerometer data collected from a heavy truck chassis driven over rough gravel roads in an unloaded condition. Proof of compliance will be provided upon request.

Automatic locks will be provided for both the "in" and "out" positions. The trip mechanism for the locks will be located at the front of the tray for ease of use with a gloved hand.

The location(s) will be RS1, RS4, LS1 and LS4.

### **SWING OUT TOOLBOARD**

A swing out aluminum toolboard will be provided.

It will be a minimum of .188" thick without holes in the board.

A 1.00" x 1.00" aluminum tube frame will be welded to the edge of the pegboard.

The board will be mounted on a pivoting device at the front of the compartment on the top and bottom to allow easy movement in and out of the compartment. The maximum tool load will be 400 pounds.

The board will have positive lock in the stowed and extended position.

The board will be mounted on adjustable tracks from front to back within the compartment.

There will be One (1) toolboard(s) provided. The toolboard(s) will be spatter gray painted and installed to be determined.

### **TOOL BOARD**

An aluminum tool board will be provided.

It will be a minimum of .188" thick with .20" diameter holes in a pegboard pattern with 1.00" centers between holes.

A 1.00" x 1.00" aluminum tube frame will be welded to the edge of the board.

The board will be installed on adjustable tracks on a slide out tray. The tracks will allow side to side adjustment. The board will be as high as space permits and full length of the tray. The tray is not included in this option.

There will be One (1) toolboard(s) provided. The toolboard(s) will be spatter gray painted and installed tbd.

### **DRAWER ASSEMBLY**

A slideout drawer assembly will be installed to be determined.

The clear dimension of the top drawer will be 2.25" with a face plate that is 3.00" high x 21.00" deep. The clear dimension of the second drawer will be 3.75" with a face plate that is 4.00" high x 21.00" deep. The clear dimension of the third drawer will be 3.75" with a face plate that is 4.00" high x 21.00" deep. The clear dimension of the fourth drawer will be 3.75" with a face plate that is 4.00" high x 21.00" deep. The clear dimension of the bottom drawer will be 3.75" with a face plate that is 4.00" high x 21.00" deep.

The drawers will have a capacity of 250 pounds.

The drawers will be mounted in a cabinet housing constructed of light gray powder coated aluminum with anodized aluminum frames. The housing will be 24.00" deep, and completely enclose the drawer.

A full-length aluminum extruded rail will be provided at the top edge of each drawer. This rail will act as the latching mechanism as well as the handle for each drawer.

There will be a total of one (1) provided.

### **RUB RAIL**

Bottom edge of the side compartments will be trimmed with a bright aluminum extruded rub rail.

Trim will be 2.12" high with 1.38" flanges turned outward for rigidity.

The rub rails will not be an integral part of the body construction, which allows replacement in the event of damage.

### **BODY FENDER CROWNS**

Stainless steel fender crowns will be provided around the rear wheel openings.

A rubber welting will be provided between the body and the crown to seal the seam and restrict moisture from entering.

### **HARD SUCTION HOSE**

Hard suction hose will not be required.

### **THREE AIR BOTTLE STORAGE COMPARTMENT**

A total of two (2) air bottle compartments will be provided and located one (1) on the left side and one (1) on the right side, centered between the tandem rear wheels. The air bottle compartment will consist of individual bins each designed to hold an air bottle with a maximum diameter of 7.63" and a maximum depth of 26.00".

Each compartment will hold three (3) air bottles stored horizontally. Each bottle will be separated by a partition.

Flooring will be rubber lined and have a drain hole. A drop down door with support cables with pair of Southco raised trigger C2 chrome lever latches will be provided for each compartment. The door will be painted stainless steel. A dielectric barrier will be provided between the door hinge, hinge fasteners and the body sheet metal.

### **AIR BOTTLE COMPARTMENT STRAP**

Straps will be provided in the air bottle compartment(s) to help contain the air bottles. The straps will wrap around the neck of each bottle and attach to the wall of the compartment.

### **SINGLE AIR BOTTLE STORAGE COMPARTMENT**

A quantity of two (2) air bottle compartments, 7.75" in diameter x 26.00" deep, will be provided on the left side rearward of the rear wheels. The triangular door shall cover the air bottle opening and the fuel tank access, and on the right side forward of the rear wheels. A painted stainless steel door with a

Southco raised trigger C2 chrome lever latch will be provided to contain the air bottle. A dielectric barrier will be provided between the door hinge, hinge fasteners and the body sheet metal.

Inside the compartment, black rubber matting will be provided.

### **EXTINGUISHER STORAGE**

A quantity of two (2) extinguisher compartments will be provided on the right side forward of the rear wheels and on the right side rearward of the rear wheels. The extinguisher compartment will be in the form of a 9.00" square tube and of adequate depth to accommodate different size extinguishers. A painted stainless steel door with a Southco raised trigger C2 chrome lever latch will be provided to contain the extinguisher. A dielectric barrier will be provided between the door hinge, hinge fasteners, and the body sheet metal.

Inside the compartment, black Dura-Surf friction reducing material will be provided. There will also be a drain hole for each compartment.

### **EXTENSION LADDER**

There will be one (1) 35' two (2) section aluminum Duo-Safety Series 1200-A extension ladder(s) provided.

### **ADDED EXTENSION LADDER**

There will be one (1) 28', two (2) section, aluminum, Duo-Safety Series 1200A extension ladder provided.

### **AERIAL EXTENSION LADDER**

There will be one (1) 24' two (2) section aluminum Series 900-A extension ladder(s) provided and located in the aerial torque box.

### **ROOF LADDERS**

There will be two (2) 16' aluminum Duo-Safety Series 875-A roof ladders provided.

### **AERIAL FOLDING LADDER**

There will be one (1) 10' aluminum Duo-Safety Series 585-A folding ladder(s) provided and located in the aerial torque box.

### **GROUND LADDER STORAGE**

The ground ladders are stored within the torque box and are removable from the rear.

Ladders will be enclosed to prevent road dirt and debris from fouling or damaging the ladders.

The ladders rest in full length stainless steel slides and are arranged in such a manner that any one ladder can be removed without having to move or remove any other ladder.

A Gortite rollup door will be provided at the rear, double faced, aluminum construction, and an anodized satin finish. A polished stainless steel lift bar to be provided for the rear roll-up door. The

latching mechanism will consist of a full length lift bar lock with latches on the outer extrusion of the door frame.

A stainless plate with a 2-bend flange and a stainless steel hinge will be provided to secure the aerial ladder complement. The plate assembly will be mounted to the bottom of the entrance of the torque box ladder storage area.

When the plate is vertical, it will secure the ladders and prevent them from migrating to the rear of the apparatus. When the plate is down and not securing the ladders, the rollup door can not close, which will activate the "Open Door Indicator Light" within the cab. The rollup door together with hinge friction will secure the plate in place during driving operations.

A door guard will be provided to prevent tools inside the torque box from damaging the rollup door.

### **LADDER STORAGE LIGHTING**

There will be two (2) Truck Lite Model 40227C, 4.00" white incandescent lights with Model 40700, grommets used to illuminate the torque box ladder storage compartment. One (1) each side will be located on the side wall of the torque box near the ladder storage entry area.

The lights will be activated when the ladder storage compartment door is opened.

### **NESTED LADDER STORAGE**

There will be nested ladders on the right side of the ladder storage compartment.

### **PIKE POLES**

There will be two (2) 12' Duo Safety pike pole(s) with fiberglass handles provided. The pike pole(s) will be stored in tubular holders located in the ground ladder storage compartment.

#### **8' PIKE POLE**

There will be two (2) 8' Duo Safety pike pole(s) with fiberglass handle provided. The pike pole(s) will be stored in tubular holders located in the ground ladder storage compartment.

#### **6' PIKE POLE**

There will be two (2) 6' Duo Safety pike pole(s) with fiberglass handle provided. The pike pole(s) will be stored in tubular holders located in the ground ladder storage compartment.

### **ADDITIONAL PIKE POLE(S)**

There will be two (2) 6' long trash hook(s), Fire Hooks Unlimited TRH-6, with fiberglass shaft and "D" handle provided.

### **PIKE POLE STORAGE IN TORQUE BOX/LADDER STORAGE**

There will be ABS tubing provided in the torque box/ladder storage area for a total of six (6) pike poles.

If the head of a pike pole can come into contact with a painted surface, a stainless steel scuffplate will be provided.

### **PIKE POLE STORAGE**

Smooth aluminum U-shaped trough(s) for the storage of one (1) pike pole, with D-handle style grip, will be provided and installed forward of the lower crosslay to be pulled from the driver side.

### **PIKE POLE STORAGE**

Aluminum tubing will be used for the storage of one (1) pike pole and will be located forward of the crosslay to be pulled from the driver side. If the head of a pike pole can come in contact with a painted surface, a stainless steel scuffplate will be provided. The pike pole tube will be notched to allow a New York style pike pole to fit into the tube.

### **PUMP**

Pump will be a Pierce, low profile, 1500 gpm single stage midship mounted centrifugal type, mounted below the cab. The pump will have a 15 percent reserve capacity to allow for extended time between pump rebuild. To ensure efficient pump/vehicle design the capacity to weight ratio will not be less than 1.5:1.

The pump casing will consist of three (3) discharge outlets, one (1) to each side in line with the impeller and one (1) to the rear. The pump casing will incorporate two (2) water strippers to maintain radial balance.

Pump will be the Class A type.

Pump will be certified to deliver the percentage of rated discharge from draft at pressure indicated below:

- 100 percent of rated capacity at 150 psi net pump pressure
- 70 percent of rated capacity at 200 psi net pump pressure
- 50 percent of rated capacity at 250 psi net pump pressure

The pump will have the capacity to deliver the percentage of rated discharge from a pressurized source as indicated below:

- 135 percent of rated capacity at 100 psi net pump pressure from a 5 psi source

Pump body will be fine-grained gray iron. Pump will incorporate a heater/cooling jacket integral to the pump housing.

The impeller will be high strength vacuum cast bronze alloy accurately machine balanced and splined to a 10 spline stainless steel pump shaft for precision fit, exceptional durability, and efficiency. Double replaceable reverse flow labyrinth type bronze wear ring design will help to minimize end thrust. The impeller will be a twisted vane design to create higher lift.

The pump will include o-ring gaskets throughout the pump.

Deep groove radial type oversize ball bearings will be provided. The bearings will be protected at the openings from road dirt and water with an oil seal and a water slinger.



The pump will have a flat, patterned area on the top of the pump intake wye to allow standing for plumbing maintenance. The main inlet manifold will be 6.00" in diameter and will have a low profile design to facilitate low crosslays and high flows.

For ease of service, the pump housing, intake wye, impeller, mechanical seal, and gear case will be accessible from above the chassis frame by tilting the cab. The intake wyes will be removable without having to remove the main intake casting. Removal of the main inlet wyes will provide access to the impeller, mechanical seal, and wear ring.

The tank to pump line and the primary discharge line will be the only piping required to be removed for overhaul.

For ease of service and overhaul there will be no piping or manifolding located directly over the pump.

### **PUMP MOUNTING**

Pump will be mounted to the chassis frame rails directly below the crew cab, to minimize wheelbase and facilitate service, using rubber isolators in a modified V pattern that include two (2) central mounted isolators located between the frame rails, and one (1) on each side outside the frame rails. The mounting will allow chassis frame rails to flex independently without damage to the fire pump. Each isolator will be 2.55" in total outside diameter and will be rated at 490 lb. The pump will be completely accessible by tilting the cab with no piping located directly above the pump.

### **MECHANICAL SEALS**

Silicon carbide mechanical seals will be provided. The seals will be spring loaded and self-adjusting. The seals will have a minimum thermal conductivity of 126 W/m\*K to run cooler. Seals will have a minimum hardness of 2800 kg/mm<sup>2</sup> to be more resistant to wear, and have thermal expansion characteristics of no more than 4.0 X10<sup>-6</sup>mm/mm\*K to be more resistant to thermal shock.

### **PUMP GEAR CASE**

The pump gear case will be a pressure-lubricated to cool, lubricate, and filter the oil. The gear case will include an auxiliary PTO opening. The gear case will be constructed of lightweight aluminum, and impregnated with resin in accordance to MIL Spec MIL-I-17563. A dipstick, accessible by tilting the cab, will be provided for easy fluid level checks. A filter screen will be provided for long life.

The gear case will consist of two (2) gears to drive the pump impeller and one (1) for the auxiliary PTO.

The auxiliary PTO opening will provide for the addition of PTO driven accessories.

The pump will be driven through the rear engine power take-off and clutch. The rear engine power take-off drive will be live at all times to allow for pump and roll applications. Rear engine power take-off's allow for high horsepower and torque ratings needed for large pump applications, and is a proven drive system throughout the rugged construction industry.

## **CLUTCH**

There will be a heavy-duty electric clutch mounted directly to the front of the pump to engage and disengage the pump without gear clash. The clutch will be a multiple disc design for maximum torque. The clutch will be fully self-adjusting to provide automatic wear compensation, and consistent torque throughout the life of the clutch. Positive engagement and disengagement will be provided through a high efficient and dependable magnetic system to assure superior performance. The clutch will have a 500 lb-ft rating. Clutch will be of a time-tested design used in critical military applications.

## **PUMPING MODE**

Pump will provide for both pump and roll mode and stationary pumping mode.

Stationary pumping mode will be accomplished by stopping the vehicle, setting the parking brake and engaging the water pump switch on the cab switch panel. The transmission will shift to "Neutral" range automatically when the parking brake is set. The "OK to Stationary Pump" indicator will also illuminate when the parking brake is set. If the vehicle is equipped with a foam system or CAFS system, these systems will be engaged from the cab switch panel as well.

Pump and roll mode will be accomplished by the use of the main pump and will not require the use of a secondary pump. Pump and roll mode will use the same operation sequence as stationary pumping mode with a few additional steps. After the vehicle is setup for stationary pumping, the operator will leave the cab and set-up the pump panel to discharge at the desired outlet(s). Upon returning to the cab, the operator will disengage the parking brake. An "OK to Pump & Roll" indicator will illuminate on the cab switch panel. First gear on the transmission gear selector will be selected by the operator for pump and roll operations. The operator as needed will apply the foot throttle. Pump and roll mode will be maintained unless the transmission shifts out of first gear.

Stopping either stationary pumping mode or pump and roll mode will be accomplished by pressing the "Water Pump" switch down to disengage the pump.

## **PUMP SHIFT**

Pump will be engaged in not more than two steps, by simply setting the parking brake, which will automatically put the transmission into neutral, and activating a rocker switch in the cab. Switches in the cab will also allow for water, foam, or CAFS if equipped, and activate the appropriate system to preset parameters. The engagement will provide simple two-step operation, enhance reliability, and completely eliminate gear clash. The shift will include the indicator lights as mandated by NFPA. A direct override switch will be located behind a door in the lower pump operator's panel. The switch will automatically disengage when the door is closed.

As the parking brake is applied, the pump panel throttle will be activated and deactivate the chassis foot throttle for stationary operation.

Pump and roll operation will be available by releasing the parking brake with the pump in the pumping mode. Releasing the parking brake will activate the chassis foot throttle, and deactivate the pump

panel throttle. To protect from accidental pump overheating, the pump will automatically disengage when the truck transmission shifts into second gear.

### **TRANSMISSION LOCK UP**

Transmission lock up is not required as transmission will automatically shift to neutral as soon as the parking brake is set.

### **AUXILIARY COOLING SYSTEM**

A supplementary heat exchange cooling system will be provided to allow the use of water from the discharge side of the pump for cooling the engine water. A water-to-coolant heat exchanger will be used.

### **INTAKE RELIEF VALVE - PUMP**

There will be One (1) Elkhart Style 40 relief valve(s) installed on the suction side of the pump preset at 125 psig.

The relief valve(s) will have a working range of 75 psi to 250 psi.

The outlet will terminate below the frame rails with a 2.50" National Standard hose thread adapter and will have a "do not cap" warning tag.

The relief valve pressure control will be located behind behind the right side pump panel with a stainless steel access door .

### **PRESSURE CONTROLLER**

A Pierce Pressure Governor will be provided. An electric pressure governor will be provided which is capable of automatically maintaining a desired preset discharge pressure in the water pump. When operating in the pressure control mode, the system will automatically maintain the discharge pressure set by the operator (within the discharge capabilities of the pump and water supply) regardless of flow, within the discharge capacities of the water pump and water supply.

A pressure transducer will be installed in the water discharge of the pump. The transducer continuously monitors pump pressure sending a signal to the Electronic Control Module (ECM).

The governor can be used in two (2) modes of operation, RPM mode and pressure modes.

In the RPM mode, the governor can be activated after vehicle parking brake has been set. When in this mode, the governor will maintain the set engine speed, regardless of engine load (within engine operation capabilities).

In the pressure mode, the governor system can only operate after the fire pump has been engaged and the vehicle parking brake has been set. When in the pressure mode, the pressure controller monitors the pump pressure and varies engine speed to maintain a precise pump pressure. The pressure controller will use a quicker reacting J1939 database for engine control.

A preset feature allows a predetermined pressure or rpm to be set.

A pump cavitation protection feature is also provided which will return the engine to idle should the pump cavitate. Cavitation is sensed by the combination of pump pressure below 30 psi and engine speed above 2000 rpm for more than five (5) seconds.

The throttle will be a vernier style control, with a large control knob for use with a gloved hand. A throttle ready light will be provided adjacent to the throttle control. A large 0.75" RPM display will be provided to be visible at a glance.

Check engine, and stop engine indicator lights will be provided for easy viewing.

Large 0.75" push buttons will be provided for menu, mode, preset, and silence selections.

The water tank level indicator will be incorporated in the pressure governor.

A fuel level indicator will be incorporated in the pressure controller.

A pump hour meter will be incorporated in the pressure controller.

The pressure controller will incorporate monitoring for engine temperature, oil pressure, fuel level alarm, and voltage. Pump monitoring will include, pump gearcase temperature, error codes, diagnostic data, pump service reminders, and time stamped data logging, to allow for fast accurate trouble shooting. It will also notify the driver/engineer of any problems with the engine and the apparatus. Complete understandable messages will be provided in a 20-character display, providing for fewer abbreviations in the messages. An automatic dim feature will be included for night operations.

The pressure controller will include a USB port for easy software upgrades, which can be downloaded through a USB memory stick, eliminating the need for a laptop for software installations.

A complete interactive manual will be provided with the pressure controller.

### **PRIMING PUMP**

The priming pump will be a Trident Emergency Products compressed air powered, high efficiency, multistage venturi based AirPrime System, conforming to standards outlined in the current edition of NFPA 1901.

All wetted metallic parts of the priming system are to be of brass and stainless steel construction.

One (1) priming control will open the priming valve and start the pump primer.

### **GARDEN HOSE DIRECT TANK FILL**

There shall be a 0.75" direct tank fill terminating at the on the driver side pump panel pump panel with a female garden hose swivel thread adapter and plug. A 0.75" swing handle valve and plumbing shall be provided.

The direct tank fill shall be plumbed to the water tank dome just above the height of the overflow pipe to eliminate head pressure while in use. A stainless steel elbow shall be installed in the water tank dome, pointing down to prevent water from entering the over flow tube.

## **PUMP MANUALS**

There will be a total of two (2) pump manuals provided by the pump manufacturer and furnished with the apparatus. The manuals will be provided by the pump manufacturer in the form of two (2) electronic copies. Each manual will cover pump operation, maintenance, and parts.

## **PLUMBING, STAINLESS STEEL AND HOSE**

All inlet and outlet lines will be plumbed with either stainless steel pipe, flexible polypropylene tubing or synthetic rubber hose reinforced with hi-tensile polyester braid. All hose's will be equipped with brass or stainless steel couplings. All stainless steel hard plumbing will be a minimum of a schedule 10 wall thickness.

Where vibration or chassis flexing may damage or loosen piping or where a coupling is required for servicing, the piping will be equipped with victaulic or rubber couplings.

Plumbing manifold bodies will be ductile cast iron or stainless steel.

All piping lines are to be drained through a master drain valve or will be equipped with individual drain valves. All drain lines will be extended with a hose to drain below the chassis frame.

All water carrying gauge lines will be of flexible polypropylene tubing.

All piping, hose and fittings will have a minimum of a 500 PSI hydrodynamic pressure rating.

## **FOAM SYSTEM PLUMBING**

All piping that is in contact with the foam concentrate or foam/water solution will be stainless steel. The fittings will be stainless steel or brass. Cast iron pump manifolds will be allowed.

## **MAIN PUMP INLETS**

A 6.00" pump manifold inlet will be provided on each side of the vehicle. The suction inlets will include removable die cast zinc screens that are designed to provide cathodic protection for the pump, thus reducing corrosion in the pump.

Main pump inlets will not be located on the main operator's panel and will maintain a low connection height by terminating below the top of the chassis frame rail.

## **MAIN PUMP INLET CAP**

The main pump inlets will have National Standard Threads with a long handle chrome cap.

The cap will be the Pierce VLH, which incorporates an exclusive thread design to automatically relieve stored pressure in the line when disconnected.

## **INLET BUTTERFLY VALVE**

One (1) Pierce big flow valve will be provided on the left side main pump inlet.

The 6.00" inlet valve will be provided with a built-in, adjustable pressure relief valve and a 3/4" bleeder valve will be provided on the inlet side of the valve.

The valve will be capable of flowing 1950 GPM at 1 PSI pressure drop.

Valve will be electrically operated. An electric actuator, with valve position indicator lights, will be provided at the pump operator's panel.

The electric actuator will be furnished with a manual over ride, extended to the pump panel.

### **VALVES**

All ball valves will be Akron® Brass. The Akron valves will be the 8000 series heavy-duty style with a stainless steel ball and a simple two-seat design. No lubrication or regular maintenance is required on the valve.

Valves will have a **ten (10) year** warranty.

### **LEFT SIDE INLET**

There will be one (1) auxiliary inlet with a 2.50" valve at the left side pump panel, terminating with a 2.50" (F) National Standard hose thread adapter.

The auxiliary inlet will be provided with a strainer, chrome swivel and plug.

### **RIGHT SIDE INLET**

There will be one (1) auxiliary inlet with a 2.50" valve at the right side pump panel, terminating with a 2.50" (F) National Standard hose thread adapter.

The auxiliary inlet will be provided with a strainer, chrome swivel and plug.

The location of the valve for the one (1) inlet will be recessed behind the pump panel.

### **ANODE, INLET**

A pair of sacrificial zinc anodes will be provided in the water pump inlets to protect the pump from corrosion.

### **INLET CONTROL**

The side auxiliary inlet(s) will incorporate a quarter-turn ball valve with the control located at the inlet valve. The valve operating mechanism will indicate the position of the valve.

### **INLET BLEEDER VALVE**

A 0.75" bleeder valve will be provided for each side gated inlet. The valves will be located behind the panel with a swing style handle control extended to the outside of the panel. The handles will be chrome plated and provide a visual indication of valve position. The swing handle will provide an ergonomic position for operating the valve without twisting the wrist and provides excellent leverage. The water discharged by the bleeders will be routed below the chassis frame rails.

### **TANK TO PUMP**

The booster tank will have a 3.00" outlet and be connected to the intake side of the pump with heavy duty 4.00" piping and a quarter turn 3.00" full flow line valve with the control located at the operator's

panel. A rubber coupling will be included in this line to prevent damage from vibration or chassis flexing.

A check valve will be provided in the tank to pump supply line to prevent the possibility of "back filling" the water tank.

### **TANK REFILL**

A 1.50" combination tank refill and pump re-circulation line will be provided, using a quarter-turn full flow ball valve controlled from the pump operator's panel.

### **LEFT SIDE DISCHARGE OUTLETS**

There will be two (2) discharges with a 2.50" valves on the left side of the apparatus, terminating with a 2.50" (M) National Standard hose thread adapter. Discharges will be located below the cab, and will be no higher than the top of the chassis frame rail. Discharges will not be located on the pump operator's panel. Lever controls will be provided at the valve.

### **RIGHT SIDE DISCHARGE OUTLETS**

There will be One (1) discharge outlet with a 2.50" valve on the right side of the apparatus, terminating with a 2.50" MNST adapter. The discharge(s) will be located below the crew cab and will be no higher than the top of the chassis frame rail.

There will be Akron 9335 electric valve controller(s) provided on the pump operators panel. The electric control(s) must be of a true position feedback design, requiring no clutches in the motor or current limiting. The unit(s) must be completely sealed with momentary open, close as well and an optional one touch full open feature to operate the valve actuator. The controller(s) will provide position indication on a full color, backlit LCD display. They will have manual adjustment of the brightness as well as an auto dimming option.

In addition to valve position, each controller will include a pressure display.

### **LARGE DIAMETER DISCHARGE OUTLET**

There will be a 4.00" discharge outlet with a 4.00" valve installed on the right side of the apparatus, terminating with 4.00" MNST threads. The discharge will be located below the crew cab and will be no higher than the top of the chassis frame rail.

There will be an Akron 9335 electric valve controller provided on the pump operators panel. The electric control must be of a true position feedback design, requiring no clutches in the motor or current limiting. The unit must be completely sealed with momentary open, close as well and an optional one touch full open feature to operate the valve actuator. The controller will provide position indication on a full color, backlit LCD display. It will have manual adjustment of the brightness as well as an auto dimming option.

In addition to valve position, the controller will include a pressure display.

### **FRONT DISCHARGE OUTLET**

There will be one (1) 1.50" discharge outlet piped to the front of the apparatus and located on the top of the left side of the front bumper.

Plumbing will consist of 2.00" piping and flexible hose with a 2.00" ball valve with control at the pump operator's panel. A fabricated weldment made of stainless steel pipe will be used in the plumbing where appropriate. The piping will terminate with a 1.50" NST with 90 degree stainless steel swivel.

There will be automatic drains provided at all low points of the piping.

### **DISCHARGE CAPS/ INLET PLUGS**

Chrome plated, rocker lug, caps with chain will be furnished for all discharge outlets 1.00" thru 3.00" in size, besides the pre-connected hose outlets.

Chrome plated, rocker lug, plugs with chain will be furnished for all auxiliary inlets 1.00" thru 3.00" in size.

The caps and plugs will incorporate a thread design to automatically relieve stored pressure in the line when disconnected.

### **OUTLET BLEEDER VALVE**

A 0.75" bleeder valve will be provided for each outlet 1.50" or larger. Automatic drain valves are acceptable with some outlets if deemed appropriate with the application.

The valves will be located behind the panel with a swing style handle control extended to the outside of the side pump panel. The handles will be chrome plated and provide a visual indication of valve position. The swing handle will provide an ergonomic position for operating the valve without twisting the wrist and provides excellent leverage. Bleeders will be located at the bottom of the pump panel. They will be properly labeled identifying the discharge they are plumbed in to. The water discharged by the bleeders will be routed below the chassis frame rails.

### **LARGE DIAMETER OUTLET CAP**

The large diameter outlet will have a National Standard hose thread adapter with a 4.00" rocker lug chrome plated cap and chain.

The cap will be the Pierce VLH, which incorporates a patent pending thread design to automatically relieve stored pressure in the line when disconnected.

### **DISCHARGE OUTLET CONTROLS**

The right side discharges will incorporate a quarter-turn ball valve and be controlled by Akron 9335 electric valve controllers provided on the pump operators panel. The electric controls must be of a true position feedback design, requiring no clutches in the motor or current limiting. The units must be completely sealed with momentary open, close as well and an optional one touch full open feature to operate their corresponding valve actuator. The controllers will provide position indication on a full color, backlit LCD display. They will have manual adjustment of the brightness as well as an auto



dimming option. In addition to the valve controls, the electric valve controllers will include a pressure display

All other outlets will have manual swing handles that operate in a vertical up and down motion. These handles will be able to lock in place to prevent valve creep under pressure.

### **AERIAL OUTLET**

The aerial waterway will be plumbed from the pump to the water tower line with 4.00" pipe and a 4.00" valve. The control for the waterway valve will be located at the pump operator's panel.

An indicator will be provided to show when the valve is in the open or closed position.

### **CROSSLAY MODULE**

The crosslay module will be full width of the rear body.

The crosslay module will include a boom support compartment. The interior of the boom support compartment will be a DA finish.

The forward, upper corners of the module will have full body corners.

The crosslay module will be manufactured for installation of roll up doors on each side to include the boom support compartment with on common roll up door.

### **ROLLUP DOOR, CROSSLAY ENDS**

The compartment doors will be rollup style, double faced aluminum construction painted one (1) color to match the lower portion of the body and manufactured by R-O-M Corporation.

The slats will be double wall box frame extrusion. The exterior surface will be flat and the interior surface will be concave to help loose equipment fall to the ground and prevent it from jamming the door.

Between each slat will be a PVC inner seal to prevent metal to metal contact and prevent dirt or moisture from entering the compartments.

A lift bar with locking key latches to be provided for each roll-up door. The keys to be Model 751 to match all compartment and cab doors. The lift bar will be located at the bottom of the door and have latches on the outer extrusion of the door frame. A ledge will be supplied over the lift bar as additional area to aid in closing the door.

Each door will have a 4.00" counter balance to assist in lifting.

A heavy-duty magnetic switch will be used for the control of open compartment door warning lights.

The crosslays will have a drip pan below the roll of the door.

### **CROSSLAY(S), LOWER**

There will be two (2) lower crosslays provided.

### **1.50" Crosslays**

There will be two (2) 1.50" crosslays plumbed with 2.00" welded or formed schedule 10 304L stainless steel pipe.

The crosslays will be low mounted with the bottom of both crosslay trays no more than 11.00" above the frame rails for simple, safe reloading and deployment.

There will be a 1.50" National Standard hose thread 90-degree swivel provided in each hose bed, so that the hose may be removed from either side of apparatus. The swivel will be as far outbound as possible for ease of changing hose.

Each crosslay will be gated with a 2.00" quarter turn ball valve with the controls located at the pump operator's panel.

Each hose bed will be capable of carrying 200' of 1.75" double jacket hose .

### **Crosslay Hose Trays**

A removable tray will be provided for each crosslay hose bed. The crosslay tray will be constructed of black poly to provide a lightweight sturdy tray. Two (2) hand holes will be in the floor and additional hand holes will be provided in the sides for easy removal and installation from the compartment. The floor of the trays will be perforated to allow for drainage and hose drying.

Trays will be held in place by a mechanical spring-loaded stainless-steel latch that automatically deploys upon loading the trays to hold the trays in place during transit.

### **UPPER DEADLAY HOSE BED**

One (1) dead lay, without plumbing, will be provided in the upper crosslay compartment capable of carrying 400' of 2.5" .

### **Crosslay Hose Trays**

A removable tray will be provided for each crosslay hose bed. The crosslay tray will be constructed of black poly to provide a lightweight sturdy tray. Two (2) hand holes will be in the floor and additional hand holes will be provided in the sides for easy removal and installation from the compartment. The floor of the trays will be perforated to allow for drainage and hose drying.

Trays will be held in place by a mechanical spring-loaded stainless-steel latch that automatically deploys upon loading the trays to hold the trays in place during transit.

### **BOOSTER HOSE REEL**

A Hannay electric rewind booster hose reel will be installed over the pump in a recessed open compartment on the right side of the apparatus. The reel will be fabricated of aluminum and have highly polished end discs.

A polished stainless steel roller and guide assembly will be mounted on the reel side of the apparatus.

Discharge control will be provided at the pump operator's panel. Plumbing to the reel will consist of 1.50" Aeroquip hose and a 1.50" valve.

Reel motor will be protected from overload with a circuit breaker rated to match the motor.

An electric rewind control switch will be installed on the reel side pump panel.

Booster hose, 1.00" diameter and 150 feet, with chrome plated Barway, or equal couplings will be provided.

Working pressure of the booster hose will be a minimum of 800 psi.

Capacity of the hose reel will be 150 feet of 1.00" booster hose.

### **HUSKY 3 FOAM PROPORTIONER**

A Pierce Husky® 3 foam proportioning system will be provided. The Husky 3 is an on demand, automatic proportioning, single point, direct injection system suitable for all types of Class A and B foam concentrates, including the high viscosity (6000 cps), alcohol resistant Class B foams. Operation will be based on direct measurement of water flow, and remain consistent within the specified flows and pressures. The system will automatically proportion foam solution at rates from 0.1 percent to 3 percent regardless of variations in water pressure and flow, up to the maximum rated capacity of the foam concentrate pump.

The design of the system will allow operation from draft, hydrant, or relay operation.

### **System Capacity**

The system will have the ability to deliver the following minimum foam solution flow rates at accuracies that meet or exceed NFPA requirements at a pump rating of 150 psi.

100 gpm @ 3 percent

300 gpm @ 1 percent

600 gpm @ 0.5 percent

Class A foam setting in 0.1 percent increments from 0.1 percent to 1 percent. Typical settings of 1 percent, 0.5 percent and 0.3 percent (maximum capacity will be limited to the plumbing and water pump capacity).

### **Control System**

The system will be equipped with a digital electronic control display located on the pump operators panel. Push button controls will be integrated into the panel to turn the system on/off, control the foam percentage, and to set the operation modes.

The percent of injection will have a preset. This preset can be changed at the fire department as desired. The percent of injection will be able to be easily changed at the scene to adjust to changing demands.

Three (3) 0.50" high LEDs will display the foam percentage in numeric characters. Three (3) indicator LEDs will also be included: one (1) green, one (1) red, and one (1) yellow. The LEDs will indicate various system operation or error states.

The indications will be:

- Solid Green - System On
- Solid Red - Valve Position Error
- Solid Yellow - Priming System
- Flashing Green - Injecting Foam
- Flashing Red - Low Tank Level
- Flashing Yellow - Refilling Tank

The control display will house a microprocessor, which receives input from the systems water flow meter while also monitoring the position of the foam concentrate pump. The microprocessor will compare the values of the water flow versus the position/rate of the foam pump, to ensure the proportion rate is accurate. One (1) check valve will be installed in the plumbing to prevent foam from contaminating the water pump.

### **Hydraulic Drive System**

The foam concentrate pump will be powered by an electric over hydraulic drive system. The hydraulic system and motor will be integrated into one unit.

### **Foam Concentrate Pump**

The foam concentrate pump will be of positive displacement, self-priming; linear actuated design, driven by the hydraulic system. The pump will be constructed of brass body; chrome plated stainless steel shaft, with a stainless steel piston. In order to increase longevity of the pump, no aluminum will be present in its construction.

A relief system will be provided which is designed to protect the drive system components and prevent over pressuring the foam concentrate pump.

The foam concentrate pump will have minimum capacity for 3 gpm with all types of foam concentrates with a viscosity at or below 6000 cps including protein, fluoroprotein, AFFF, FFFP, or AR-AFFF. The system will deliver only the amount of foam concentrate flow required, without recirculating foam back to the storage tank. Recirculating foam concentrate back to the storage tank can cause agitation and premature foaming of the concentrate, which can result in system failure. The foam concentrate pump will be self-priming and have the ability to draw foam concentrate from external supplies such as drums or pails.

### **External Foam Concentrate Connection**

An external foam pick-up will be provided to enable use of a foam agent that is not stored on the vehicle. The external foam pick-up will be designed to allow continued operation after the on-board foam tank is empty, or the use of foam different than the foam in the foam tank.

### **Panel Mounted External Pick-Up Connection / Valve**

A bronze three (3)-way valve will be provided. The unit will be mounted to the pump panel. The valve unit will function as the foam system tank to pump valve and external suction valve. The external foam pick-up will be one (1) 0.75" male connection GHT (garden hose thread) with a cap.

### **Pick-Up Hose**

A 0.75" flexible hose with an end for insertion into foam containers will be provided. The hose will be supplied with a 0.75" female swivel GHT (garden hose thread) swivel connector. The hose will be shipped loose.

### **Discharges**

The foam system will be plumbed to the lower rear crosslay, lower front crosslay, left side of front bumper and hose reel in right side of dunnage area.

### **System Electrical Load**

The maximum current draw of the electric motor and system will be no more than 55 amperes at 12 VDC.

### **SINGLE FOAM TANK REFILL**

The foam system's proportioning pump will be used to fill the foam tank. This will allow use of the auxiliary foam pick-up to pump the foam from pails or a drum on the ground into the foam tank. A foam shut-off switch will be installed in the fill dome of the tank to shut the system down when the tank is full. The fill operation will be controlled by a mode in the foam system controller. While the proportioner pump is filling the tank, the controller will display a flashing yellow LED to indicate that the tank is filling. When the tank is full, as determined by the float switch in the tank dome, the pump will stop and the controller will shut the yellow LED off. If it attempted to use tank fill and the refill valve and suction valve are in the wrong position(s), then a red LED will illuminate to indicate the improper valve position(s). When the valves are positioned properly, then filling will commence.

### **FOAM TANK**

The foam tank will be an integral portion of the polypropylene water tank. The cell will have a capacity of 40 gallons of foam with the intended use of Class A foam. The brand of foam stored in this tank will be to be determined. The foam cell will not reduce the capacity of the water tank. The foam cell will have a screen in the fill dome and a breather in the lid.

### **FOAM TANK DRAIN**

The foam tank drain will be a 1.00" quarter turn drain valve located inside the pump/plumbing compartment.

### **PUC MODULE**

The pump module will be separate from the hose body and compartments so that each may flex independently of the other. It will be a fabricated assembly of aluminum tubing, angles and channels which supports both the plumbing and the side running boards.

The pump module will be mounted on the chassis frame rails with standard body angles in four places to allow for chassis frame twist.

Pump module, plumbing and gauge panels will be removable from the chassis in a single assembly.

### **PUMP CONTROL PANELS (LEFT SIDE CONTROL)**

Pump controls and gauges will be located midship at the left side of the apparatus and properly identified.

The main pump operator's control panel will be completely enclosed and located in the forward section of the body compartment. There will be a roll up door to protect against road debris and weather elements. This roll-up door compartment will include a drip pan below the roll of the door. The pump operator's panels will be no more than 31.00" wide, and made in four (4) sections with the center section easily removable with simple hand tools. For the safety of the pump operator, there will be no discharge outlets or pump inlets located on the main pump operators panel.

Layout of the pump control panel will be ergonomically efficient and systematically organized. The upper section will contain the master gauges. This section will be angled down for easy visibility. The center section will contain the pump controls aligned in two horizontal rows. The pressure control device, engine monitoring gauges, electrical switches, and foam controls (if applicable) will be located on or adjacent to the center panel, on the side walls for easy operation and visibility. The lower section will contain the outlet drains.

Manual controls will be easy moving 8" long lever style controls that operate in a vertical, up and down swing motion. These handles will have a 2.25" diameter knob and be able to lock in place to prevent valve creep under any pressure. Bright finish bezels will encompass the opening, be securely mounted to the pump operator's panel, and will incorporate the discharge gauge bezel. Bezels will be bolted to the panel for easy removal and gauge service. The driver's side discharges will be controlled directly at the valve. There will be no push-pull style control handles.

Identification tags for the discharge controls will be recessed within the same bezel. The discharge identification tags will be color coded, with each discharge having its own unique color.

All remaining identification tags will be mounted on the pump panel in chrome-plated bezels.

All discharge outlets will be color coded and labeled to correspond with the discharge identification tag.

The pump panels for the discharge and intake ports will be located ahead of the pump module with no side discharge or intake higher than the frame rail. The pump panels will be easily removable with simple hand tools.

A recessed cargo area will be provided at the front of the body, ahead of the water tank above the plumbing.

### **PASSENGER SIDE PUC MODULE COMPARTMENT**

A full height compartment with a roll-up door ahead of the front stabilizer will be provided, as convenient large storage compartment for often used items for the crew. The interior dimensions of this compartment will be 30.25" wide x 52.00" high x 25.13" deep. The depth of the compartment will be calculated with the compartment door closed. The compartment interior will be fully open from the compartment ceiling to the compartment floor and designed so that no permanent dividers are required between the upper and lower sections. The clear door opening of this compartment will be 28.00" wide x 52.00 high.

Closing of the door will not require releasing, unlocking, or unlatching any mechanism and will easily be accomplished with one hand.

This roll-up door compartment will include a drip pan below the roll of the door.

The following drawing(s) will be provided for approval by the customer. The drawing(s) will be made for up One (01) Truck apparatus and/or similar Pierce job number.

### **PUMP OPERATOR'S PANEL DRAWING**

A detailed drawing to scale of the pump operator's panel will be provided for the customer to review. The drawing will include all of the gauges, controls, switching, etc., located on the pump operator's panel. The customer will be allowed to make changes and/or mark-ups to this approval drawing. The fire apparatus manufacturer will make revisions (If needed) to the drawing per the customer changes and/or mark-ups as long as the changes are physically possible within a specific product line.

The finalized and signed customer approved pump operator's panel drawing will become part of the contract documents.

Due to the way drain(s), bleeder(s), operational/maintenance tag(s) and NFPA required warning tag(s) are placed on pump panel(s), these items will NOT be shown on any pump panel approval drawing(s). These item(s) will be placed on pump panel(s) at the fire apparatus manufacturer discretion.

### **REMAINING PUMP PANEL(S)**

Detailed drawing(s) to scale of the remaining pump panel(s) will be provided for the customer to review. The drawing(s) will include all of the gauges, controls, switching, etc., located on the pump panel(s). The customer will be allowed to make changes and/or mark-ups to these approval drawing(s). The fire apparatus manufacturer will make revisions (If needed) to the drawing(s) per the customer changes and/or mark-ups as long as the changes are physically possible within a specific product line.

The finalized and signed customer approved pump panel drawing(s) will become part of the contract documents.

Due to the way drain(s), bleeder(s), operational/maintenance tag(s) and NFPA required warning tag(s) are placed on pump panel(s), these items will NOT be shown on any pump panel approval drawing(s). These item(s) will be placed on pump panel(s) at the fire apparatus manufacturer discretion.

### **COLOR CODED TAGS**

A detailed drawing/chart of the colors used on all of the inlet(s) and outlet(s) will be provided for the customer to review. The customer will be allowed to make changes and/or mark-ups to this approval drawing/chart. The fire apparatus manufacturer will make revisions (If needed) to the drawing per the customer changes and/or mark-ups as long as the changes are physically possible within a specific product line.

The finalized and signed customer approved drawing/chart of the colors will become part of the contract documents.

### **SPECIAL TEXT/VERBIAGE TAGS**

A detailed drawing/chart of the text/verbiage used on all of the inlet(s) and outlet(s) will be provided for the customer to review. The customer will be allowed to make changes and/or mark-ups to this approval drawing/chart. The fire apparatus manufacturer will make revisions (If needed) to the drawing per the customer changes and/or mark-ups as long as the changes are physically possible within a specific product line.

The finalized and signed customer approved drawing/chart of the text/verbiage will become part of the contract documents.

### **PUMP PANEL CONFIGURATION**

The pump panel configuration will be arranged and installed in an organized manner that will provide user-friendly operation.

### **PUMP OPERATOR'S PLATFORM**

A pull out, flip down platform will be provided at the pump operator's control panel.

The front edge and the top surface of the platform will be made of DA finished aluminum with a Morton Cass insert.

The platform will be approximately 13.75" deep when in the stowed position and approximately 22.00" deep when extended. The platform will be as wide as possible. The platform will lock in the retracted and the extended position.

The platform will be wired to the "step not stowed" indicator in the cab.

### **PUMP OPERATOR'S PLATFORM PERIMETER LIGHT**

There will be an On Scene Solutions, Model Night Stick Access, 20.00" white 12 volt DC LED strip light provided to illuminate the ground area.

### **PUMP AND GAUGE PANEL**

The pump operator's panel and gauge panels will be constructed of stainless steel with a brushed finish.

The side control panels will be constructed of stainless steel with a brushed finish for durability and ease of maintenance.



### **PUMP AND PLUMBING ACCESS**

Simple access to the plumbing will be provided through the front of the body area by raising the cab for complete plumbing service and valve maintenance. Access to valves will not require removal of operator panels or pump panels. Access for rebuilding of the pump will not require removal of more than the tank to pump line and a single discharge line. This access will allow for fast, easy valve or pump rebuilding, making for reduced out of service times. Steps will be provided for access to the top of the pump.

Access to the pump will be provided by raising the cab. The pump will be positioned such that all maintenance and overhaul work can be performed above the frame and under the tilted cab. The service and overhaul work on the pump will not require the removal of operator panels or pump panels. Complete pump casing and gear case removal will require no more than removal of the intake and discharge manifolds, driveline, coolers and a single discharge line. The pump case and gear case will be able to be removed by lifting upward without interference from piping and be removable in less than 3 hours.

### **PUMP COMPARTMENT LIGHT**

There will be one (1) Whelen®, Model 3SC0CDCR, 3.00" white 12 volt DC LED light(s) with Whelen, Model 3FLANGEC, flange(s) installed in the plumbing area.

The light(s) will be activated by a toggle switch located in the pump compartment area.

Engine monitoring graduated LED indicators will be incorporated with the pressure controller.

### **THROTTLE READY GREEN INDICATOR LIGHT**

There will be a green indicator light integrated with the pressure governor and/or engine throttle installed on the pump operators panel that is activated when the pump is in throttle ready mode.

### **VACUUM AND PRESSURE GAUGES**

The pump vacuum and pressure gauges will be liquid filled and manufactured by Class 1 Incorporated ©.

The gauges will be a minimum of 4.00" in diameter and will have white faces with black lettering, with a pressure range of 30.00"-0-600#.

Gauge construction will include a Zytel nylon case with adhesive mounting gasket and threaded retaining nut.

The pump pressure and vacuum gauges will be installed adjacent to each other at the pump operator's control panel.

Test port connections will be provided at the pump operator's panel. One will be connected to the intake side of the pump, and the other to the discharge manifold of the pump. They will have 0.25 in. standard pipe thread connections and non-corrosive polished stainless steel or brass plugs. They will be marked with a label.

This gauge will include a 10 year warranty against leakage, pointer defect, and defective bourdon tube.

### **PRESSURE GAUGES**

The individual "line" pressure gauges for the discharges will be Class 1© interlube filled.

They will be a minimum of 2.00" in diameter and have white faces with black lettering.

Gauge construction will include a Zytel nylon case with adhesive mounting gasket and threaded retaining nut.

Gauges will have a pressure range of 30"-0-400#.

The individual pressure gauge will be installed as close to the outlet control as practical.

This gauge will include a 10 year warranty against leakage, pointer defect, and defective bourdon tube.

### **WATER LEVEL GAUGE**

A Fire Research TankVision Pro model WLA300-A00 water tank indicator gauge will be installed on the pump operators panel. The gauge kit will include an electronic indicator module, a pressure sensor, and a 10' sensor cable. The gauge will show the volume of water in the tank on nine (9) easy to see super bright RGB LEDs. A wide view lens over the LEDs will provide for a viewing angle of 180 degrees. The gauge case will be waterproof, manufactured of Polycarbonate/Nylon material, and have a distinctive blue label.

The program features will be accessed from the front of the indicator module. The program will support self-diagnostics capabilities, self-calibration, six (6) programmable colored light patterns to display tank volume, adjustable brightness control levels and a data link to connect remote indicators. Low water warnings will include flashing LEDs at 1/4 tank and down chasing LEDs when the tank is almost empty.

The gauge will receive an input signal from an electronic pressure sensor. The sensor will be mounted from the outside of the water tank near the bottom. No probe will be placed on the interior of the tank. Wiring will be weather resistant and have automotive type plug-in connectors.

### **ADDITIONAL WATER LEVEL GAUGE**

There will be two (2) additional Fire Research MaxVision model WLA280-A00 water tank remote indicators provided and installed behind the crew cab doors. The indicators will show the volume of water in the tank on Ninety six (96) easy to see super bright Tri-color LEDs. The indicator case will be waterproof, manufactured of Polycarbonate material with an integrated lens.

The remote indicator will indicate the level as a single color in Red for 25% or less, Amber color for up to 50% volume, Blue color for up to 75% volume and Green color for up to 100% volume. When the level reaches 25%, the red LEDs will begin flashing. When the level is empty, the red LEDs will scroll in a down-chasing motion and then flash three times.

The flash rate will be determined by the main water tank sensor.

It will have the program capability to adjust the brightness level for day time and night time viewing. The LEDs can also be programmed for different colors.

This module will be activated when the pump is in gear.

### **FOAM LEVEL GAUGE**

A Pierce electric foam level gauge will be provided on the operator's panel, that registers foam level by means of nine (9) LEDs. There will also be a mini foam level gauge with five (5) LEDs in the cab. They will be at 1/8 level increments with a tank empty LED. The LEDs will be a bright type that is readable in sunlight, and have a full 180 degree of clear viewing. The gauge will match the water level gauge in the pressure controller.

To further alert the pump operator, will have a warning flash when the tank volume is less than 25 percent, and will have Down Chasing LEDs when the tank is almost empty.

The level measurement will be ascertained by sensing the head pressure of the fluid in the tank or cell. This method provides accuracy with an array of multi-viscosity foams.

The foam level gauge in the cab will be activated by pump is in gear.

### **SIDE CONTROL PUMP OPERATOR'S/PUMP PANEL LIGHTING**

Illumination will be provided for controls, switches, essential instructions, gauges, and instruments necessary for the operation of the apparatus and the equipment provided on it. External illumination will be a minimum of five (5) foot-candles on the face of the device. Internal illumination will be a minimum of four (4) footlamberts.

The pump panels will be illuminated by two (2) Truck-Lite, Model 60354C, 6.00" x 2.00" oval white LED lights with Model 60700, grommets and chrome covers installed on the back of the cab, one (1) on the driver's side and one (1) on the passenger's side.

The pump operator's panel will utilize the same LED strip lighting at the forward doorframe as all other compartment lighting.

There will be a small white LED pump engaged indicator light installed overhead.

### **AIR HORN SYSTEM**

There will be two (2) Grover air horns recessed in the front bumper. The horn system will be piped to the air brake system wet tank utilizing 0.38" tubing. A pressure protection valve will be installed in-line to prevent loss of air in the air brake system.

#### **Air Horn Location**

The air horns will be located on each side of the bumper, towards the outside.

#### **Air Horn Control**

The air horns will be actuated by a chrome push button located on the officer's side of the engine tunnel and by the horn button in the steering wheel. The driver will have the option to control the air

horns or the chassis horns from the horn button by means of a selector switch located on the instrument panel.

### **ELECTRONIC SIREN**

There will be a Whelen®, Carbide™, Model CCSRNT4A electronic siren amplifier mounted tbd and Model CANCTL6 (same layout and features as the CCSRN36) remote head installed tbd.

The control head will control the rear traffic directing light.

Slide1, Slide2 and Slide3 will all turn on "WAIL" and activate the horn relay output. (Each slide switch position will have the same function, only siren on and siren off is required.)

Inputs;

- Input #1 TA Flash
- Input #2 Open
- Input #3 Open
- Input #4 Foot switch input (Horn Ring by default)

Electronic siren head will be recessed in the driver side center switch panel.

The electronic siren will be controlled on the siren head only. No horn button or foot switches will be provided.

### **SPEAKER**

There will be one (1) Whelen®, Model SA315P, black nylon composite, 100-watt, speaker with through bumper mounting brackets and polished stainless steel grille provided. The speaker will be connected to the siren amplifier.

The speaker(s) will be recessed in the center of the front bumper.

### **AUXILIARY MECHANICAL SIREN**

A Federal Q2B® siren will be furnished.

The control solenoid will be powered up after the emergency master switch is activated.

The mechanical siren will be recessed in the front bumper on the right side. The siren will be properly supported using the bumper framework.

The mechanical siren will be actuated by two (2) foot switches, one (1) located on the officer's side and one (1) on the driver's side.

A momentary chrome push button switch will be included in the right side dash panel to activate the siren brake.

### **FRONT ZONE UPPER WARNING LIGHTS**

There will be two (2) 21.50" Whelen Freedom IV LED lightbars mounted on the cab roof, one (1) on each side, above the driver's and passenger's door, facing forward.

The driver's side lightbar will include the following:

- One (1) red flashing LED module in the outside end position.
- One (1) red flashing LED module in the outside front corner position.
- One (1) red flashing LED module in the outside front position.
- One (1) red flashing LED module in the inside front position.
- One (1) red flashing LED module in the inside front corner position.

The passenger's side lightbar will include the following:

- One (1) red flashing LED module in the inside front corner position.
- One (1) red flashing LED module in the inside front position.
- One (1) red flashing LED module in the outside front position.
- One (1) red flashing LED module in the outside front corner position.
- One (1) red flashing LED module in the outside end position.

There will be clear lenses included on the lightbar.

There will be a switch in the cab on the switch panel to control the lightbars.

### **FRONT ZONE UPPER LIGHTING, PLATFORM**

Two (2) Whelen model M6R, red flashing LED lights will be located at the front of the platform basket facing forward. The color of the lenses will be the same color as the LED's.

These lights are required to meet or exceed the NFPA Front upper zone optical warning light requirements.

These lights will be deactivated when the ladder is lifted from the stowed position.

The lights will be controlled by the same switch as the lightbars. The switch will be provided on the cab instrument panel.

The lights will be located on each forward facing basket door and be provided with with a flange.

### **TRAFFIC LIGHT CONTROLLER**

There will be a GTT, Model 794\* LED Opticom traffic light controller with national standard high priority remote mounted on the front edge of the platform basket, on the platform basket.

The Opticom traffic light controller will be activated by a cab switch with emergency master control.

The Opticom traffic light controller will have no momentary activation switch.

The Opticom traffic light controller will be disabled when the parking brake is applied.

## **SIDE WARNING LIGHTS**

There will be two (2) 21.50" Whelen Freedom IV LED lightbars mounted on the roof, one (1) on each side, over the side crew cab windows.

Each lightbar will include the following:

- One (1) red flashing LED module in the outside rear corner position.
- One (1) red flashing LED module in the rear outside position.
- One (1) red flashing LED module in the front outside position.
- One (1) red flashing LED module in the outside front corner position.

There will be clear lenses included on the lightbar.

There will be a switch in the cab on the switch panel to control the lightbars.

These lights may be load managed when the parking brake is applied.

## **CAB FACE WARNING LIGHTS**

There will be four (4) Whelen®, Model M6\*C, LED flashing warning lights installed on the cab face, above the headlights, mounted in a common bezel.

- The driver's side front outside warning light to be red
- The driver's side front inside warning light to be red
- The passenger's side front inside warning light to be red
- The passenger's side front outside warning light to be red

All four (4) lights will include a clear lens.

There will be a switch located in the cab, on the switch panel, to control the four (4) lights.

The inside lights may be load managed if colored or disabled if white, when the parking brake is set.

## **HEADLIGHT FLASHER**

The high beam headlights will flash alternately between the left and right side.

There will be a switch installed in the cab on the switch panel to control the high beam flash. This switch will be live when the battery switch and the emergency master switches are on.

The flashing will automatically cancel when the hi-beam headlight switch is activated or when the parking brake is set.

## **SIDE ZONE LOWER LIGHTING**

There will be six (6) Whelen®, 4.32" high x 6.75" long LED lights with Model M6FC, chrome flanges installed per the following:

- Two (2) Model M6\*\*, flashing warning lights, one (1) each side on the front cab corner. The side front lights to be red.

- Two (2) Model M6\*\*, flashing warning lights, behind the crew cab door. The side middle lights to be red.
- Two (2) Model M6V2\*, flashing warning lights with lower scene LEDs, above the rear axles. The side rear lights to be red.

The warning light lens color(s) to be clear.

There will be a switch in the cab on the switch panel to control the warning lights.

The scene lights will be activated by a switch at the driver's side switch panel.

#### **INTERIOR CAB DOOR WARNING LIGHTS**

There will be four (4) Weldon, Model 8401-0000-20, amber 12 volt DC LED flashing strip lights provided.

- One (1) light on the driver's side cab door over the window.
- One (1) light on the passenger's side cab door over the window.
- One (1) light on the passenger's side crew cab door over the window.
- One (1) light on the driver's side crew cab door over the window.

Each light will be activated when the battery switch is on and the adjacent door is opened.

Each light will be installed so the flash pattern directs traffic away from the doors.

#### **INTERIOR CAB DOOR WARNING LIGHTS**

There will be four (4) Whelen, Model M2\*, LED flashing warning lights with Whelen, Model M2FC, chrome flange provided, one (1) on each cab and crew cab door pan.

The color will be red.

Each light will include a lens color that is clear.

Each light will be activated by the door jam switch of the associated door.

#### **SIDE WARNING LIGHTS**

There will be two (2) Whelen, Model M6\* LED flashing warning light(s) with bezel(s) provided on each side of the basket, in the lower rear corner.

The color of the lights will be red.

All of these lights will include a lens color that is the same as the LED's

These lights will be activated with the Side Zone Lower warning lights.

#### **REAR ZONE LOWER LIGHTING**

There will be two (2) Whelen®, Model M6\*C LED flashing warning lights with chrome trim located at the rear of the apparatus.

- The driver's side rear light to be red
- The passenger's side rear light to be red

The lenses will be clear.

There will be a switch located in the cab on the switch panel to control the lights.

### **WARNING LIGHTS (REAR)**

There will be two (2) Whelen®, Model M6# split color LED flashing warning light(s) with chrome trim provided below the rear upper warning.

The rear light to be amber to the outside and red to the inside.

These light(s) will be controlled with the rear upper warning switch.

These light(s) will include a lens that is clear.

### **WARNING LIGHTS (REAR OF HOSE BED)**

There will be two (2) Whelen, Model MCFLED2\* LED warning lights provided at the rear of the truck, located one (1) each side.

- One (1) of these lights will be all red LED with clear lenses.
- One (1) of these lights will be all amber LED with clear lenses.

The location of the lights will be on the upper rear corners of the body

There will be one (1) switch located in the cab on the switch panel to control the lights.

### **TRAFFIC DIRECTING LIGHT**

There will be one (1) Whelen, Model TAM65, 36.00" long x 2.84" high x 2.24" deep, amber LED traffic directing light installed at the rear of the apparatus.

This traffic directing light will be mounted on top of the body below the turntable with a treadplate box at the rear of the apparatus.

The traffic directing light will be controlled by the electronic siren control head.

### **ELECTRICAL SYSTEM GENERAL DESIGN FOR ALTERNATING CURRENT**

The following guidelines will apply to the 120/240 VAC system installation:

#### **General**

Any fixed line voltage power source producing alternating current (ac) line voltage will produce electric power at 60 cycles plus or minus 3 cycles.

Except where superseded by the requirements of NFPA 1901, all components, equipment and installation procedures will conform to NFPA 70, National Electrical Code (herein referred to as the NEC).



Line voltage electrical system equipment and materials included on the apparatus will be listed and installed in accordance with the manufacturer's instructions. All products will be used only in the manner for which they have been listed.

### **Grounding**

Grounding will be in accordance with Section 250-6 "Portable and Vehicle Mounted Generators" of the NEC. Ungrounded systems will not be used. Only stranded or braided copper conductors will be used for grounding and bonding.

An equipment grounding means will be provided in accordance with Section 250-91 (Grounding Conductor Material) of the NEC.

The grounded current carrying conductor (neutral) will be insulated from the equipment grounding conductors and from the equipment enclosures and other grounded parts. The neutral conductor will be colored white or gray in accordance with Section 200-6 (Means of Identifying Grounding Conductors) of the NEC.

In addition to the bonding required for the low voltage return current, each body and driving or crew compartment enclosure will be bonded to the vehicle frame by a copper conductor. This conductor will have a minimum amperage rating of 115 percent of the nameplate current rating of the power source specification label as defined in Section 310-15 (amp capacities) of the NEC. A single conductor properly sized to meet the low voltage and line voltage requirements will be permitted to be used.

All power source system mechanical and electrical components will be sized to support the continuous duty nameplate rating of the power source.

### **Operation**

Instructions that provide the operator with the essential power source operating instructions, including the power-up and power-down sequence, will be permanently attached to the apparatus at any point where such operations can take place.

Provisions will be made for quickly and easily placing the power source into operation. The control will be marked to indicate when it is correctly positioned for power source operation. Any control device used in the drive train will be equipped with a means to prevent the unintentional movement of the control device from its set position.

A power source specification label will be permanently attached to the apparatus near the operator's control station. The label will provide the operator with the following information:

- Rated voltage(s) and type (ac or dc)
- Phase
- Rated frequency
- Rated amperage
- Continuous rated watts
- Power source engine speed

Direct drive (PTO) and portable generator installations will comply with Article 445 (Generators) of the NEC.

### **Overcurrent protection**

The conductors used in the power supply assembly between the output terminals of the power source and the main over current protection device will not exceed 144.00" (3658 mm) in length.

For fixed power supplies, all conductors in the power supply assembly will be type THHW, THW, or use stranded conductors enclosed in nonmetallic liquid tight flexible conduit rated for a minimum of 194 degree Fahrenheit (90 degrees Celsius).

For portable power supplies, conductors located between the power source and the line side of the main overcurrent protection device will be type SO or type SEO with suffix WA flexible cord rated for 600-volts at 194 degrees Fahrenheit (90 degrees Celsius).

### **Wiring Methods**

Fixed wiring systems will be limited to the following:

- Metallic or nonmetallic liquid tight flexible conduit rated at not less than 194 degrees Fahrenheit (90 degrees Celsius)
- or
- Type SO or Type SEO cord with a WA suffix, rated at 600 volts at not less than 194 degrees Fahrenheit (90 degrees Celsius)

Electrical cord or conduit will not be attached to chassis suspension components, water or fuel lines, air or air brake lines, fire pump piping, hydraulic lines, exhaust system components, or low voltage wiring. In addition the wiring will be run as follows.

- Separated by a minimum of 12.00" (305 mm), or properly shielded, from exhaust piping
- Separated from fuel lines by a minimum of 6.00" (152 mm) distance

Electrical cord or conduit will be supported within 6.00" (152 mm) of any junction box and at a minimum of every 24.00" (610 mm) of continuous run. Supports will be made of nonmetallic materials or corrosion protected metal. All supports will be of a design that does not cut or abrade the conduit or cable and will be mechanically fastened to the vehicle.

### **Wiring Identification**

All line voltage conductors located in the main panel board will be individually and permanently identified. The identification will reference the wiring schematic or indicate the final termination point. When prewiring for future power sources or devices, the unterminated ends will be labeled showing function and wire size.

### **Wet Locations**

All wet location receptacle outlets and inlet devices, including those on hardwired remote power distribution boxes, will be of the grounding type provided with a wet location cover and installed in accordance with Section 210-7 "Receptacles and Cord Connections" of the NEC.

All receptacles located in a wet location will be not less than 24.00" (610 mm) from the ground. Receptacles on off-road vehicles will be a minimum of 30.00" (762 mm) from the ground.

The face of any wet location receptacle will be installed in a plane from vertical to not more than 45 degrees off vertical. No receptacle will be installed in a face up position.

### **Dry Locations**

All receptacles located in a dry location will be of the grounding type. Receptacles will be not less than 30.00" (762 mm) above the interior floor height.

All receptacles will be marked with the type of line voltage (120-volts or 240-volts) and the current rating in amps. If the receptacles are direct current, or other than single phase, they will be so marked.

### **Listing**

All receptacles and electrical inlet devices will be listed to UL 498, Standard for Safety Attachment Plugs and Receptacles, or other appropriate performance standards. Receptacles used for direct current voltages will be rated for the appropriate service.

### **Electrical System Testing**

The wiring and associated equipment will be tested by the apparatus manufacturer or the installer of the line voltage system.

The wiring and permanently connected devices and equipment will be subjected to a dielectric voltage withstand test of 900-volts for one (1) minute. The test will be conducted between live parts and the neutral conductor, and between live parts and the vehicle frame with any switches in the circuit(s) closed. This test will be conducted after all body work has been completed.

Electrical polarity verification will be made of all permanently wired equipment and receptacles to determine that connections have been properly made.

### **Operational Test per Current NFPA 1901 Standard**

The apparatus manufacturer will perform the following operation test and ensure that the power source and any devices that are attached to the line voltage electrical system are properly connected and in working order. The test will be witnessed and the results certified by an independent third-party certification organization.

The prime mover will be started from a cold start condition and the line voltage electrical system loaded to 100 percent of the nameplate rating.

The power source will be operated at 100 percent of its nameplate voltage for a minimum of two (2) hours unless the system meets category certification as defined in the current NFPA 1901 standard.

Where the line voltage power is derived from the vehicle's low voltage system, the minimum continuous electrical load as defined in the current NFPA 1901 standard will be applied to the low voltage electrical system during the operational test.

## **GENERATOR**

The apparatus will be equipped with a complete AC (alternating current) electrical power system. The generator will be a Harrison, Model MSV, 6,000 watt hydraulic driven unit with vertical exhaust.

The generator will be driven by a transmission power take off unit, through a hydraulic pump and motor.

The hydraulic engagement supply will be operational at any time (no interlocks).

An electric/hydraulic valve will supply hydraulic fluid to the clutch engagement unit provided on the chassis PTO drive.

## **Generator Instruments and Controls**

To properly monitor the generator performance, a voltmeter will be furnished near the breaker box.

## **GENERATOR LOCATION**

The generator will be mounted in the cargo area at the front of the body in in best location. The flooring in this area will be either reinforced or constructed, in such a manner, that it will handle the additional weight of the generator.

## **GENERATOR START**

There will be a switch provided on the cab instrument panel to engage the generator.

## **CIRCUIT BREAKER PANEL**

The circuit breaker panel will be located in the compartment above the left side front stabilizer.

## **SUB FEED CIRCUIT BREAKER PANEL**

There will be a shoreline to generator transfer switch powered sub feed circuit breaker panel installed in the to be determined. A directory for each breaker will be provided adjacent to the circuit breaker panel. Identification of circuits will be done in a durable manner that provides years of service.

## **ELECTRIC CORD REEL**

Furnished with the AC electrical system will be a Hannay, Series 1600, cord reel wired for a four (4) conductor cord. The reel will be provided with a 12-volt electric rewind switch that is guarded to prevent accidental operation and labeled for its intended use. The push button switch will be protected with a fuse and installed at a height not to exceed 72.00" above the operators standing position.

The exterior finish of the reel(s) will be painted #269 gray from the reel manufacturer.

A captive roller assembly to be provided to aid in the payout and loading of the reel. A ball stop will be provided to prevent the cord from being wound on the reel.

A label will be provided in a readily visible location adjacent to the reel. The label will indicate current rating, current type, phase, voltage and total cable length.

A total of two (2) cord reels will be provided one (1) reel in the driver's side front compartment over the driver's side front stabilizer and one (1) reel in the passenger's side front compartment over the passenger's side front stabilizer.

### **CORD**

Provided for electric distribution will be two (2) lengths, one (1) for each reel, of 175 feet of Carol Super Vu-Tron II yellow 12/4 electrical cord. No connector will be installed on the end of the cord.

### **PORTABLE JUNCTION BOX**

There will be two (2) Akron EJBX electric junction box(es) provided.

There will be a cable strain relief and direct connection, no plug provided for each box.

Each box will be provided with the following:

- four (4) 20 amp 120 volt AC twist lock receptacles with flip up covers
- a 120 volt AC light inside the box

### **120 VOLT RECEPTACLE**

There will be two (2), 15/20 amp 120 volt AC three (3) wire straight blade duplex receptacle(s) with interior stainless steel wall plate(s), installed to be determined. The NEMA configuration for the receptacle(s) will be 5-20R.

The receptacle(s) will be powered from the shoreline inlet.

There will be a label installed near the receptacle(s) that state the following:

- Line Voltage
- Current Rating (amps)
- Phase
- Frequency

### **120 VOLT RECEPTACLE**

There will be four (4), 15/20 amp 120 volt AC three (3) wire straight blade duplex receptacle(s) with interior stainless steel wall plate(s), installed to be determined. The NEMA configuration for the receptacle(s) will be 5-20R.

The receptacle(s) will be powered from the shoreline inlet.

There will be a label installed near the receptacle(s) that state the following:

- Line Voltage
- Current Rating (amps)
- Phase
- Frequency

### **120 VOLT RECEPTACLE**

There will be two (2), 20 amp 120 volt AC three (3) wire twist lock receptacle(s) installed at the rear of the truck. The NEMA configuration for the receptacles will be L5-20R. There will be a weatherproof flip up cover installed if the receptacle is installed in an exposed location. There will be a interior cover plate install if the receptacle is installed in a protected location.

The receptacle(s) will be powered from the generator.

There will be a label installed near the receptacle(s) that state the following:

- Line Voltage
- Current Rating (amps)
- Phase
- Frequency

### **THREE SECTION 100' AERIAL PLATFORM**

#### **General Information**

It is the intent of these specifications to describe a telescoping, elevating platform. The unit will consist of a three (3) section, steel ladder with a self-leveling basket attached, to the ladder fly section.

#### **Operation on Grades**

The aerial unit will be capable of operating safely, on any slope up to 10 degrees at full capacities. (Operation beyond this limit will be at the operator's discretion.)

#### **Construction Standards**

The ladder will be constructed to meet all of the requirements as described in current NFPA 1901 standard.

These capabilities will be established in an unsupported configuration.

All structural load supporting elements of the aerial device that are made of a ductile material will have a design stress of not more than 50 percent of the minimum yield strength of the material based on the combination of the live load and the dead load. This 2:1 structural safety factor meets the current NFPA 1901 standard.

All structural load supporting elements of the aerial device that are made of non-ductile material will have a design stress of not more than 20 percent of the minimum ultimate strength of the material, based on the combination of the rated capacity and the dead load. This 5:1 safety factor meets the current NFPA 1901 standard.

The aerial device will be capable of sustaining a static load one and one-half times its rated tip load capacity (live load) in every position in which the aerial device can be placed when the vehicle is on a firm level surface.

The aerial device will be capable of sustaining a static load one and one-third times its rated tip load capacity (live load) in every position the aerial device can be placed when the vehicle is on a slope of five degrees downward in the direction most likely to cause overturning.

With the aerial device out of the cradle in the in the fully extended position at zero degrees elevation, a test load will be applied in a horizontal direction normal to the centerline of the ladder. The turntable will not rotate and the ladder will not deflect beyond what the product specification allows.

All welding will be in compliance with the American Welding Society standards. All welding personnel will be certified, as qualified under AWS welding codes.

All material and welds will have a structural safety factor of 2:1. This will be derived from taking into account structure weight, payload, wind load, ice load, and nozzle reactions.

The aerial device will be capable of operating in wind conditions of up to 35 mph and icing conditions of up to a 0.25" coating over the aerial structure.

All of the design criteria must be supported by the following test data:

- Strain gage testing of the complete aerial device
- Analysis of deflection data taken while the aerial device was under test load

The following standards for materials are to be used in the design of the aerial device:

- Materials are to be certified by the mill that manufactured the material
- Materials that are certified or recertified by vendors other than the mill will not be acceptable
- Material testing that is performed after the mill test will be for verification only and not with the intent of changing the classification.

### **Ladder Construction**

The ladder will be comprised of three (3) sections and will extend to a nominal height, of 100' above the ground, as measured by 1901 recommendations. The ladder (handrails, baserails, trusses, k-braces and rungs) will be constructed of welded, high strength steel certified by the manufacturer as being a minimum of 70,000 pounds per square inch of yield strength. Each section will be trussed diagonally, vertical and horizontally using round steel tubing. All critical points will be reinforced, for extra rigidity, and to provide a high strength-to-weight ratio. All ladder rungs will be round and welded to each section in two (2) places with "K" bracing for lateral and torsional rigidity.

The inside width dimensions of the ladder will be:

Base Section: 38.75"  
Mid Section: 28.88"  
Fly Section: 21.50"

The height of the handrails above the centerline of the rungs will be:

Base Section: 31.31"  
Mid Section: 26.82"  
Fly Section: 22.75"

### **Vertical Height**

The height of the unit will extend to no less than 100', as measured by a plumb line from the top surface of the basket handrail assembly to the ground, with the basket raised to a 75 degree angle. The aerial device will be measured, in this manner, for accurate comparison.

### **Horizontal Reach**

The rated horizontal reach will be 93'. The measurement of horizontal reach will be consistent with NFPA standards.

### **Mounting of Elevating Platform**

The aerial device will be rear mounted, to a torque box, on the truck chassis. Midship mounted aerial devices will not be acceptable.

### **Torque Box**

A "torsion box" subframe will be installed between the two sets of stabilizers. The torque box will be constructed of 0.312" steel plate (50,000 lb per square inch yield) with steel tubing reinforcement, on each side of the box, in the turntable area. The dimensions of the torque box will be 41.00" wide x 29.00" high x 253.50" long. The torque box subframe assembly will be capable of withstanding all torsional and horizontal loads when the unit is on the stabilizers. The torque box will be bolted to the chassis frame rails using thirty-two 0.750" SAE grade 8 bolts with nuts.

### **Turntable**

The turntable will be a 1.00" thick steel deck, coated with a non-skid, chemical resistant material in the walking areas. The stepping surfaces will meet the skid-resistance requirements of the current NFPA 1901 standard.

The turntable will measure 81.00" long x 96.00" wide. The turntable will include an enclosure for the hydraulic valves and rotation motor, which will also serve as a step, for access to the ladder.

The turntable handrails will be a minimum 42.00" high and will not increase the overall travel height of the vehicle. The handrails will be constructed from aluminum and have a slip resistant knurled surface.

### **Elevation System**

Two (2) double acting, lift cylinders will be utilized to provide smooth, precise elevation from 5 degrees below horizontal to 75 degrees above horizontal. The lift cylinder will be attached to each side of the base section. The lift cylinder rod will be chrome plated, to provide smooth operation of the aerial and reduce seal wear. The lift cylinders will be equipped with integral holding valves located in the cylinder, to prevent the unit from descending should the charged lines be severed, at any point within the hydraulic system and to maintain the ladder in the bedded position during road travel. The integral holding valves will NOT be located in the transfer tubes.



The elevation system will be controlled by the microprocessor. The microprocessor will provide the following features:

- Collision avoidance of the elevation system to prevent accidental body damage
- Automatic deceleration when the aerial device is lowered into the cradle
- Automatic deceleration at the end of stroke, in maximum raise and lower positions
- Deceleration of the aerial device from 0 to -5 degrees

### **Extension/Retraction System**

A hydraulically powered, extension and retraction system will be provided through dual hydraulic cylinders and wire ropes. Each set will be capable of operating the ladder in the event of a failure, of the other. For safety, systems that use only a single extension/retraction system will not be acceptable. The extension cylinder rod will be chrome plated to provide smooth operation of the aerial device and reduce seal wear. The extension/retraction cylinders will be equipped, with integral holding valves, to prevent the unit from retracting should the charged line be severed, at any point within the hydraulic system. The integral holding valves will NOT be located in the transfer tubes.

Wire ropes and attaching systems used to extend and retract the fly sections will have a 5:1 safety factor based on the ultimate strength under all operating conditions. The factor of safety for the wire rope will remain above 2:1 during any extension or retraction stall. The minimum ratio of the diameter of wire rope used to the diameter of the sheave used will be 1:12. Wire ropes will be constructed of seven (7) strands over an inner wire for increased flexibility. The wire rope will be galvanized to reduce corrosion.

The extension/retraction system will be controlled by the microprocessor. The microprocessor will provide the following features:

- Automatic deceleration at the end of stroke, in maximum extend and retract positions
- Controls the rate of retraction while flowing water

All sheaves will be greaseless and all sheave pins and pivot pins will be polished stainless steel.

### **Rotation System**

A 54.00" external tooth, monorace swing circle bearing will be used for the rotation system and will provide 360 degree continuous rotation. To insure proper bearing installation, both the open base bearing plate and the turntable bearing plate will be milled surfaces. The bearing will be bolted to the turntable and the base plate by a minimum of sixty grade 8, 0.88" bolts. Two (2) hydraulically driven, planetary gear boxes with drive speed reducers will be used to provide infinite and minute rotation control throughout the entire rotational travel. Two (2) spring applied, hydraulically released disc type swing brakes will be furnished to provide positive braking of the turntable assembly. Provisions will be made for emergency operation of the rotation system should complete loss of normal hydraulic power occur. The hydraulic system will be equipped with pressure relief valves which will limit the rotational torque to a nondestructive power.

The rotation system will be controlled by the microprocessor. The microprocessor will provide the following features:

- Envelope control of rotation system to prevent accidental body damage
- Prevent the aerial from being rotated into an unstable condition

### **Manual Override Controls**

Manual override controls will be provided for all aerial and stabilizer functions.

### **Ladder Slide Mechanism**

UHMW polyethylene wear pads will be used between the telescoping ladder sections, to provide greater bearing surface area for load transfer. Adjustable slide pads will also be used to control side play between the ladder sections.

### **Basket Leveling System**

A basket leveling system will be provided and so designed, that the basket with it's rated load, can be supported and maintained level, relative to the turntable, regardless of the elevation or flexion of the ladder.

Basket leveling will be accomplished by hydraulic circuitry, that is independent from the main hydraulic system. The leveling of the basket features a dual master/slave hydraulic cylinder system, with each side capable of supporting the load, while maintaining the basket level. Two (2) master cylinders are mounted between the turntable and the base ladder section, with two (2) slave cylinders mounted between the ladder fly section and the basket. The slave and master cylinders are 100 percent matched, so as the ladder is raised or lowered, exact amounts of hydraulic fluid are transferred between the master and slave cylinders thus maintaining the basket level.

The hydraulic circuitry includes pressure operated counter balance valves, on the load side of the slave cylinders, to prevent the basket from tipping should the hydraulic lines be severed.

A momentary switch is provided, on the cab instrument panel, to level the basket should this become necessary due to ambient temperature changes. It is not necessary to start the engine and activate the main hydraulic system to level the basket.

### **Rotation Interlock**

The microprocessor will be used to prevent the rotation of the aerial device to the side in which the stabilizers have not been fully deployed (short-jacked). The microprocessor will allow full and unrestricted use of the aerial, in the 180 degree area, on the side(s) where the stabilizers have been fully deployed. The system will also have a manual override, to comply with NFPA 1901.

### **Load Capacities**

The following load capacities will be established with the stabilizers at full horizontal extension and placed in the down position to level the truck and to relieve the weight from the tires and axles. Capacities will be based upon full extension and 360 degree rotation.

A load chart, visible at the operator's station, will be provided. The load chart will show the recommended safe load at any condition of the aerial device's elevation and extension.

### **35 MPH Wind Conditions/Dry**

Degrees of Elevation	-5 to 29	30 to 39	40 to 49	50 to 75
Basket	1000	1000	1000	1000
Fly	-	-	250	500
Mid	-	250	500	750
Base	250	500	750	1000

### **Water Tower Operation**

The following capacities will be based upon continuous 360 degree rotation and full extension.

### **35 MPH Wind Conditions/Water Charged**

Degrees of Elevation	-5 to 29	30 to 39	40 to 49	50 to 75
Basket	500	500	500	500
Fly	-	-	250	500
Mid	-	250	500	500
Base	-	500	500	750

### **Elevation -5 to +75 Degrees**

The aerial device will be able to maintain the above load capacities while flowing up to 1500 GPM and a nozzle position of 0 to 90 degrees to either side of the ladder centerline, as far above and below horizontal to the platform as nozzle design allows.

While flowing 1500 to 2000 GPM the nozzle position will be limited to 45 degrees either side of the ladder centerline horizontal to the platform, 30 degrees above horizontal, and as far below horizontal to the platform as nozzle design allows.

**Reduced loads in the basket can be redistributed in 250 lb increments to the fly, mid, or base as needed.**

### **Ladder Cradle Interlock System**

A ladder cradle interlock system will be provided through the microprocessor to prevent the lifting of the aerial device from the nested position until the operator places all the stabilizers in a load supporting configuration. A switch will be installed at the boom support to prevent operation of the stabilizers once the aerial has been elevated from the nested position.

### **Boom Support**

A heavy duty boom support, constructed of steel, is to be provided for support of the ladder in the travel position. The boom support will be bolted to the chassis frame as close to the front axle as

design allows. On the base section of the ladder, a stainless steel scuffplate will be provided where the ladder comes into contact with the boom support.

The boom support will be located just to the rear of the chassis cab.

#### **AERIAL BOOM SUPPORT LIGHT**

There will be one (1) Amdor®, Model AY-LB-12HW012, 190 lumen, 12" long, white LED strip light mounted on the boom support cradle. This light will be activated when the aerial master switch is activated.

#### **AERIAL BOOM PANEL**

There will be one boom panel provided on each side of the aerial ladder base section. The boom panel will be painted #10 white.

The boom panels will be designed so no mounting bolts are in the face of the panel. This will keep the lettering surface free of holes.

#### **EXTENSION INDICATOR**

Extension markings and corresponding numerical indicators will be provided along each inside and outside top rail of the base section of the aerial every five (5) feet. They will indicate various positions of extension up to full. Markings and indicators will be clearly visible to the console operator. To aid in visibility during hours of darkness, the markings and numerical indicators will be of a black reflective material.

#### **AERIAL DEVICE RUNG COVERS**

Each rung will be covered with a secure, heavy-duty, fiberglass pultrusion that incorporates an aggressive, no-slip coating.

The rung covers will be glued to each rung, and will be easily replaceable should the rung cover become damaged.

The center portion of each rung cover will be black and the outside 2.00" edge at each side will be safety yellow.

Under no circumstances will the rung covers be fastened to the rungs using screws or rivets.

The rung covers will have a 10-year, limited warranty.

#### **RUBBISH HOOK MOUNTING BRACKET**

Mounting will be provided near the end of the fly section of the aerial ladder for a rubbish hook.

The bracket will be sized to hold a Nupla 6' roof vent rubbish hook with D handle.

#### **STOKES AND BACKBOARD STORAGE BOX**

There will be two (2) aluminum storage box(es) provided at the base section of the aerial ladder on each side of the aerial device. The box will be painted to match the aerial device with the face of the box painted to match the boom sign color. The box(es) will be located in place of the aerial boom

panel and have a hinged cover with butterfly latch to secure the equipment. The cover will have the same finish as the box. A divider will be provided to separate the stokes basket and the backboard. The box(es) will have no louvers.

The size of the stokes basket and backboard will be to be determined.

The maximum capacity of each box will be 75 lb.

### **STABILITY TEST**

An aerial stability test will be run on this apparatus using the maximum weight allowance for tip options.

### **BASKET STRUCTURE**

The complete basket structure will be constructed of welded high strength steel certified by the manufacturer to have a minimum of 46,000 lb per square inch yield strength. Modular construction of the aerial platform basket will allow for easy component replacement should the basket become damaged during use. The aerial basket will be fully tested and independent third party certified.

The flooring and front decking of the basket will be multi-piece Morton Cass material, preventing the accumulation of water on the standing surface. The floor will measure approximately 34.00" long x 92.00" wide. The stepping surfaces will meet the skid-resistance requirements of current NFPA 1901 standard.

The outside basket steps used for transferring in and out of the basket will be at the same level as the basket floor. The steps on the front are approximately 16.00" deep. The front corners of the basket step will be mitered at 45 degrees to allow the basket to be maneuvered closer to buildings when approaching at an angle. A heavy extruded rubber bumper strip will be fastened to the outside edge of the step.

Four (4) stainless steel pompier belt safety loops will be attached to the inside of the basket. Two (2) lifting eyes will be provided on the bottom side of the basket support structure.

Two (2) rubber bumpers are provided on the bottom side of the basket structure for damage protection when setting it down on a surface.

The basket interior will be illuminated as required per the current edition of NFPA 1901. All hoses and wiring at the basket will be fully enclosed. Electrical sub-components will be mounted at the rear of the basket in a separate enclosure for easy servicing while maintaining an unobstructed basket interior.

### **BASKET SIDES**

The sides of the basket will be of solid single pan aluminum construction and, along with the basket doors, will form a continuous 42.00" high wall around the basket. The modular design of the basket will allow for easy replacement of components in case of damage.

### **BASKET ENTRANCES/EXITS**

Two (2) swing-in, spring-loaded, self-closing double pan doors constructed of aluminum will be provided at the front of the basket. The basket doors will be provided with positive locking latches. The rear of the basket will be equipped with a vertical self-closing gate for transfer to and from the basket's ladder device. Telescoping-type handrails will be provided as a banister to bridge the gap between the basket and the fly section at all elevations.

### **ACCESSORY MOUNTING RECEPTACLES**

Two (2) universal accessory mounting receptacles will be permanently affixed on the front of the basket to receive the **LyfeLine™** family of options such as the **Support™** rescue basket holders, **positive locking latches** rappelling arms, **LyfeLadder™** roof ladder brackets, **LyfeHoist™** winch, etc. Complete interchangeability will be required without modification to the basket.

### **ADDITIONAL MASK BOX AT BASKET**

An air mask storage box with a hinged cover and a SouthCo stainless steel draw latch will be provided at the basket. The cover will be weatherproof to protect the inside of the box from the elements. The box will be constructed of smooth aluminum and will be painted to match the aerial device. The box will be large enough for two (2) air mask(s) and hose.

### **LYFE BRACKET STORAGE BOX AT PLATFORM**

There will be one (1) storage box(es) with cover and rubber hood latch provided for the basket option brackets. The box(es) will be located at the right side of the basket when viewed from the turntable and will be painted to match the aerial device.

### **BASKET LANDING PAD EXTENSIONS**

There will be extension pads provided for each of the aerial basket landing feet located on the under side of the basket

### **MULTIPLEX DISPLAY COVER**

A cover will be provided for the multiplex display in the platform basket. The cover will be hinged at the front of the basket and when down it will cover the multiplex display. The cover will be constructed of tinted lexan.

The cover will be held down with a rubber draw latch.

### **LIGHTS FOR TURNTABLE WALKWAY**

There will be white LED lights provided at the aerial turntable. The lights will be located to illuminate the entire walking surface of the turntable including the area around the turntable console. These lights will be activated by the aerial master switch.

### **TURNTABLE CONSOLE LIGHTING**

There will be one (1), TecNiq Model T10, white LED light strip mounted in the turntable console cover to illuminate the controls located on both the upper and lower portion of the turntable control station. These lights will be activated by the aerial master switch.

### **ROTATION BEARING COVER**

An aluminum treadplate cover will be fitted over the aerial rotation bearing and drive pinion gear(s). The cover will be attached to the underside of the turntable deck.

### **BASKET HEAT SHIELDS**

A heat reflective shield will be provided on the front, sides and bottom of the basket.

The double pan basket access doors will form the heat shield at the front of the basket. The area between the access doors and behind the monitor(s) will be shielded with a horizontally hinged single pan aluminum fold down panel. The side heat shields will be formed by a single sheet of .090" aluminum. These heat shields will be painted to match the aerial basket.

Full under the basket heat shield protection with a non-glare finish will be provided with dual swing-down doors for ease of servicing and clean out.

### **INFORMATION CENTER**

There will be an information center provided. The information center will operate in temperatures from -40 to 185 degrees Fahrenheit. The information center will employ a Linux operating system and a 7.00" (diagonal measurement) LCD display. The LCD will have a minimum 400nits rated, color display. The LCD will be sunlight readable. The LCD display will be encased in an ABS, black plastic housing with a gray decal. There will be five (5), weather-resistant user interface switches provided. The LCD display can be changed to an available foreign language.

### **Operation**

The information center will be designed for easy operation in everyday use. There will be a page button to cycle from one screen to the next screen in a rotating fashion. A video button will allow an NTSC signal into the information center to be displayed on the LCD. If any button is pressed while viewing a video feed, the information center will return to the vehicle information screens. There will be a menu button to provide access to maintenance, setup, and diagnostic screens. All other button labels will be specific to the information being viewed.

### **General Screen Design**

Where possible, background colors will be used to provide vehicle information *At A Glance*. If the information provided on a screen is within acceptable limits, a green background color will be used. If the information provided on a screen is not within acceptable limits, an amber background color will indicate a caution condition and a red background color will indicate a warning condition.

Every screen in the information center will include the aerial tip temperature, the time (12- or 24-hour mode) and a text Alert Center. The time will be synchronized between all Command Zone color displays located on the vehicle. The Alert Center will display text messages for audible alarms. The text messages will identify any items causing the audible alarm to sound. If more than one (1) audible alarm is activated, the text message for each alarm will cycle every second until the problems have been resolved. The background for the Alert Center will change to indicate the severity of the warning message. Amber will indicate a caution condition and red will indicate a warning condition. If a

warning and a caution condition occur simultaneously, the red background color will be shown for all Alert Center messages.

A label will be provided for each button. The label will indicate the function for each active button for each screen. If the button is not utilized on specific screens, it will have a button label with no text.

Symbols will accurately depict the aerial device type the information pertains to such as rear mount ladder, rear mount platform, mid-mount ladder or mid-mount platform.

### **Page Screens**

The Information center will include the following pages:

The Aerial Main and Load Chart page will indicate the following information:

Rungs Aligned and Rungs Not Aligned will be indicated with text and respective green or red colored ladder symbols

Ladder Elevation will be indicated via a fire apparatus vehicle with ladder symbol with the degree of elevation indicated between the vehicle and ladder

Water Flow (if applicable) will be indicated via a water nozzle symbol and text indicating flow / time

Breathing Air Levels will be indicated via an air bottle symbol and text indicating the percent (%) of air remaining. A green bar graphs shown inside the bottle will indicate oxygen levels above 20%. A red bar graph will indicate oxygen levels at or below 20%. When oxygen levels are at or below 10% the red bar graph will flash.

The Aerial Load Chart will indicate the load limit on each section of the ladder based on actual ladder position and water flow (if applicable).

*At A Glance* color features will be utilized on this screen. Caution type conditions will be indicated via a yellow background. Warning type conditions will be indicated via a red background. Conditions operating within acceptable limits will be indicated via a green background.

The Aerial Reach and Hydraulic Systems page will indicate the following information:

Aerial Hydraulic Oil Temperature will be indicated with symbol and text. At a glance features will be utilized.

Aerial Hydraulic Oil Pressure will be indicated with a symbol and text. At a glance features will be utilized.

The following calculations will be indicated on a representative vehicle symbol:

Aerial Device Extension length.

Aerial Device Height indicating the height of the aerial device tip from the ground.



Aerial Device Reach indicating the horizontal distance the aerial reaches from the turntable.

Aerial Device Angle indicating the angle from the vehicle which the device is at.

*At A Glance* color features will be utilized on this screen. Caution type conditions will be indicated via a yellow background. Warning type conditions will be indicated via a red background. Conditions operating within acceptable limits will be indicated via a green background.

The Level Vehicle page will indicate the following information:

The grade of the vehicle will be indicated via a fire apparatus vehicle symbol with the degree of grade shown in text format. The symbol will tilt dependent on the vehicle grade.

The slope of the vehicle will be indicated via a fire apparatus vehicle symbol with the degree of slope shown in text format. The symbol will tilt dependent on the vehicle slope.

Outriggers status will be indicated via a colored symbol for each outrigger present. Each outrigger status will be defined as one of the following:

Outrigger stowed indicated with a silver pan located close to the vehicle

Outrigger fully extended indicated with a fully deployed green outrigger

Outrigger short-jacked indicated by a yellow outrigger partially deployed

Outrigger not set indicated by a red outrigger that is not set on the ground

A text box located on the vehicle symbol will be utilized to identify the overall status of the outrigger leveling system. The following status will be indicated in the text box:

Deployed status will indicate all outriggers are properly set on the ground at full extension

Shortjacked status will indicate one or more outriggers are set on the ground but not fully extended.

Not Set status will indicate one or more outriggers is not properly set on the ground.

Stowed status will indicate all outriggers are stowed for vehicle travel.

A bedding assist alert will indicate that the aerial device is being aligned by the Command Zone system as the operator lowers the aerial device into the cradle with the joystick.

*At A Glance* color features will be utilized on this screen. Caution type conditions will be indicated via a yellow background. Warning type conditions will be indicated via a red background. Conditions operating within acceptable limits will be indicated via a green background.

### **Menu Screens**

The following screens will be available through the Menu button:

The View System Information screen will display aerial device hours, aerial PTO hours, ladder aligned for stowing, aerial rotation angle, total water flow (if applicable), and aerial waterway valve status (if applicable).

The Set Display Brightness screen will allow brightness increase and decrease and include a default setting button.

The Configure Video Mode screen will allow setting of video contrast, video color and video tint.

The Set Startup screen allows setting of the screen that will be active at vehicle power-up.

The Set Date and Time screen has a 12- or 24-hour format, and allows setting of the time and date.

The View Active Alarms screen shows a list of all active alarms including the date and time of each alarm occurrence and shows all alarms that are silenced.

The System Diagnostics screen allows the user to view system status for each module and it's respective inputs and outputs. Viewable data will include the module type and ID number; the module version; and module diagnostics information including input or output number, the circuit number connected to that input or output, the circuit name (item connected to the circuit), status of the input or output, and other module diagnostic information.

Aerial Calibrations screen indicates items that may be calibrated by the user and instructions to follow for proper calibration of the aerial device.

Button functions and button labels may change with each screen.

### **LOWER CONTROL STATION**

A lower control station will be located at the rear of the apparatus in an easily accessible area. The controls and indication labels will be illuminated for nighttime operation. The following items will be furnished at the lower control station and will be clearly identified and conveniently located for ease of operation and viewing:

- Level assist switch
- Override switch to override microprocessor
- Emergency power unit switch

### **AERIAL DEVICE CONTROL STATIONS**

There will be two (2) device control stations, one (1) will be referred to as the basket control station and the other as the turntable control station. All elevation, extension and rotation controls will operate from both of these locations. The controls will permit the operator to regulate the speed of the aerial functions, within the safe limits, as determined by the manufacturer and NFPA standards. The controls will be grouped and operate in an identical manner at both stations for similarity of operation. The controls will be clearly marked and lighted for nighttime operation.

Each control will be equipped with a positive lock to hold the control in a neutral position, preventing accidental activation. In addition to the neutral lock, a console cover will be provided at the turntable control station. The controls will be so designed to allow the turntable control station to immediately override the basket controls, even if the ladder is being operated by the basket controls.

### **TURNTABLE CONTROL STATION**

The turntable control station will be located on the left side of the turntable so the operator may easily observe the basket while operating the controls.

The following items will be installed at the turntable control station, clearly identified and lighted for nighttime operation and conveniently located for ease of operation and viewing:

- Electric controls for elevation, rotation, extension/retraction
- Intercom controls
- Tip tracking light switch
- Emergency power unit switch
- Operator's load chart
- Three (3) position switch for selecting aerial operational speed

### **BASKET CONTROL CONSOLE**

The basket instrument panel will be located at the front center of the aerial platform. The following controls will be installed at the console and be clearly identified and illuminated for nighttime operation and conveniently located for ease of operation and viewing:

- Intercom controls
- Operator's load chart

### **AERIAL FUNCTION CONTROLS**

The aerial function controls, elevation, rotation, extension/retraction will be mounted in a separate control box, which will be attached to the front of the platform control console by means of an easily removable slide mechanism. The aerial function control box will have infinite positions along with three (3) fixed attachment points in the basket. The electrical connection will be by a permanently attached, strain relieved, coiled cord. The legend for the control lever functions will be illuminated.

### **HIGH IDLE**

The high idle will be controlled by the microprocessor. The microprocessor will automatically adjust the engine rpm to compensate for the amount of load placed upon the system. The system will include a safety device that allows activation of the high idle only when the parking brake is set and the transmission is placed in neutral.

### **STABILIZERS**

Two (2) sets of extendible out and down "H" type stabilizers will be provided for stability. The stabilizers will have a spread of 18'.

The stabilizers will be the double box design, with jack cylinders, that have a 4.25" internal diameter (bore) and 3.00" diameter cylinder rod. The jack cylinders will be equipped with integral holding valves, which will hold the cylinder either in the stowed position or the working position, should a charged line be severed at any point within the hydraulic system. For safety, the integral holding valves will be located in the cylinder base end, NOT in the transfer tube. Vertical jack cylinder rods will be fully enclosed by a telescoping inner box to protect the cylinder rods against damage which may occur.

The extension cylinders will be totally enclosed within the extension beams. The horizontal extension cylinders will be of the trombone type to eliminate wear and potential failure of hydraulic hoses.

The stabilizers will have the capability of 18.00" of ground penetration for set-up on uneven terrain. Extension of the horizontal beams will be activated by an extension cylinder totally enclosed within the extension beams. The cylinders will be equipped with internal decelerators. The cross section dimensions will be 13.00" high x 6.81" wide.

Each stabilizer leg will have attached to the end of the leg a 16 gauge polished stainless steel shield. The stainless steel shield will be of the split-pan design and will be a maximum 13.50" wide so as to allow the extension of the stabilizer between parked cars. This plate will serve as a protective guard and a mounting surface for warning lights. The top, forward, and rear edges will be flanged back for added strength.

### **STABILIZER CONTROLS**

A portable stabilizer control box will be provided. The control box will be weatherproof and oil resistant. Each function and indicator light will be labeled on a metal photo panel. The control box can be taken as far away as 15' from the vehicle with an extension cable.

The stabilizer control box will include the following:

- One (1) green power indicator light for stabilizer control that will be illuminated when the aerial master and "PTO" switches in the cab are activated.
- Four (4) electric toggle switches for stabilizers: each toggle switch will control the extend/retract and raise/lower of its respective stabilizer to allow vehicle set up in restricted areas and/or on uneven surfaces.
- Auto leveling assist switch: The outrigger control system will incorporate a computerized self leveling system in addition to the standard outrigger controls. The operator will have the option to manually or automatically level the truck. The computerized system will ensure full outrigger extension, proper jack penetration, and will level the vehicle within 1/2 a degree of level for safe operation of the aerial device.
- One (1) electric toggle switch for the engaging the emergency power unit.
- One (1) red "stabilizer not stowed" indicator light: this light will illuminate when the stabilizers are not in the fully stowed position.

- Four (4) fully extended beams green indicator lights: these lights will be illuminated when each of the respective stabilizer beams are fully extended.
- Four (4) firm on ground green indicator lights: each light will be illuminated when its respective stabilizer shoe is in the load supporting condition.

Each toggle switch will activate the engine fast idle automatically.

Manual override will be supplied for each stabilizer control valve.

A "Stabilizers Not Stowed" indicator will be provided in the driver's compartment. It will illuminate automatically whenever the stabilizers are not fully stowed to prevent damage to the apparatus if moved. The stabilizer system will also be wired to the "Do Not Move Indicator Light", which will flash whenever the apparatus parking brake is not fully engaged and the stabilizers are not fully stowed.

### **STABILIZER PADS**

A one (1) position, floating stabilizer pad will be provided on each stabilizer. The pads will require no operator adjustment during set up. The stabilizer pad will have the ability to pivot in a 360 degree plane for set up on uneven terrain.

### **AUXILIARY STABILIZER PADS**

A set of four auxiliary pads with handles will be provided for additional load distribution on soft surfaces. Their size will be 31.00" x 26.00" and they will be constructed of a lightweight composite material. The ground contact area for each stabilizer will be such that a unit pressure not greater than 75 psi (500 kPa) will be exerted over the ground contact area when the apparatus is loaded to its maximum in-service weight and the aerial device is carrying its rated capacity in every position permitted by the manufacturer. The pads will be stored in a double stacked configuration, two (2) behind each rear tandem axle in a single bracket.

### **CRADLE INTERLOCK SYSTEM**

A cradle interlock system will be provided to prevent the lifting of the aerial from the nested position until the operator has positioned all the stabilizers in a load supporting configuration. A switch will be installed at the cradle to prevent operation of the stabilizers once the aerial has been elevated from the nested position.

### **STABILIZER PINS**

The stabilizer jacks will not have holes for the stabilizer pins.

### **STABILIZER CONTROL BOX ALUMINUM DOOR**

A vertically hinged smooth aluminum door will be provided over the stabilizer control box. The door will be hinged outboard.

### **STABILIZER PLACEMENT**

There will be four (4) cameras provided and installed on the body, one (1) directly above each stabilizer. The cameras will be activated with a switch in the cab and will provide a picture to specify

the fully extended stabilizer position allowing the driver the ability to position the vehicle with the proper clearance for stabilizer deployment.

### **HYDRAULIC SYSTEM**

All high-pressure hoses will have an abrasion resistant cover, and have a rating greater than or equal to the working pressure of the circuit in which they are installed. All hydraulic fittings will be plated to minimize corrosion. The fitting will use an O-ring face seal, where possible, to minimize hydraulic leaks. All pressure carrying hydraulic hoses will have a 4:1 safety rating based on burst pressure

An interlock will be provided that prevents activation of the hydraulic pump until the transmission is placed in neutral and the parking brake is set as outlined in NFPA standards.

The hydraulic system will be of the load sense design to minimize heat build up and provide smooth control of the aerial ladder. The system will meet the performance requirement in NFPA standards, which requires adequate cooling after less than 2 1/2 hours of operations.

All hydraulic components that are non-sealing, where failure could result in the aerial movement, will comply with NFPA standards and have burst strength of 4:1. Dynamic sealing components, where failure could cause aerial movement, will have a margin of 2:1 on maximum operating pressure per NFPA standards. All hydraulic hoses, tubes, and connections will have minimum burst strength of 3:1 per NFPA standards.

A hydraulic oil pressure gauge will be supplied at the base control location per NFPA standards.

The aerial hydraulic system will be designed in such a manner that a hydraulic pump failure or line rupture will not allow the aerial or outriggers to lose position. Hydraulic holding valves will be mounted directly into cylinders. To insure reliable performance of holding valves, no hoses or tubing will be permitted between a holding valve and cylinder. The aerial will incorporate the use of trombone steel tubes inside the stabilizer beams to eliminate hydraulic hose wear and leaks. Hydraulic power to the ladder will be transferred from the pedestal by a hydraulic swivel.

### **HYDRAULIC RESERVOIR**

The hydraulic system will consist of an oil reservoir mounted to the torque box and plumbed to the hydraulic pump. There will be plumbing for a supply and return line and a tank drain on the reservoir.

The hydraulic pump suction line will have a shut-off ball valve for pump servicing.

The hydraulic oil reservoir fill will be labeled per NFPA standards. The hydraulic system will use multi-weight, SAE grade oil. ISO grade will be based on geographical location. The manufacturer will certify that the oil meets or exceeds the hydraulic cleanliness rating of 18/15/13 per ISO 4406:1999 before delivery.

### **HYDRAULIC FILTERS**

The system will incorporate the following filters to provide dependable service:

- Separate magnet (not on strainer)

- Reservoir suction strainer: 125 mesh
- Pressure filter with dirt alarm: Nominal 5 micron filter with a rating of 6.5 micron @ Beta 200 (99.5% efficiency); 7.5 micron @ Beta 1000 (99.9% efficiency)
- Return filter with dirt alarm: Nominal 5 micron filter with a rating of 6.5 micron @ Beta 200 (99.5% efficiency); 7.5 micron @ Beta 1000 (99.9% efficiency)
- Desiccant breather filter: Water capacity 4 fluid oz, 5 micron rating

### **HYDRAULIC CYLINDERS**

All hydraulic cylinders used on the aerial device will be produced by a manufacturer that specializes in the production of hydraulic cylinders.

### **POWER TAKEOFF / HYDRAULIC PUMP**

The apparatus will be equipped with a power takeoff driven by the chassis transmission and actuated by an electric shift located inside the cab. The power takeoff, which drives the hydraulic pump, will meet all the requirements for the aerial unit operations. The hydraulic pump will be a variable displacement piston pump, for consistent and rapid response, and be capable of supplying hydraulic oil at a nominal 50gpm flow at pressures up to 3000 psi. The system will operate up to 3000 psi with flow controls to protect hydraulic components and incorporate a relief valve set at 3150 psi to prevent over pressurization. The hydraulic pump will be solely dedicated to aerial operations. An amber indicator light will be installed on the cab instrument panel to notify the operator that the power takeoff is engaged.

An interlock will be provided that allows operation of the aerial power takeoff shift only after the chassis spring brake has been set and the chassis transmission has either been placed in the neutral position or drive position after the driveline has been disengaged from the rear axle.

### **EMERGENCY PUMP**

The hydraulic system will be designed with an auxiliary power unit meeting the guidelines of NFPA standards. The auxiliary power unit will be a 12-volt pump connected to the chassis electrical system. The pump will provide operation at reduced speeds to store the aerial device and outriggers for road transportation.

Self-centering switches will be provided at the turntable and stabilizer control station to activate the system. The system will be designed to provide a minimum of 30 minutes of hydraulic power to operate functions.

### **HYDRAULIC SWIVEL**

The aerial ladder will be equipped with a three (3) port, high pressure hydraulic swivel which will connect the hydraulic lines from the hydraulic pump and reservoir through the rotation point to the aerial control bank. The hydraulic swivel will allow for 360 degree continuous rotation of the aerial.

### **ELECTRIC SWIVEL**

The ladder will be equipped with an electric swivel to allow 360 degrees rotation of the aerial while connecting all electrical circuits through the rotation point. A minimum of 36 collector rings will be provided that are capable of supplying 20 amp continuous service. All collector rings will be enclosed and protected with desiccant plugs against condensation and corrosion. No oil or silicone will be used.

### **WATER SWIVEL**

Water will be transferred to the aerial waterway by means of a 5.00" internal diameter waterway, through the swivel, permitting 360 degree continuous rotation.

### **12-BIT ABSOLUTE ENCODER**

The aerial ladder will be equipped with a 12-Bit Absolute Encoder which provides 4096 counts per shaft turn for position and direction reference.

The 12-Bit Absolute Encoder will provide a unique binary word to reference each position and direction for all 360 degrees of rotation.

If the power is interrupted for any reason, the 12-Bit Absolute Encoder will allow power to be returned to the system without having to re-zero the settings.

The 12-Bit Absolute Encoder will be an integral part of a micro-processor based control system.

### **ELECTRICAL SYSTEM**

The 100' platform will utilize a microprocessor-based control system. The system will consist of the following components:

A tethered, CAN- based stabilizer control will be provided. The tethered control will be weatherproof and oil resistant. The stabilizer control will be illuminated with a LED strip light in the face of the unit. The electrical connection at the tethered control will be permanently attached by a strained relieved coil cord that will allow the operator to move 14ft away from the electrical connection for operation.

Remote Stabilizer Controls

Weatherproof and oil resistant

One (1) green "power" indicator light

One (1) red "stabilizer not stowed" indicator light

One (1) electric push button switch for auto level assist

One (1) electric push button switch for the emergency power unit

One (1) joystick for each stabilizer to control:

Extend/retract function

Raise/lower function



One (1) green "stabilizer fully extended" indicator light for each stabilizer

One (1) green "firm on ground" indicator light for each stabilizer

Control System Modules

Each of the control system modules will be configured as follows:

Sealed to a NEMA 4 rating

Operating range from -40 degrees F to 185 degrees F (-40 degrees C to 85 degrees C)

Communicate using J1939 data link

Two (2) diagnostic LED lights

One (1) green light that illuminates when module has power (B+) and ground

One (1) red light that flashes to indicate the module is capable of communicating via the data link

Ground matrix identification system

The following control system modules will be used:

Control Module

Main controller for the system

USB connection for computer diagnostics

Power Module

Built-in fault sensing

Eight (8) digital outputs

Pulse width modulating (PWM) capable

10A continuous per output

Circuit protection based on actual current draw (not affected by heat)

Constant Current Module

Built-in fault sensing

Three (3) analog inputs

Eight (8) digital outputs

Pulse width modulating (PWM) capable

3A continuous per output

Closed Loop System

Circuit protection based on actual current draw (not affected by heat)

Input Module

16 software selectable digital inputs

Output Module

16 digital outputs

Input/Output Module

Eight (8) software selectable (digital or analog) inputs

Eight (8) digital outputs

### **SPOTLIGHTS**

There will be four (4) Whelen bail mount Micro Pioneer, Model MPB\*, 12 volt DC LED lights furnished.

- One (1) will be mounted on the driver's side of the base section of the ladder.
- One (1) will be mounted on the passenger's side of the base section of the ladder.
- One (1) will be mounted on the front of the basket, on the driver's side.
- One (1) will be mounted on the front of the basket, on the passenger's side.

The painted parts of this light assembly to be white.

Power to the "tracking lights" will be controlled by an on/off switch at the turntable control operator's position.

The lights at the platform will be controlled by platform/tip and turntable.

The lights will be mounted below the handrail height so as not to increase the overall height of the unit.

### **LIGHTING ON AERIAL LADDER**

There will be TecNiq, Model D02, LED rung lighting provided on both sides of the aerial ladder base, mid, and fly sections. The lighting will be located adjacent to the ladder rungs along the lower rail of the ladder sections and will run the length of the ladder section.

The color of the sections will be:

- The base section of the ladder to be blue.
- The mid section of the ladder to be blue.
- The fly section of the ladder to be blue.

The LED rung lighting will be activated when the aerial master switch is activated.

The lights may be load managed when the parking brake is applied.

### **STABILIZER WARNING LIGHTS**

There will be four (4) Whelen®, Model M6\*C, LED flashing warning lights with Whelen, Model M6FC, chrome flanges installed, one (1) on each stabilizer cover panel.

- The front stabilizer pan lights will be red LED with a clear lens
- The rear stabilizer pan lights will be red LED with a clear lens

These warning lights will be activated by the same switch as the side warning lights.

### **STABILIZER BEAM WARNING LIGHTS**

Two (2) 4.00" diameter red LED flashing lights will be mounted on each stabilizer, one (1) facing forward and one (1) facing rearward. The lights will be Grote Supernova 40 series LED lights. The lights will be recessed in the horizontal beam of the stabilizer. These warning lights will be activated with the aerial master switch.

### **STABILIZER SCENE LIGHTS**

There will be one (1) Truck-Lite, Model 40227C 4.00" incandescent, scene light installed under each stabilizer beam to illuminate the surrounding area. A total of four (4) lights will be installed. These lights will be activated by the aerial master switch.

### **PLATFORM 120-VOLT ELECTRIC SYSTEM**

Two (2), 20 amp, NEMA L5-20, 120-volt, three (3)-prong twist lock receptacles with weatherproof covers will be provided in the aerial platform. One (1) receptacle will be located at the platform control console and one (1) will be located at the rear of the basket. Each receptacle will be supplied from individual branch circuits protected by dedicated 20 amp/120-volt circuit breakers. All wiring will be sized to and conform to the latest edition of NEC standards.

### **120 VOLT UNDER PLATFORM LIGHTING**

There will be Two (2) Whelen, Model PFP1AC, LED 120 volt floodlight(s) installed in semi-recessed housing(s) Model PBA103, provided under the platform basket, under driver side facing down, under passenger side facing forward.

The painted parts of this light assembly to be white

Light(s) will be switched at the platform/tip and turntable.

### **120 VOLT BASKET LIGHTING**

There will be Two (2) Whelen, Model PFP2AP, 120 volt AC LED flood light(s) provided at the platform basket.

The painted parts of this light assembly to be white.

The light(s) will be located on the driver and passenger side.

Light(s) will be switched at the platform/tip and turntable

## **2-WAY AERIAL COMMUNICATION SYSTEM**

There will be a Fire Research model ICA910 two-way intercom system provided. The control module with an LED volume display and push-button volume control will be located on the turntable operator console.

A hands free module will be located at the aerial tip or platform and constantly transmit to the other module unless the control module push-to-talk button is pressed.

Each intercom unit will be weatherproof.

## **VIDEO CAMERA SYSTEM**

There will be one (1) color CCD back-up style camera with 180 degree field of view color camera attached to the aerial water monitor in place of the monitor light and connected to a 2.4GHz wireless transmitter. A 2.4GHz receiver will be provided on the turntable and the cable will interface with the turntable multiplex information center display.

The following components will be supplied:

- One (1) Sharp Vision, Model SV-CW134639CAI Camera
- One (1) Sharp Vision, Model SV-WT-434 Transmitter
- One (1) Sharp Vision, Model SV-WR-096 Receiver
- All required cables

## **BREATHING AIR**

Breathing air will be supplied to the aerial platform. The air system will incorporate one (1), 437 cubic foot, 4500-psi cylinder. To allow the turntable operator an unobstructed view of the platform the cylinder will be mounted directly in front of the turntable and below the ladders. The air cylinder will be interconnected through a pressure regulator located at the air cylinder. A shutoff valve with guard will be provided on the cylinder. The air will be routed to the basket using hose especially designed for use in breathing air systems. At the platform, the breathing air will be accessible via two (2) quick couplings for air masks. These will have a Hansen brass 3000 series coupling. One (1) coupling will be located at the front of the basket on the right side and one (1) coupling will be located at the rear of the basket on the left hand side. There will be a weather resistant storage compartment for two (2) air

masks provided at the basket with a rubber draw latch. A 50' recharge hose will be provided for refilling the air cylinder without having to remove the tank from its mounting.

The breathing air cylinder will be designed and constructed to conform to the requirements of the United Nations (UN) on the transportation of dangerous goods.

### **BREATHING AIR LEVEL AND WARNING SYSTEM**

The level of breathing air remaining will be visible on the LCD display at all operating positions. The display will incorporate a low-pressure warning circuit that activates an audible alarm when 20% maximum air cylinder capacity remains. A second, louder audible alarm will activate when the remaining air level drops to 10% of maximum air cylinder capacity.

### **RAISED AERIAL PEDESTAL**

The aerial pedestal will be raised to accommodate the height of the cab.

### **WINCH**

A 500 pound portable electric winch will be provided.

The winch will mount to the front of the platform basket with a zinc coated bracket and be held in place with two (2) hardened 1.00" hitch pins. The winch will be powered by a 110V receptacle in the basket. The winch will be easily removable for storage.

The winch will be provided with 150 feet of .18" cable with a safety latch hook.

The winch is for cargo hoisting only and is not rated for human hoisting purposes.

A label will be placed on or near the mounting that states the maximum winch load rating and the maximum rope load rating that the mount can support.

### **LYFECOMBO™BRACKETS**

One (1) set of brackets will be supplied which will have the following three (3) options combined into one (1) set of brackets.

**LyfeLadder™**brackets will be provided for use at the front of the platform basket to increase the safety of firefighters during fireground and rescue operations. **LyfeLadder**brackets will be capable of holding up to a 20' Duo-Safety roof ladder securely in place. The roof ladder will be 19.00" wide. The ladder will be secured through its beams and one (1) rung, by a bar capable of being latched in place and able to withstand a minimum of a 500 pound load while maintaining a minimum of a two to one (2:1) safety factor. The complete system will maintain and exceed this criteria as well. There will also be a latching pawl to keep the ladder in a vertical position at all times and will latch on a rung, at least two (2) rungs below the primary attachment point. There has been appropriate strain gauging and testing completed on the system, (ladder and complete holding device), proving the above criteria has been satisfied. Additionally there is a letter on file from the roof ladder manufacturer, (Duo-Safety Corporation), stating that their standard roof ladder is approved for such an application.

**LyfeEye™** rappelling arms will be provided. The **LyfeEye** brackets will mount to the front of the platform basket, one (1) each side over the monitor/s and will be held in place with four (4) hardened 1.00" hitch pins, two (2) for each bracket. The **LyfeEye** brackets will be easily removable for storage. Each **LyfeEye** rappelling arm will have a capacity of 300#.

**LyfeSupport™** rescue basket support brackets will be provided. The **LyfeSupport** brackets will mount to the front of the platform basket, one (1) each side over the monitor/s and will be held in place with four (4) hardened 1.00" hitch pins, two (2) for each bracket. The **LyfeSupport** brackets will be easily removable for storage. Two (2) quick clip basket straps will be used to secure the basket to the **LyfeSupport** brackets.

### **AERIAL TURNTABLE MANSAVER™ BARS**

ManSaver™ bars will be installed at the aerial turntable.

### **AERIAL WATERWAY**

The aerial waterway will be capable of being supplied by either a midship mounted pump or an external water source through a 5.00" intake at the rear of the apparatus.

A 5.00" water swivel will be installed below the aerial turntable permitting the ladder to rotate 360 degrees continuously.

A 5.00" water swivel will be installed at the aerial heel pivot pin that will permit water tower operations of -5 degrees to 75 degrees. The heel pivot pin will not be integral with the waterway swivel at any point. The waterway design will allow complete servicing of the waterway swivel without disturbing the heel pivot pin.

A telescoping aluminum waterway will be installed beneath the center of the aerial ladder. The waterway will consist of a 5.00" diameter tube for the base section, 4.50" diameter tube for the mid-section and 4.00" diameter tube for the fly section.

A 1.50" drain will be provided for the waterway with the control at the rear of the unit.

### **WATERWAY SEALS**

The waterway seals will be of type-B PolyPak design, composed of nitroxile seal and a nitrile wiper, which together offer maximum stability and extrusion resistance on the waterway. The seal will be capable of withstanding pressures up to 2000 psi, temperatures in excess of 250 degrees Fahrenheit and have resistance to all foam generating solutions. The seals will be internally lubricated.

The waterway seals will have automatic centering guides constructed of synthetic thermalpolymer. The guides will provide positive centering of the extendible sections within each other and the base section to insure longer service life and smoother operation.

### **PLATFORM WATER SYSTEM**

A 4.00" (internal diameter) water swivel will connect the fly section waterway to the platform waterway. The water swivel will permit water tower operations from -5 degrees to 75 degrees. The

water will be routed from the swivel to a 4.00" gear operated butterfly valve on the front of the platform using a 4.00" tube. The deluge gun will be bolted onto the butterfly valve.

A 2.50" preset pressure relief valve will be provided in the waterway system. It will be designed to protect the aerial waterway from excess pressure. It will dump water to the ground when operating.

A shower nozzle rated at 75 gpm will be provided beneath the platform for heat protection for the platform personnel. A direct linkage control for the shower nozzle will be provided.

Two (2) - 2.50" preconnects will be provided at the front of the platform. The preconnects will be gated at the platform. One preconnect will be furnished with 2.50" NST threads and chrome plated cap and the other will be provided with a 2.50" x 1.50" NST reducer and a chrome plated cap.

### **AERIAL MONITOR**

There will be two (2) Akron Model 3480 monitors with stow and deploy provided at the front of the platform. One monitor will have a Arkon 2000 gpm Model 5178 electric nozzle with built in stream shaper and the other monitor will have a Akron 2000 gpm Model 5178 electric nozzle with built in stream shaper.

The monitor's functions will be controlled electrically from two (2) separate locations. One (1) control will be located at the turntable control console and the other at the basket control console.

### **WATERWAY FLOWMETER**

Waterway flow, including total water flowed, will be monitored by the microprocessor. An LCD display will be located at the upper and lower control stations.

### **REAR INLET**

A 5.00" NST inlet to the aerial waterway will be provided at the rear of the apparatus. It will be furnished with a 5.00" chrome plated adapter and a 5.00" chrome plated, long handle cap.

### **TOOLS**

The following tools will be provided for retorquing of all specified bolts as recommended by the manufacturer:

- Torque Wrench
- All Required Extensions, Sockets and Adapters
- 4-to-1 Multiplier

### **MANUALS**

The aerial manufacturer will provide two (2) operator maintenance manuals and two (2) wiring diagrams pertaining to the aerial device.

### **INITIAL INSTRUCTION**

On initial delivery of the fire apparatus, the contractor will supply a qualified representative to demonstrate the apparatus and provide initial instruction to the fire department regarding the operation, care, and maintenance of the apparatus for a period of four (4) consecutive days.

## **LOOSE EQUIPMENT**

The following equipment will be furnished with the completed unit:

- One (1) bag of chrome, stainless steel, or cadmium plated screws, nuts, bolts and washers, as used in the construction of the unit.

## **NFPA REQUIRED LOOSE EQUIPMENT PROVIDED BY FIRE DEPARTMENT**

The following loose equipment as outlined in NFPA 1901, 2016 edition, section 9.9.3 and 9.9.4 will be provided by the fire department.

- 800 ft (240 m) of 2.50" (65 mm) or larger fire hose, in any combination.
- 400 ft (120 m) of 1.50" (38 mm), 1.75" (45 mm), or 2.00" (52 mm) fire hose, in any combination.
- One (1) handline nozzle, 200 gpm (750 L/min) minimum.
- Two (2) handline nozzles, 95 gpm (360 L/min) minimum.
- One (1) playpipe with shutoff and 1.00" (25 mm), 1.125" (29 mm), and 1.25" (32 mm) tips.
- One (1) SCBA complying with NFPA 1981 for each assigned seating position, but not fewer than four (4), mounted in brackets fastened to the apparatus or stored in containers supplied by the SCBA manufacturer.
- One (1) spare SCBA cylinder for each SCBA carried, each mounted in a bracket fastened to the apparatus or stored in a specially designed storage space(s).
- One (1) first aid kit.
- Four (4) salvage covers, each a minimum size of 12 ft × 14 ft (3.6 m × 5.5 m).
- Four (4) combination spanner wrenches.
- Two (2) hydrant wrenches.
- One (1) double female 2.50" (65 mm) adapter with National Hose threads.
- One (1) double male 2.50" (65 mm) adapter with National Hose threads.
- One (1) rubber mallet, for use on suction hose connections.
- Four (4) ladder belts meeting the requirements of NFPA 1983.
- One (1) 150 ft (45 m) light-use life safety rope meeting the requirements of NFPA 1983.
- One (1) 150 ft (45 m) general-use life safety rope meeting the requirements of NFPA 1983.
- One (1) traffic vest for each seating position, each vest to comply with ANSI/ISEA 207, *Standard for High Visibility Public Safety Vests*, and have a five-point breakaway feature that includes two (2) at the shoulders, two (2) at the sides, and one (1) at the front.
- Five (5) fluorescent orange traffic cones not less than 28.00" (711 mm) in height, each equipped with a 6.00" (152 mm) retro-reflective white band no more than 4.00" (152 mm) from the top of the cone, and an additional 4.00" (102 mm) retro-reflective white band 2.00" (51 mm) below the 6.00" (152 mm) band.
- Five (5) illuminated warning devices such as highway flares, unless the five (5) fluorescent orange traffic cones have illuminating capabilities.
- One (1) automatic external defibrillator (AED).



- If the supply hose carried does not use sexless couplings, an additional double female adapter and double male adapter, sized to fit the supply hose carried, will be carried mounted in brackets fastened to the apparatus.
- If none of the pump intakes are valved, a hose appliance that is equipped with one or more gated intakes with female swivel connection(s) compatible with the supply hose used on one side and a swivel connection with pump intake threads on the other side will be carried. Any intake connection larger than 3.00" (75 mm) will include a pressure relief device that meets the requirements of 16.6.6.
- If the apparatus does not have a 2.50" National Hose (NH) intake, an adapter from 2.50" NH female to a pump intake will be carried, mounted in a bracket fastened to the apparatus if not already mounted directly to the intake.
- If the supply hose carried has other than 2.50" National Hose (NH) threads, adapters will be carried to allow feeding the supply hose from a 2.50" NH thread male discharge and to allow the hose to connect to a 2.50" NH female intake, mounted in brackets fastened to the apparatus if not already mounted directly to the discharge or intake.

#### **SOFT SUCTION HOSE**

There will be no soft suction hose provided.

#### **DRY CHEMICAL EXTINGUISHER PROVIDED BY FIRE DEPARTMENT**

NFPA 1901, 2016 edition, section 9.9.4 requires one (1) approved dry chemical portable fire extinguisher with a minimum 80-B:C rating mounted in a bracket fastened to the apparatus.

The extinguisher is not on the apparatus as manufactured. The fire department will provide and mount the extinguisher.

#### **WATER EXTINGUISHER PROVIDED BY FIRE DEPARTMENT**

NFPA 1901, 2016 edition, section 9.9.4 requires one (1) 2.5 gallon or larger water extinguisher mounted in a bracket fastened to the apparatus.

The extinguisher is not on the apparatus as manufactured. The fire department will provide and mount the extinguisher.

#### **AERIAL LADDER BELTS**

The following ladder belts will be provided:

- no small/medium belts
- two (2) large/extra large belts for 34"-42" waist
- one (1) XXL belt for 42"-50" waist

#### **FLATHEAD AXE PROVIDED BY FIRE DEPARTMENT**

NFPA 1901, 2016 edition, Section 9.9.4 requires one (1) flathead axe mounted in a bracket fastened to the apparatus.

The axe is not on the apparatus as manufactured. The fire department will provide and mount the axe.

### **PICKHEAD AXE PROVIDED BY FIRE DEPARTMENT**

NFPA 1901, 2016 edition, Section 9.9.4 requires one (1) pickhead axe mounted in a bracket fastened to the apparatus.

The axe is not on the apparatus as manufactured. The fire department will provide and mount the axe.

### **PAINT**

The exterior custom cab and body painting procedure will consist of a seven (7) step finishing process as follows:

1. Manual Surface Preparation - All exposed metal surfaces on the custom cab and body will be thoroughly cleaned and prepared for painting. Imperfections on the exterior surfaces will be removed and sanded to a smooth finish. Exterior seams will be sealed before painting. Exterior surfaces that will not be painted include; chrome plating, polished stainless steel, anodized aluminum and bright aluminum treadplate.
2. Chemical Cleaning and Pretreatment - All surfaces will be chemically cleaned to remove dirt, oil, grease, and metal oxides to ensure the subsequent coatings bond well. The aluminum surfaces will be properly cleaned and treated using a high pressure, high temperature 4 step Acid Etch process. The steel and stainless surfaces will be properly cleaned and treated using a high temperature 3 step process specifically designed for steel or stainless. The chemical treatment converts the metal surface to a passive condition to help prevent corrosion. A final pure water rinse will be applied to all metal surfaces.
3. Surfacer Primer - The Surfacer Primer will be applied to a chemically treated metal surface to provide a strong corrosion protective basecoat. A minimum thickness of 2 mils of Surfacer Primer is applied to surfaces that require a Critical aesthetic finish. The Surfacer Primer is a two-component high solids urethane that has excellent sanding properties and an extra smooth finish when sanded.
4. Finish Sanding - The Surfacer Primer will be sanded with a fine grit abrasive to achieve an ultra-smooth finish. This sanding process is critical to produce the smooth mirror like finish in the topcoat.
5. Sealer Primer - The Sealer Primer is applied prior to the Basecoat in all areas that have not been previously primed with the Surfacer Primer. The Sealer Primer is a two-component high solids urethane that goes on smooth and provides excellent gloss hold out when topcoated.
6. Basecoat Paint - Two coats of a high performance, two component high solids polyurethane basecoat will be applied. The Basecoat will be applied to a thickness that will achieve the proper color match. The Basecoat will be used in conjunction with a urethane clear coat to provide protection from the environment.
7. Clear Coat - Two (2) coats of Clear Coat will be applied over the Basecoat color. The Clear Coat is a two-component high solids urethane that provides superior gloss and durability to the

exterior surfaces. Lap style and roll-up doors will be Clear Coated to match the body. Paint warranty for the roll-up doors will be provided by the roll-up door manufacture.

Each batch of basecoat color is checked for a proper match before painting of the cab and the body. After the cab and body are painted, the color is verified again to make sure that it matches the color standard. Electronic color measuring equipment is used to compare the color sample to the color standard entered into the computer. Color specifications are used to determine the color match. A Delta E reading is used to determine a good color match within each family color.

All removable items such as brackets, compartment doors, door hinges, and trim will be removed and separately if required, to ensure paint behind all mounted items. Body assemblies that cannot be finish painted after assembly will be finish painted before assembly.

Pierce Manufacturing paint finish quality levels for critical areas of the apparatus (cab front and sides, body sides and doors, and boom lettering panels) meet or exceed the Cadillac/General Motors GMW15777 global paint requirements. Orange peel levels meet or exceed the #6 A.C.T. standard in critical areas. These requirements are met in order for the exterior paint finish to be considered acceptable. The Pierce Manufacturing written paint standards will be available upon request.

The cab will be two-tone, with the upper section painted #20 white along with a shield design on the cab face and lower section of the cab and body painted 268 Red.

#### **PAINT - ENVIRONMENTAL IMPACT**

Contractor will meet or exceed all current State regulations concerning paint operations. Pollution control will include measures to protect the atmosphere, water and soil. Controls will include the following conditions:

- Topcoats and primers will be chrome and lead free.
- Metal treatment chemicals will be chrome free. The wastewater generated in the metal treatment process will be treated on-site to remove any other heavy metals.
- Particulate emission collection from sanding operations will have a 99.99% efficiency factor.
- Particulate emissions from painting operations will be collected by a dry filter or water wash process. If the dry filter is used, it will have an efficiency rating of 98.00%. Water wash systems will be 99.97% efficient
- Water from water wash booths will be reused. Solids will be removed on a continual basis to keep the water clean.
- Paint wastes are disposed of in an environmentally safe manner.
- Empty metal paint containers will be to recover the metal.
- Solvents used in clean-up operations will be recycled on-site or sent off-site for distillation and returned for reuse.

Additionally, the finished apparatus will not be manufactured with or contain products that have ozone depleting substances. Contractor will, upon demand, present evidence that the manufacturing facility meets the above conditions and that it is in compliance with his State EPA rules and regulations.

## **PAINT CHASSIS FRAME ASSEMBLY**

The chassis frame assembly will be finished with a single system black top coat before the installation of the cab and body, and before installation of the engine and transmission assembly, air brake lines, electrical wire harnesses, etc.

Components that are included with the chassis frame assembly that will be painted are:

- Frame rails
- Frame liners
- Cross members
- Axles
- Suspensions
- Steering gear
- Battery boxes
- Bumper extension weldment
- Frame extensions
- Body mounting angles
- Rear Body support substructure (front and rear)
- Pump house substructure
- Air tanks
- Steel fuel tank
- Castings
- Individual piece parts used in chassis and body assembly

Components treated with epoxy E-coat protection prior to paint:

- Two (2) C-channel frame rails
- Two (2) frame liners

The E-coat process will meet the technical properties shown.

## **AXLE HUB PAINT**

All axle hubs will be painted to match lower job color.

## **COMPARTMENT INTERIOR PAINT**

The interior of all compartments will be painted with a gray spatter finish for ease of cleaning and to make it easier to touch up scratches and nicks.

## **AERIAL DEVICE PAINT COLOR**

The aerial device paint procedure will consist of a seven (7) step finishing process as follows:

1. Manual Surface Preparation - All exposed metal surfaces on the aerial device structural components above the rotation point will be thoroughly cleaned and mechanically shot-blasted to remove metal impurities and prepare the aerial for painting.

2. Zinc Rich Primer - Zinc rich primer will be applied to the torque box and stabilizers.
3. Primer/Surfacer Coats - A two (2) component epoxy primer/surfacer will be applied to the mechanically shot-blasted metal surfaces to provide a strong corrosion protective base coat and to smooth out the surface. All seams will be caulked with a two (2) component epoxy caulk before painting.
4. Hand Sanding - The primer/surfacer coat of the outer surfaces of the hand rails and base rails will be lightly sanded to a smooth finish.
5. Primer Coat - A two (2) component epoxy primer coat will be applied over the sanded primer.
6. Topcoat Paint - Urethane base coat will be applied to opacity for correct color matching.
7. Clear Coat - Two (2) coats of an automotive grade two (2) component urethane will be applied.

Surfaces that will not be painted include all chrome plated, polished stainless steel, anodized aluminum and bright aluminum treadplate.

All buy out components, such as monitor, nozzle, gauges, etc. will be supplied as received from the vendor.

Removable items such as brackets will be removed and painted separately to ensure paint coverage behind all mounted items.

The aerial device components will be painted as follows using the aforementioned seven (7) step finishing process:

- Aerial basket and basket leveling cylinders at tip: blue white 20
- Aerial device ladder sections and extension cylinders: blue white 20
- Aerial turntable and leveling cylinders (if applicable) at turntable: blue white 20
- Aerial control console: blue white 20
- Aerial lift cylinders: blue white 20
- Aerial rotation motor (if applicable): black
- Aerial torque box, support structure and components below the rotation point: gloss black primer
- Aerial stabilizers (middle and rear only): black 101
- Aerial boom support: gloss black primer

### **REFLECTIVE BAND**

A 6.00" white reflective band will be provided across the front of the vehicle and along the sides of the body.

The reflective band provided on the cab face will be at the headlight level.

### **REAR CHEVRON STRIPING**

There will be alternating chevron striping located on the rear-facing vertical surface of the apparatus. Covered surfaces will include the rear wall and aluminum doors. Rear compartment doors, stainless steel access doors, and the rear bumper will not be covered.

The colors will be red and fluorescent yellow green diamond grade.

Each stripe will be 6.00" in width.

This will meet the requirements of the current edition of NFPA 1901, which states that 50% of the rear surface will be covered with chevron striping.

### **REFLECTIVE STRIPE ON STABILIZERS**

There will be a 4.00" wide fluorescent yellow green diamond grade reflective stripe provided on the forward and rear facing side of all aerial stabilizers.

### **JOG(S) IN REFLECTIVE BAND**

The reflective band located on each side of the apparatus body will contain one (1) jog(s) and will be angled at approximately a 45 degrees when installed.

### **CAB DOOR REFLECTIVE STRIPE**

A 6.00" x 16.00" white reflective stripe will be provided across the interior of each cab door. The stripe will be located approximately 1.00" up from the bottom, on the door panel.

This stripe will meet the NFPA 1901 requirement.

### **BODY STRIPE**

There will be a genuine gold leaf stripe provided on each side of the body, located along the top of the side compartmentation.

### **CAB STRIPE**

There will be a genuine gold leaf stripe provided on both sides of the cab in place of the chrome molding.

### **LETTERING**

The lettering will be totally encapsulated between two (2) layers of clear vinyl.

### **LETTERING**

Forty-one (41) to sixty (60) genuine gold leaf lettering, 3.00" high, with outline and shade will be provided.

### **LETTERING**

There will be non-reflective vinyl lettering, 8.00" high, with outline and shade provided. There will be six (6) letters provided.

**LETTERING**

There will be non-reflective vinyl lettering, 5.00" high, with outline and shade provided. There will be 17 letters provided.

**LETTERING**

There will be non-reflective vinyl lettering, 18.00" high, with [Outline, Lettering] provided. There will be [Qty, Lettering] provided.

**DECAL INSTALLATION**

There will be one (1) pair of decals furnished by the fire department and applied by the apparatus manufacturer.

**EMBLEM/S**

There will be one (1) pair of genuine gold leaf emblems, 12.00" to 14.00" wide, supplied and installed centered above the grille. The emblems will include the fire department's monogram or number inside of a circle with scrolling.

**DEALER PROVIDED TOOL MOUNTING**

The Dealer is to provide fabrication and mounting bracket for equipment to be installed on the apparatus up to the amount of \$15,000. Fire Department to provide a list of equipment and apparatus to use as a model.

**FIRE APPARATUS PARTS MANUAL**

There will be one (1) custom parts manual(s) in USB flash drive format for the complete fire apparatus provided.

The manual(s) will contain the following:

- Job number
- Part numbers with full descriptions
- Table of contents
- Parts section sorted in functional groups reflecting a major system, component, or assembly
- Parts section sorted in alphabetical order
- Instructions on how to locate parts

Each manual will be specifically written for the chassis and body model being purchased. It will not be a generic manual for a multitude of different chassis and bodies.

**Service Parts Internet Site**

The service parts information included in these manuals are also available on the Pierce website. The website offers additional functions and features not contained in this manual, such as digital photographs and line drawings of select items. The website also features electronic search tools to assist in locating parts quickly.

### **CHASSIS SERVICE MANUALS**

There will be one (1) chassis service manuals on USB flash drives containing parts and service information on major components provided with the completed unit.

The manual will contain the following sections:

- Job number
- Table of contents
- Troubleshooting
- Front Axle/Suspension
- Brakes
- Engine
- Tires
- Wheels
- Cab
- Electrical, DC
- Air Systems
- Plumbing
- Appendix

The manual will be specifically written for the chassis model being purchased. It will not be a generic manual for a multitude of different chassis and bodies.

### **CHASSIS OPERATION MANUAL**

The chassis operation manual will be provided on one (1) USB flash drive.

### **ONE (1) YEAR MATERIAL AND WORKMANSHIP**

A Pierce basic apparatus limited warranty certificate, WA0008, is included with this proposal.

### **ENGINE WARRANTY**

A Detroit Diesel **five (5) year** limited engine warranty will be provided. A limited warranty certificate, WA0180, is included with this proposal.

### **STEERING GEAR WARRANTY**

A Sheppard **three (3) year** limited steering gear warranty will be provided. A copy of the warranty certificate will be submitted with the bid package.

### **FIFTY (50) YEAR STRUCTURAL INTEGRITY**

The Pierce custom chassis frame limited warranty certificate, WA0013, is included with this proposal.

### **FRONT AXLE THREE (3) YEAR MATERIAL AND WORKMANSHIP WARRANTY**

The Pierce TAK-4 suspension limited warranty certificate, WA0050, is included with this proposal.

### **TDM REAR AXLE FIVE (5) YEAR MATERIAL AND WORKMANSHIP WARRANTY**

A Meritor™ Axle 5 year limited warranty will be provided.



#### **ABS BRAKE SYSTEM THREE (3) YEAR MATERIAL AND WORKMANSHIP WARRANTY**

A Meritor Wabco™ ABS brake system limited warranty certificate, WA0232, is included with this proposal.

#### **TEN (10) YEAR STRUCTURAL INTEGRITY**

The Pierce custom cab limited warranty certificate, WA0012, is included with this proposal.

#### **TEN (10) YEAR PRO-RATED PAINT AND CORROSION**

A Pierce cab limited pro-rated paint warranty certificate, WA0055, is included with this proposal.

#### **FIVE (5) YEAR MATERIAL AND WORKMANSHIP**

The Pierce Command Zone electronics limited warranty certificate, WA0014, is included with this proposal.

#### **CAMERA SYSTEM WARRANTY**

A Pierce fifty four (54) month warranty will be provided for the camera system.

#### **COMPARTMENT LIGHT WARRANTY**

The Pierce 12 volt DC LED strip lights limited warranty certificate, WA0203, is included with this proposal.

#### **TRANSMISSION WARRANTY**

The transmission will have a **five (5) year/unlimited mileage** warranty covering 100 percent parts and labor. The warranty will be provided by Allison Transmission.

Note: The transmission cooler is not covered under any extended warranty you may be getting on your Allison Transmission. Please review your Allison Transmission warranty for coverage limitations.

#### **TRANSMISSION COOLER WARRANTY**

The transmission cooler will carry a five (5) year parts and labor warranty (exclusive to the transmission cooler). In addition, a collateral damage warranty will also be in effect for the first three (3) years of the warranty coverage and will not exceed \$10,000 per occurrence. A copy of the warranty certificate will be submitted with the bid package.

#### **WATER TANK WARRANTY**

A UPF poly water tank limited warranty certificate, WA0195, is included with this proposal.

#### **TEN (10) YEAR STRUCTURAL INTEGRITY**

The Pierce apparatus body limited warranty certificate, WA0009, is included with this proposal.

#### **ROLL UP DOOR MATERIAL AND WORKMANSHIP WARRANTY**

A Gortite roll-up door limited warranty will be provided. The mechanical components of the roll-up door will be warranted against defects in material and workmanship for the lifetime of the vehicle. A **six (6) year** limited warranty will be provided on painted and satin roll up doors.

The limited warranty certificate, WA0190, is included with this proposal.

**SIX (6) YEAR PARTS, ONE (1) YEAR LABOR**

The pump and its components will be provided with a six (6) year parts and one (1) year labor limited warranty. The manufacturer's warranty will provide that the pump and its components will be free from failures caused by defects in material and workmanship that would arise under normal use and service.

A copy of the warranty certificate will be submitted with the bid package.

**TEN (10) YEAR PUMP PLUMBING WARRANTY**

The Pierce apparatus plumbing limited warranty certificate, WA0035, is included with this proposal.

**FOAM SYSTEM WARRANTY**

The Husky 3 foam system limited warranty certificate, WA0231, is included with this proposal.

**TWENTY (20) YEAR AERIAL DEVICE STRUCTURAL INTEGRITY WARRANTY**

The Pierce device limited warranty certificate, WA0052, is included with this proposal.

**AERIAL SWIVEL WARRANTY**

An Amity five (5) year limited swivel warranty will be provided. A copy of the warranty certificate will be submitted with the bid package.

**HYDRAULIC SYSTEM COMPONENTS WARRANTY**

Aerial hydraulic system components will be provided with a five (5) year material and workmanship limited warranty.

**HYDRAULIC SEAL WARRANTY**

Aerial hydraulic seals will be provided with a three (3) year material and workmanship limited warranty.

A copy of the warranty certificates will be submitted with the bid package.

**AERIAL WATERWAY WARRANTY**

An Amity ten (10) year limited waterway warranty will be provided. A copy of the warranty certificate will be submitted with the bid package.

**FOUR (4) YEAR PRO-RATED PAINT AND CORROSION**

A Pierce aerial device limited pro-rated paint warranty certificate, WA0047, is included with this proposal.

**FIVE (5) YEAR MATERIAL AND WORKMANSHIP**

The Pierce Command Zone electronics limited warranty certificate, WA0014, is included with this proposal.

**SIX (6) YEAR GENERATOR MATERIAL AND WORKMANSHIP WARRANTY**

A Harrison Hydra-Gen limited warranty certificate, WA0285, is included with this proposal.

**TEN (10) YEAR PRO-RATED PAINT AND CORROSION**

A Pierce body limited pro-rated paint warranty certificate, WA0057, is included with this proposal.

### **THREE (3) YEAR MATERIAL AND WORKMANSHIP**

The Pierce Goldstar gold leaf lamination limited warranty limited warranty certificate, WA0018, is included with this proposal.

### **VEHICLE STABILITY CERTIFICATION**

The fire apparatus manufacturer will provide a certification stating the apparatus complies with NFPA 1901, current edition, section 4.13, Vehicle Stability. The certification will be provided at the time of bid.

### **ENGINE INSTALLATION CERTIFICATION**

The fire apparatus manufacturer will provide a certification, along with a letter from the engine manufacturer stating they approve of the engine installation in the bidder's chassis. The certification will be provided at the time of bid.

### **POWER STEERING CERTIFICATION**

The fire apparatus manufacturer will provide a certification stating the power steering system as installed meets the requirements of the component supplier. The certification will be provided at the time of bid.

### **CAB INTEGRITY CERTIFICATION**

The fire apparatus manufacturer will provide a cab crash test certification with this proposal. The certification states that the cab must meet or exceed the requirements below:

- European Occupant Protection Standard ECE Regulation No.29
- SAE J2422 Cab Roof Strength Evaluation - Quasi-Static Loading Heavy Trucks
- SAE J2420 COE Frontal Strength Evaluation - Dynamic Loading Heavy Trucks
- Roof Crush
  - The cab will be subjected to a roof crush force of 100,000 lb. This value will be 450 percent of the ECE 29 criteria, which must be equivalent to the front axle rating up to a maximum of ten (10) metric tons.
- Side Impact
  - The cab will be subjected to dynamic preload with a 13,275-lb moving barrier is slammed into the side of the cab at 5.50 mph, striking with an impact of 13,000 ft-lb of energy. This test will closely represent the forces a cab will see in a rollover incident.
- Frontal Impact
  - The cab will withstand a frontal force produced from 65,200 ft-lb of energy using a swing-bob type platen.

The same cab will withstand all tests without any measurable intrusion into the survival space of the occupant area.

There will be no exception to any portion of the cab integrity certification. Nonconformance will lead to immediate rejection of bid.

### **CAB DOOR DURABILITY CERTIFICATION**

Robust cab doors help protect occupants. Cab doors will survive a 200,000 cycle door slam test where the slamming force exceeds 20 G's of deceleration. The bidder will certify that the sample doors similar to those provided on the apparatus have been tested and have met these criteria without structural damage, latch malfunction, or significant component wear.

### **WINDSHIELD WIPER DURABILITY CERTIFICATION**

Visibility during inclement weather is essential to safe apparatus performance. Windshield wipers will survive a 3 million cycle durability test in accordance with section 6.2 of SAE J198 *Windshield Wiper Systems - Trucks, Buses and Multipurpose Vehicles*. The bidder will certify that the wiper system design has been tested and that the wiper system has met these criteria.

### **ELECTRIC WINDOW DURABILITY CERTIFICATION**

Cab window roll-up systems can cause maintenance problems if not designed for long service life. The window regulator design will complete 30,000 complete up-down cycles and still function normally when finished. The bidder will certify that sample doors and windows similar to those provided on the apparatus have been tested and have met these criteria without malfunction or significant component wear.

### **SEAT BELT ANCHOR STRENGTH**

Seat belt attachment strength is regulated by Federal Motor Vehicle Safety Standards and should be validated through testing. Each seat belt anchor design will withstand 3000 lb of pull on both the lap and shoulder belt in accordance with FMVSS 571.210 Seat Belt Assembly Anchorages. The bidder will certify that each anchor design was pull tested to the required force and met the appropriate criteria.

### **SEAT MOUNTING STRENGTH**

Seat attachment strength is regulated by Federal Motor Vehicle Safety Standards and should be validated through testing. Each seat mounting design will be tested to withstand 20 G's of force in accordance with FMVSS 571.207 Seating Systems. The bidder will certify that each seat mount and cab structure design was pull tested to the required force and met the appropriate criteria.

### **CAB DEFROSTER CERTIFICATION**

Visibility during inclement weather is essential to safe apparatus performance. The defroster system will clear the required windshield zones in accordance with SAE J381 Windshield Defrosting Systems Test Procedure And Performance Requirements - Trucks, Buses, And Multipurpose Vehicles. The bidder will certify that the defrost system design has been tested in a cold chamber and passes the SAE J381 criteria.

### **CAB HEATER CERTIFICATION**

Good cab heat performance and regulation provides a more effective working environment for personnel, whether in-transit, or at a scene. The cab heaters will warm the cab 77 degrees Fahrenheit from a cold-soak, within 30 minutes when tested using the coolant supply methods found in SAE J381. The bidder will certify that a substantially similar cab has been tested and has met these criteria.

### **CAB AIR CONDITIONING PERFORMANCE CERTIFICATION**

Good cab air conditioning temperature and air flow performance keeps occupants comfortable, reduces humidity, and provides a climate for recuperation while at the scene. The cab air conditioning system will cool the cab from a heat-soaked condition at 100 degrees Fahrenheit to an average of 72 degrees Fahrenheit in 30 minutes. The bidder will certify that a substantially similar cab has been tested and has met these criteria.

### **AMP DRAW REPORT**

The bidder will provide, at the time of bid and delivery, an itemized print out of the expected amp draw of the entire vehicle's electrical system.

The manufacturer of the apparatus will provide the following:

- Documentation of the electrical system performance tests.
- A written load analysis, which will include the following:
  - The nameplate rating of the alternator.
  - The alternator rating under the conditions specified per:
    - Applicable NFPA 1901 or 1906 (Current Edition).
  - The minimum continuous load of each component that is specified per:
    - Applicable NFPA 1901 or 1906 (Current Edition).
  - Additional loads that, when added to the minimum continuous load, determine the total connected load.
  - Each individual intermittent load.

All of the above listed items will be provided by the bidder per the applicable NFPA 1901 or 1906 (Current Edition).



## Santa Fe Springs Fire Department

100% Pre-Payment Option  
September 30, 2020

If a 100% pre-payment were made at contract signing, the following discount would be applied to the final invoice:

	Each	Extension
<b>One ( 1 )</b>		
<b>Arrow XT 100' Legacy Platform Aerial</b>		
	<b>\$ 1,410,719.00</b>	<b>\$ 1,410,719.00</b>
100% Prepayment Discount	\$ (47,223.00)	\$ (47,223.00)
<b>APPARATUS COST</b>	<b>\$ 1,363,496.00</b>	<b>\$ 1,363,496.00</b>
Sales Tax @ 10.500%	\$ 143,167.08	\$ 143,167.08
Performance Bond	\$ 3,129.12	\$ 3,129.12
California Tire Fee	\$ 17.50	\$ 17.50
Consortium Fee Not Applicable	\$ -	\$ -
<b>TOTAL PREPAY PURCHASE PRICE</b>	<b>\$ 1,509,809.70</b>	<b>\$ 1,509,809.70</b>
Less 100% pre-payment at Contract Signing	\$ 1,509,809.70	\$ 1,509,809.70
<b>BALANCE DUE AT DELIVERY</b>	<b>\$0.00</b>	<b>\$0.00</b>

<b>100% PRE-PAYMENT DISCOUNT SHOWN ABOVE IS AVAILABLE IN TWO WAYS:</b>
--

- a) If your department makes a 100% cash pre-payment at contract signing.
- b) If your department signs up for a lease-purchase with Pierce Financial Solutions. This would require no money down and no payments for one (1) year if desired.

- \* Discount for the 100% pre-payment option includes discounts for the chassis, interest, aerial (if applicable), and flooring charges.
- \* Any item added after this option is elected will come at additional cost and will be added to the final invoice.

# Motorola Solutions

## Customer Quote

Prepared By: Joe Warner

Phone: (312) 204-9300

Date: Sep. 14, 2020

Quote #: APX8500 Fire Mobile

CUSTOMER #:

PREPARED FOR: Vic Marin	Bill To Please provide	Ship to PLEASE PROVIDE
COMPANY: Santa Fe Springs Fire	Address:	Address:
PHONE:		
FAX:		

### Equipment Details and Pricing

Qty.	Model	Description	Unit Price	Discount Price	Total Price
2	M37TSS9PW1 N	APX8500 ALL BAND MID POWER	\$4,770.00	\$3,005.10	\$ 6,010.20
2	G806	ADD: ASTRO DIGITAL CAI OPERATION	\$515.00	\$324.45	\$ 648.90
2	G51	ENH: SMARTZONE OPERATION APX	\$1,500.00	\$945.00	\$ 1,890.00
2	G361	ADD: P25 TRUNKING SOFTWARE	\$300.00	\$189.00	\$ 378.00
2	GA00580	ADD: TDMA OPERATION	\$450.00	\$283.50	\$ 567.00
2	G442	ADD: O5 CONTROL HEAD	\$432.00	\$272.16	\$ 544.32
2	G67	ADD: REMOTE MOUNT MID POWER	\$297.00	\$187.11	\$ 374.22
		<i>(The 5 meter (17 FT) Cable Ships Standard)</i>		\$0.00	
2	GA01513	ADD: All BAND MOBILE ANTENNA 7/8,V, U)	\$95.00	\$59.85	\$ 119.70
2	W22	ADD: PALM MICROPHONE	\$72.00	\$45.36	\$ 90.72
2	B18	ADD: AUXILARY SPKR 7.5 WATT	\$60.00	\$37.80	\$ 75.60
2	W12	ADD: RF PREAMP	\$66.00	\$41.58	\$ 83.16
2	GA01515	ADD: J600 ADAPTOR CABLE	\$95.00	\$59.85	\$ 119.70
2	GA00226	ADD: GPS WIFI ANTENNA	\$75.00	\$47.25	\$ 94.50
2	GA09001	ADD: WI-FI CAPABILITY	\$300.00	\$189.00	\$ 378.00
2	GA09007	ADD: OUT OF THE BOX WI-FI Provisioning	\$0.00	\$0.00	\$ -
2	G996	ENH: OVER THE AIR PROVISIONING	\$100.00	\$63.00	\$ 126.00
2	G851	ADD: AES/DES-XL/DES-OFB ENCRYPTION	\$799.00	\$503.37	\$ 1,006.74
2	G298	ENH: ASTRO 25 OTAR W/ MULTIKEY	\$740.00	\$466.20	\$ 932.40

\$ 13,439.16

TAX 10.5% \$1,411.11

\$ 450.00

2 G78

ADD: 3 YR SFS LITE - MOBILE

\$225.00

QUOTE PAGE TOTAL

<b>\$15,300.27</b>
--------------------

#### QUOTE TERMS AND CONDITIONS:

1. Quotes are exclusive of all installation and programming charges (unless expressly stated) and all applicable taxes.
2. Purchaser will be responsible for shipping costs, which will be added to the invoice.
3. Prices quoted are valid for thirty(30) days from the date of this quote.
4. Unless otherwise stated, payment will be due within thirty days after invoice.

This quotation is provided to you for information purposes only and is not intended to be an offer or a binding proposal.

If you wish to purchase the quoted products, Motorola will be pleased to provide you with our standard terms and conditions of sale, or alternatively, receive your purchase order which will be acknowledged. Thank you for your consideration of Motorola products.

# Motorola Solutions

## Customer Quote

Prepared By: Joe Warner

Phone: (312) 204-9300

Date: Sep. 14, 2020

Quote #: APX 8000 PD

CUSTOMER #:

PREPARED FOR: Brad Davis

COMPANY: Santa Fe Springs Fire

PHONE:

FAX:

Bill To Please provide

Address:

Ship to PLEASE PROVIDE

Address:

### Equipment Details and Pricing

<u>Qty.</u>	<u>Model</u>	<u>Description</u>	<u>Unit Price</u>	<u>Discount Price</u>	<u>Total Price</u>
5	NNTN8863A	IMPRES 2 SINGLE UNIT CHARGER	\$168.30	\$134.64	\$ 673.20
					\$ 673.20
				TAX 10.5%	\$70.69

QUOTE PAGE TOTAL

**\$743.89**

#### QUOTE TERMS AND CONDITIONS:

1. Quotes are exclusive of all installation and programming charges (unless expressly stated) and all applicable taxes.
2. Purchaser will be responsible for shipping costs, which will be added to the invoice.
3. Prices quoted are valid for thirty (30) days from the date of this quote.
4. Unless otherwise stated, payment will be due within thirty days after invoice.

This quotation is provided to you for information purposes only and is not intended to be an offer or a binding proposal.

If you wish to purchase the quoted products, Motorola will be pleased to provide you with our standard terms and conditions of sale, or alternatively, receive your purchase order which will be acknowledged. Thank you for your consideration of Motorola products.



<h1>DuraTech USA, Inc.</h1> <h2>Rugged Mobile Computing Solutions</h2> <p>Mailing: 6765 Westminster Bl. #314 Westminster, CA 92683 www.DuraTechUSA.com Phone # 714-898-2171 FEIN# 20-2777132</p> <p><b>Certified 8(a), SBE #19486, DBE #40914, OCTA# 39991, CUCP#35922, MBE &amp; WBE, LACounty #128985 LSBE/PPE# 088381, POLB # 250398, METRO# 7881</b></p>		<h1>QUOTE</h1>		
		Date	Quote #	
		9/15/2020	091520SFSFD	
		Customer Information		
		Santa Fe Springs Fire Dept. 11300 Greenstone Avenue Santa Fe Springs, CA 90670 Attn: Vic Marin SFSFD Fire Engine		
Rep	Project Delivery Date	Terms	Customer E-mail	
CG	10/29/2020	Net 30	VictorMarinJr@santafespri...	
Item	Description	Qty	Cost	Total
AM4OT6QA5IXX	GETAC : A140 G2, i7-10510U, Webcam, Win10x64+16GB, 5 12GB PCIe SSD, SR (Full HD IPS+Touch), US Power Cord, 8M Rear Camera, Wifi+BT+GPS+Passthrough, Micro SD, LAN, Smart Card reader, 3 Year Warranty B2B	1	3,400.42	3,400.42T
OHHGTC8013	GETAC : Havis Triple Pass-Through Vehicle Dock with Port Replicator & bracket. DC Power Adaptor sold separately (A140)	1	651.26	651.26T
GAD2X8	GETAC : Getac 120W 11-16V, 22-32V DC Vehicle adapter (Bare Wire), 3 year warranty	1	100.04	100.04T
590GBL000240	Airgain-AP-GTC-MMF-CWG-Q-BL-19, Cell/LTE, WiFi, GNSS, 19ft coax, color black, new form factor (Threaded bolt)	1	158.91	158.91T
CA LCD Disposal Fee	CALIFORNIA LCD DISPOSAL FEE	1	4.00	4.00
4-6 Weeks ARO	4-6 Weeks After Receipt of Order		0.00	0.00T
	Sales Tax		10.50%	452.62
			<b>Total</b>	<b>\$4,767.25</b>
<p>Delivery Lead time 4-6 weeks (unless otherwise noted) from date of purchase unless otherwise noted.          Prices are good for 30 days and may be subject to change without notice          **Some Options &amp; Upgrade costs applicable to time of original purchase only          NET 30 Terms for Govt Orders. Due to highly discounted prices quoted, there will be a 3% service charge for any orders placed with a credit card.          Prepaid Company check or bank wire transfer with PO or Net30 OAC, VISA, M/C, American Express Cards Accepted (Discounts not applicable with credit card orders)          All International Orders -Prepaid Wire Transfer (\$30 Wire Fee Applies)          All California purchases require \$5 LCD Disposal Fee per unit &amp; applicable sales taxes          All Customs Fee, Duties &amp; Taxes &amp; shipping costs are the responsibility of purchaser          Please check specifications carefully! Due to Customization -All Sales are final! Send Orders to: PO@DuraTechUSA.com</p>				



September 30, 2020

Travis Hickey  
Director of Finance  
City of Santa Fe Springs Finance & Administrative Services  
12636 Emmens Way, Santa Fe Springs, CA 90670

Dear Mr. Hickey:

Public Sector Capital, LLC is pleased to submit the following proposal. This proposal does not represent a commitment to finance. The following terms and conditions apply to this proposal.

**SUMMARY OF TERMS AND CONDITIONS**

**Structure:** Tax Exempt Lease Purchase.

**Lessee:** City of Santa Fe Springs, CA

**Arranger/Placement Agent:** Public Sector Capital, LLC ("PSC")

**Lessor:** Banc of America, National Association or Designee

**Total Financing:** \$3,296,000

**Use of Proceeds:** Fire trucks and other associated handheld radio equipment.

**Security:** The Lessee will pledge to make lease payments from all legally available funds, and the payments will be subject to annual appropriations. The Lessor will be offered a first priority lien in the trucks & equipment.

**Term:** Seven Years

**Interest Rate:** 1.74%

**Tax Status:** Tax Exempt/Bank Qualified.

**Payments:** Seven annual payments in arrears.

**Closing Date:** on, or before, 10/30/20.

**Optional Redemption:** The Lease may be prepaid without penalty, on any scheduled payment date, after the first three years of the term.

**Disbursement of Proceeds:**

- The Lessor will fund directly to the vendor upon closing.
- A qualified reimbursement will be made to the Lessee.
- The transaction will fund to a mutually agreeable escrow agent.

**Acquisition/Escrow Account:** The money may be deposited into an escrow account acceptable to the Lessor, and disbursements will be made, from the account, upon execution and delivery of an Acceptance Certificate & approved invoices. The Lessor can provide escrow services to the Lessee if this is desired by the Lessee.

**Performance Bond:** A Performance Bond is standard in this type of transaction, and it will be required by the Lessor, prior to closing, with the Lessor listed on the Bond as Loss Payee.

**Closing Costs** *(All included in the financing and paid from proceeds at closing)*

- Documentation Fee: \$0
- Legal Fee: \$0
- Escrow Account Setup Fee: \$0
- Arranger/Placement Agent Fee: \$10,000

**Lessee's Documentation Expenses:** The Lessee will be responsible for its own legal & transactions costs in regards to documents and closing.

**Maintenance, Taxes and Insurance:** All maintenance, taxes and insurance in connection with the Projects and the Lease are the responsibility of the Lessee. The Lessee shall bear all risk of loss or damage to the Projects and shall be responsible for keeping the Projects insured with companies satisfactory to and for such amounts as required by Lessor. Lessor and its affiliates, successors and assigns must be named as loss payee and additional insured as applicable on all insurance policies. Evidence of such insurance must be satisfactory to Lessor.

**Documentation:** Documents shall be prepared by Lessor and will contain customary Representations and Warranties for transactions similar in amount and type. Lessee will provide a Legal/Validity Opinion, Form 8038-G, and an Authorizing Resolution. To facilitate closing, the Lessor requests a scan of all signed documents by 12:00 PM on the day prior to closing.

**Reporting Requirements:** Lessee shall deliver to Lessor(s) audited annual financial statements within 270 days of the end of each fiscal year.

**Events of Default:** The Events of Default will be standard and customary for transactions of this nature.

**Conditions Precedent:** Usual and customary conditions related to the issuance of tax-exempt financing, including acceptable legal documentation and standard approvals from the County, State and local officials, as may be required.

**Lessor Restrictions:** The Lessor has such knowledge and experience in financial and business matters that it is capable of evaluating the merits and risks of the 2020 Lease Agreement. The Lessor will be expected to sign an Investor Letter acknowledging the same.

**Governing Law:** All aspects of this financing being discussed, including this proposal, will be governed by the laws of California.

**Adverse Change & Other Credit Conditions:** If there is a material adverse change in the Lessee's financial condition, or if there are adverse circumstances of which Lessor(s) is currently unaware, Lessor(s) reserves the right to negotiate and/or terminate its interest in this transaction

at any time prior to closing. Additionally, this proposal is subject to final business, credit & legal consent by the Lessor.

**Role of Lessor:** Lessor is acting solely as Purchaser for its own account and not as a fiduciary for Issuer or in the capacity of broker, dealer, municipal securities underwriter or municipal advisor. Purchaser has not provided, and will not provide, financial, legal, tax, accounting or other advice to or on behalf of Issuer with respect to the proposed 2020 Lease Agreement. Issuer shall represent in the documentation that Issuer has sought and obtained financial, legal, tax, accounting and other advice (including as it relates to structure, timing, terms and similar matters) with respect to the proposed 2020 Lease Agreement from its financial, legal and other advisors (and not Purchaser) to the extent that Issuer desired to obtain such advice.

**Continued Disclosures:** The transaction described in this document is an arm's length, commercial transaction between each Lessor(s) and Lessee in which: (a) Lessor(s) is acting solely as a principal (i.e., as a Lessor(s)) and for its own interest; (b) neither Lessor(s) nor PSC is acting as a municipal advisor, agent or financial advisor to the Lessee, each has financial and other interests that differ from each other and from those of the Lessee, and as described herein PSC may receive compensation from the Lessor(s) that is contingent on the closing of the transaction and that may be reflected in the interest rate agreed to by the Lessee; (c) neither Lessor(s) nor PSC has a fiduciary duty pursuant to Section 15B of the Securities Exchange Act of 1934 to the Lessee with respect to this transaction and the discussions, undertakings and procedures leading thereto (irrespective of whether Lessor(s) or PSC (or its affiliates) has provided other services or is currently providing other services to the Lessee on other matters); (d) the only obligations Lessor(s) has to the Lessee with respect to this transaction will be set forth in the definitive transaction agreements between Lessor(s) and the Lessee; and (e) neither Lessor(s) nor PSC is recommending that the Lessee take an action with respect to the transaction described in this document, and before taking any action with respect to this transaction, the Lessee should discuss the information contained herein with its own legal, accounting, tax, financial and other advisors, as it deems appropriate. If the Lessee would like a municipal advisor in this transaction that has legal fiduciary duties to the Lessee, the Lessee is free to engage a municipal advisor to serve in that capacity.

**Expiration:** Please acknowledge acceptance of this proposal (by verbal or written communication) by 10/9/20.

Please feel free to contact me at 925.330.5860 if you would like to discuss this proposal. Upon written acceptance of this proposal, we will begin the closing process. Thank you for the opportunity to serve your financing needs.

Sincerely,



---

**Mark T. Stanley**  
Executive Director  
Public Sector Capital, LLC  
(M) 925.330.5860  
[mark.stanley@publicsectorcapital.com](mailto:mark.stanley@publicsectorcapital.com)



Accepted Date: \_\_\_\_\_

By: \_\_\_\_\_

Title \_\_\_\_\_

**Draft Payment Schedule**

Date	Payment	Interest	Principal	Balance
10/30/2020				3,296,000.00
10/30/2021	504,193.98	57,350.40	446,843.58	2,849,156.42
10/30/2022	504,193.98	49,575.32	454,618.66	2,394,537.76
10/30/2023	504,193.98	41,664.96	462,529.02	1,932,008.74
10/30/2024	504,193.98	33,616.95	470,577.03	1,461,431.71
10/30/2025	504,193.98	25,428.91	478,765.07	982,666.64
10/30/2026	504,193.98	17,098.40	487,095.58	495,571.06
10/30/2027	504,193.98	8,622.92	495,571.06	0.00
<b>Total</b>	<b>3,529,357.86</b>	<b>233,357.86</b>	<b>3,296,000.00</b>	