

## ARTICLE XV

### PERFORMANCE STANDARDS FOR INDUSTRIAL ZONES

SECTION 15.0 APPLICATION OF PERFORMANCE STANDARDS: After the effective date of this ordinance, any use established or changed to, and any building, structure, or tract of land developed, constructed or used for any permitted or permissible principal or accessory use in all industrial zones (I-1 and I-2) shall comply with all of the performance standards herein set forth for the district involved. If any existing use or building or other structure is extended, enlarged, or reconstructed, the performance standards for the district involved shall apply with respect to such extended, enlarged, or reconstructed portion or portions of such use or building or other structure.

SECTION 15.1 TIME SCHEDULE FOR COMPLIANCE OF PERFORMANCE STANDARDS: Except for standards regulated and enforced by the State of Kentucky, compliance with the provisions of this article of the ordinance shall be according to the following time schedule:

- A. All new installations shall comply as of going into operation.
- B. All existing installations not in compliance as of the effective date of the ordinance shall be in compliance within one (1) calendar year of the effective date of this ordinance unless the owner or person responsible for the operation of the installation shall have submitted to the zoning administrator a program and schedule for achieving compliance, such program and schedule to contain a date on or before which full compliance will be attained and such other information as the zoning administrator may require. If approved by the zoning administrator, such date will be the date on which the person shall comply.

The zoning administrator may require persons submitting such program to submit subsequent periodic reports on progress in achieving compliance.

SECTION 15.2 PERFORMANCE STANDARDS:

- A. **BUILDING ENCLOSURES:** In the I-1 and I-2 industrial districts, permitted uses shall be operated either within a completely enclosed building or within an area screened from view at the nearest district boundary, according to Section 9.17 and Article XIV of this ordinance.
- B. **LANDSCAPING:** In all industrial districts, all required yards shall either be open landscaped and grassed areas or be left in a natural state, if acceptable to the legislative body. If said area is to be landscaped, it shall be landscaped attractively with lawn, trees, shrubs, etc., according to the initially submitted plans which were first approved of for the development of such tract as a permitted use.

## Article XV Continued

In areas to be used for off-street parking, the parking arrangement and surfacing must likewise have been approved of for the development of such tract as a permitted use. Any landscaped areas shall be properly maintained thereafter in a sightly and well kept condition. Parking areas shall likewise be maintained in good condition. Any areas left in a natural state shall be properly maintained in a well kept condition.

- C. **NOISE:** For the purpose of measuring the intensity and frequencies of a sound, a sound level meter and an octave band analyzer shall be employed that conforms to specifications published by the American National Standards Institute (specifications for Sound Level Meters S1.4 – 1971, and Specifications for Octave, Half Octave and Third Octave Band Filter Sets S1.11 – 1966, American National Standards Institute, 1430 Broadway, New York, New York 10018, or the latest edition of such standards, shall be used). In the enforcement of the regulation, noises produced by the operation of motor vehicles or other transportation facilities shall not be included in determining the maximum permitted decibel level.

In the 1-1 district the sound pressure of noise radiated from any activity shall not exceed the values given in Table 3 of this section in any octave band frequency at any point on or beyond any lot line. If the 1-1 district adjoins a residential district, the maximum sound pressure level at any point on the district boundary shall be reduced by six decibels from the maximum listed in Table 3.

In the 1-2 district, the sound pressure of noise radiated from any activity shall not exceed the value given in Table 3 of this section in any octave band frequency at any point on or beyond the nearest district boundary. If said district adjoins a residential district, the maximum sound pressure shall be reduced by six (6) decibels from the maximum listed in Table 3 of this section.

In all districts, industrial noise shall be muffled so as not to become objectionable due to intermittence, beat, frequency, or shrillness.

- D. **ODOROUS MATTER:** No emission of odorous matter shall be allowed in excess of ambient air quality standards as set forth by regulations adopted by the Kentucky Department for Natural Resources and Environmental Protection, Division of Air Pollution, Cincinnati Air Quality Region.
- E. **Humidity, Heat or Glare:** In the 1-1 districts, any activity producing humidity, in the form of steam or moist air or producing heat or glare, shall be carried on in such a manner that the steam, humidity, heat or glare is not perceptible at any lot line. In the 1-2 district, any activity producing heat or glare shall be carried on in such a manner that the steam, humidity, heat or glare is not perceptible at or beyond any residential or commercial district boundary. Detailed plans for the elimination of humidity, heat or glare may be required before the issuance of a building permit.

TABLE 1

MAXIMUM PERMISSIBLE SOUND LEVEL AT SPECIFIED POINTS OF MEASUREMENT FOR NOISE RADIATED CONTINUOUSLY FROM A FACILITY

OCTAVE BAND (CYCLES PER SECOND)		SOUND PRESSURE LEVEL (DECIBELS*)
20 -	75 . . . . .	69
75 -	150 . . . . .	54
150 -	300 . . . . .	47
300 -	600 . . . . .	41
600 -	1,200 . . . . .	37
1,200 -	2,400 . . . . .	34
2,400 -	4,800 . . . . .	31
4,800 -	10,000 . . . . .	28
10,000 -	20,000 . . . . .	26**
20,000 -	30,000 . . . . .	25**
30,000 -	40,000 . . . . .	24**
40,000 -	50,000 . . . . .	23**

\* According to the following formula, Sound Pressure Level in Decibels equals 10 Log Where P2 equals 0.0002 dynes/cm2 P1/P2

\*\* To avoid possible interference with animal experiments.

TABLE 2

CORRECTION IN MAXIMUM PERMITTED SOUND PRESSURE LEVEL IN DECIBELS TO BE APPLIED TO TABLE 3

TYPE OF OPERATION OF CHARACTER OF NOISE	CORRECTION IN DECIBELS
Noise source operates less than 20% of any one hour period	plus 5*
Noise source operates less than 5% of any one hour period	plus 10*
Noise source operates less than 1% of any hour period	plus 15*
Noise of impulsive character (hammering, etc.)	minus 5

Article XV Continued

TYPE OF OPERATION OF CHARACTER OF NOISE	CORRECTION IN DECIBELS
Noise of periodic character	minus 5

\* Apply one of these corrections only.

TABLE 3

MAXIMUM PERMITTED SOUND PRESSURE LEVEL IN DECIBELS

OCTAVE BAND (CYCLES PER SECOND)	SOUND PRESSURE LEVEL (DECIBELS)*
0 - 74 . . . . .	79
75 - 149 . . . . .	74
150 - 299 . . . . .	66
300 - 599 . . . . .	59
600 - 1,199 . . . . .	53
1,200 - 2,399 . . . . .	47
2,400 - 4,799 . . . . .	41
4,800 and over . . . . .	39

\* According to the following formula, Sound Pressure Level in Decibels equals 10 Log where P2 equals 0.0002 dynes/cm<sup>2</sup> P1/P2

- F. EXTERIOR LIGHTING: Any lights used for exterior illumination, except for overhead street lighting and warning, or traffic signals shall direct light away from the adjoining zones.
- G. VIBRATION: Vibrations shall be measured at the lot line in the I-1 districts and at the nearest district boundary in the I-2 district. No vibration is permitted which is discernible to the human sense of feeling for three minutes or more duration in any one hour. Vibration shall not produce, at any time, an acceleration of more than 0.1 gravities or shall result in any combination of amplitudes and frequencies beyond the "safe" range of

Article XV Continued

Table 7, United States Bureau of Mines Bulletin No. 442, "Seismic Efforts of Quarry Blasting", on any structure. The methods and equations of said Bulletin No. 442, or any subsequent revision or amendment thereto, shall be used to compute all values for the enforcement of these provisions. Detailed plans for the elimination of vibrations may be required before the issuance of any building permit.

- H. EMISSIONS AND OPEN BURNING: No emission of particulate matter, sulphur compound, carbon monoxide, hydro-carbon, nitrogen oxide, and open burning shall be allowed in all industrial zones in excess of regulations adopted by the Kentucky Department for Natural Resources and Environmental Protection, Division of Air Pollution.
- I. RADIATION: In all industrial zones, all sources of ionizing radiation shall be registered or licensed by the Kentucky State Department of Health and operated in accordance with their regulations.
- J. ELECTRICAL RADIATION: In all industrial zones, any electrical radiation shall not adversely affect, at any point on or beyond the lot line, any operation or equipment other than those of the creation of the radiation. Avoidance of adverse effects from electrical radiation by appropriate single or mutual scheduling of operations is permitted.
- K. STORAGE: In the I-1 and I-2 zones, storage of materials, supplies, and products on the property outside the building, constructed thereon is permitted to the side and rear of the property providing that the storage of materials, supplies, and products are within an area screened from view at the nearest district boundary, in accordance with Section 9.17 and Article XV.
- L. FIRE AND EXPLOSIVE HAZARDS: In the I-2 zone only, storage, utilization, or manufacture of solid materials which requires free burning and intense burning may be allowed if permitted in said zones, providing that said materials or products shall be stored, utilized, or manufactured within completely enclosed buildings having incombustible walls and protected throughout by an automatic fire extinguishing system. In the I-2 zone only, the storage, utilization, or manufacture of flammable liquids, or materials which produce flammable or explosive vapors or gases may be allowed if permitted in said zones, provided that storage, handling, and use shall be in accordance with Standards of American Insurance Association for Storage, handling, and use shall be in accordance with Standards of American Insurance Association for Storage, Handling, and Use of Flammable Liquids, "American Insurance Association", Pamphlet No. 30, June, 1959, or any subsequent revision or amendment thereto.
- M. WASTE: Within the I-1 and I-2 zones, all waste shall be disposed of in accordance with the Solid Waste Regulations of the Kentucky Department of Natural Resources and Environmental Protection.

Article XV Continued

- N. MINING AND RECLAMATION: All methods of operation, construction of roads, backfilling, grading, blasting, water impoundments, treatment facilities, and reclamation must be in conformance with the regulations adopted by the Department for Natural Resources and Environmental Protection, Division of Reclamation. Any excavation or processing operations shall be subject to the regulation of the Kentucky Water Pollution Control Commission.
  
- O. BLASTING AND EXPLOSIVES: All blasting and the use of explosives must be conducted in accordance with the regulations set forth by the Department of Mines and Minerals, Division of Explosives and Blasting (pursuant to the authority of KRS 351.310 to 351.340 and 351.990) and in accordance with the Standards of Safety for Explosives, for the state of Kentucky, prepared by the Department of Public Safety, Division of Fire Prevention (pursuant to the authority of KRS 227.300).